

Specification Sheet

Part Number: T120R5H4

Engineered and manufactured for maximum performance and quality
Made from 100% high-quality plastic to ensure efficient recycling

Inside serration for a strong grip onto bundles

Easy application either manually or with a processing tool

Complies with MS3367-3-5, Class 1 and SAE-AS33671.



Heavy Duty MilSpec Cable Tie, 15" Long, MS3367, UL Rated, 120lb Tensile Strength, PA66, Green, 500/pkg

Article Number 111-12052

Type T120R

Color Green (GN)

Quantity Per bag

Product Description Heavy duty T-Series cable ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation. Specially manufactured to comply with Military Specification MS3367-3-5, Class 1 and SAE-AS33671.

| | |
|-------------------------------------|--|
| Short Description | Heavy Duty MilSpec Cable Tie, 15" Long, MS3367, UL Rated, 120lb Tensile Strength, PA66, Green, 500/pkg |
| Global Part Name | T120R-PA66-GN |
| Minimum Tensile Strength (Imperial) | 120.0 |
| Minimum Tensile Strength (Metric) | 535.0 |
| Length L (Imperial) | 15.0 |
| Length L (Metric) | 387.0 |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.30 |
| Width W (Metric) | 7.6 |
| Bundle Diameter Min (Imperial) | 0.20 |
| Bundle Diameter Min (Metric) | 5.0 |
| Bundle Diameter Max (Imperial) | 4.13 |

| | |
|-------------------------------|------------------------------------|
| Bundle Diameter Max (Metric) | 105.0 |
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| US MIL SPEC | MS3367-3-5, Class 1 SAE-AS33671 |
| Flammability | UL 94 V-2 |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | No |
| ROHS Compliant | Yes |
| Certification/Specification | UL 62275 |
| UL Recognized (US) | Yes |
| UL Listed (US and Canada) | Yes |
| UL Recognized (US and Canada) | Yes |
| UL Listed (US) | Yes |

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988