

## Specification Sheet

Part Number: T18L0C2

Engineered and manufactured for maximum performance and quality. Made from 100% high-quality plastic to ensure efficient recycling.

Inside serration for a strong grip onto bundles.

Easy application either manually or with a tensioning tool.

Bent tail allows for simpler insertion.



Article Number 111-00401

Type T18L

Color Black (BK)

Quantity Per bag

Product Description T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Cable Tie, 8" Long, UL Rated, 18lb Tensile Strength, PA66, Black, 100/pkg

|                                     |                 |
|-------------------------------------|-----------------|
| Global Part Name                    | T18L-PA66-BK    |
| Minimum Tensile Strength (Imperial) | 18.0            |
| Minimum Tensile Strength (Metric)   | 80.0            |
| Length L (Imperial)                 | 8.0             |
| Length L (Metric)                   | 205.0           |
| Identification Plate Position       | none            |
| Releasable Closure                  | No              |
| Tie Closure                         | plastic pawl    |
| Variant                             | Inside Serrated |
| Width W (Imperial)                  | 0.10            |
| Width W (Metric)                    | 2.5             |
| Bundle Diameter Min (Imperial)      | 0.06            |
| Bundle Diameter Min (Metric)        | 1.5             |
| Bundle Diameter Max (Imperial)      | 2.17            |
| Bundle Diameter Max (Metric)        | 55.0            |
| Thickness T (Metric)                | 1.1             |

|                               |                                  |
|-------------------------------|----------------------------------|
| Material                      | Polyamide 6.6 (PA66)             |
| Material Shortcut             | PA66                             |
| Flammability                  | UL 94 V-2                        |
| Halogen Free                  | Yes                              |
| UV Resistant (Yes/No)         | No                               |
| Operating Temperature         | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33)  | No                               |
| ROHS Compliant                | Yes                              |
| Certification/Specification   | UL 62275                         |
| UL Recognized (US)            | Yes                              |
| UL Listed (US and Canada)     | Yes                              |
| UL Recognized (US and Canada) | Yes                              |
| Package Quantity (Imperial)   | 100                              |
| Package Quantity (Metric)     | 100                              |

Customs Number

3926909988

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)