

Specification Sheet

Part Number: T30RA30000HS



The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs. Available in reels of 3,000 each or bandoliers of 30 each.

Cable Ties for AT2060, 30lb Tensile Strength, PA66HS, Black, 3000/reel

| | |
|---------------------|--|
| Article Number | 103-00004 |
| Type | T30RA |
| Color | Black (BK) |
| Quantity Per | reel |
| Product Description | Includes AT2060 tool, power supply, power cord, tool cord, and maintenance and operation manual. |
| Short Description | Cable Ties for AT2060, 30lb Tensile Strength, PA66HS, Black, 3000/reel |
| Global Part Name | T30RA-PA66HS-BK |

| | |
|-------------------------------------|---------|
| Minimum Tensile Strength (Imperial) | 30.0 |
| Minimum Tensile Strength (Metric) | 135.0 |
| Length L (Imperial) | 6.0 |
| Length L (Metric) | 152.4 |
| Identification Plate Position | none |
| Reel Diameter (Imperial) | 17.7 |
| Reel Diameter (Metric) | 450.0 |
| Reel Width (Imperial) | 7.197 |
| Reel Width (Metric) | 182.8 |
| Voltage Range | 27 Volt |
| Releasable Closure | No |
| Width W (Imperial) | 0.14 |
| Width W (Metric) | 3.6 |
| Bundle Diameter Min (Imperial) | 0.06 |
| Bundle Diameter Min (Metric) | 1.5 |
| Bundle Diameter Max (Imperial) | 1.25 |
| Bundle Diameter Max (Metric) | 31.75 |

| | |
|-------------------------------|--|
| Thickness T (Imperial) | 0.05 |
| Thickness T (Metric) | 1.2 |
| Cycle Time | 1.2 seconds |
| Tension Setting Tools | Adjustable |
| Power Supply | Electrical |
| Material | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HS |
| Flammability | UL 94 V-2 |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +257°F (-40°C to +125°C) |
| Reach Compliant (Article 33) | No |
| ROHS Compliant | Yes |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |

| | |
|-----------------------------|------------|
| Package Quantity (Imperial) | 3000 |
| Package Quantity (Metric) | 3000 |
| Customs Number | 3926909988 |
| Reel Weight (Imperial) | 7 |
| Reel Weight (Metric) | 3.175 |