

Specification Sheet

Part Number: T50R0PPC2

Polypropylene cable ties deliver excellent resistance to chemicals and salts.

Inside serrations provide strong grip on cables and wire bundles.

Easy application either manually or with a tensioning tool.

Bent tail ensures a quick and simple installation.



Cable Tie, 8" Long, 25lb Tensile Strength, PP, Black, 100/pkg

Article Number 111-04928

Type T50R

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's polypropylene cable ties offer added resistance to most chemicals. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Cable Tie, 8" Long, 25lb Tensile Strength, PP, Black, 100/pkg

| | |
|-------------------------------------|-----------------|
| Global Part Name | T50R-PP-BK |
| Minimum Tensile Strength (Imperial) | 25.0 |
| Minimum Tensile Strength (Metric) | 111.0 |
| Length L (Imperial) | 8.0 |
| Length L (Metric) | 202.0 |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.18 |
| Width W (Metric) | 4.6 |
| Bundle Diameter Min (Imperial) | 0.50 |
| Bundle Diameter Min (Metric) | 12.7 |
| Bundle Diameter Max (Imperial) | 1.75 |
| Bundle Diameter Max (Metric) | 44.5 |
| Thickness T (Imperial) | 0.05 |

| | |
|------------------------------|-----------------------------------|
| Thickness T (Metric) | 1.2 |
| Material | Polypropylene (PP) |
| Material Shortcut | PP |
| Flammability | UL 94 HB |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +239°F (-40°C to +115°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |

