

Specification Sheet

Part Number: 110-77004

- Cuts ties from 18 to 80 lb with a clean, flush cut for personnel safety and wire insulation integrity.
- Quality construction with impact-resistant housing, tested at over 1 million cycles, provides high durability resulting in fewer repairs and an extended product life.
- Lightweight tool with the most technologically advanced ergonomic design for reducing work-related risks such as fatigue and injury that affect productivity.
- Tension dial offers 33 precise, easy-to-read settings that reduce subjectivity or the need for fine tuning.
- Tension lock-in mechanism prevents operator from changing tension setting during critical applications.



EVO 7iSP Mechanical Hand Tool, Tension Range 4 - 37 lb, Short Hand Span, 1/pkg

Article Number	110-77004
Type	EVO7iSP
Color	Blue (BU) Black (BK)
Quantity Per	box

Product Description	HellermannTyton's EVO 7i industrial-grade, mechanical hand tool is ergonomically designed to reduce the risks of repetitive stress injuries to operators while simultaneously increasing productivity. The EVO 7i's Tension/Lock/Cut Technology delivers performance, safety and comfort for operators. Calibrated tensioning assures consistent wire bundle tension before flush cut-off. Available in a standard grip span (EVO 7i) or short grip span (EVO 7iSP) for smaller hands. Additional accessories are available.
Short Description	EVO 7iSP Mechanical Hand Tool, Tension Range 4 - 37 lb, Short Hand Span, 1/pkg
Global Part Name	EVO7iSP-MET/PL-BK/BU
Length L (Imperial)	7.5
Length L (Metric)	192
Tension Setting Tools	Adjustable
Material	Metal (MET) Plastic (PL)
Material Shortcut	MET PL
Use Conditions	For Indoor Use Only
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes

Package Quantity (Imperial)	1
Package Quantity (Metric)	1
Customs Number	8205599000

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.  
[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)