

Specification Sheet

Part Number: WSM60IMHSUVH1



Design makes installation along frame rails fast and easy
Using weld stud eliminates the need for grinding down painted surfaces
which saves time

Weld Stud eliminates need for stocking multiple sized metal P-Clamps
which saves time and cost

Weld Stud Mount, Max Bundle Diameter 6.0", Stud Diameter .24", PA66HIRHSUV, Black, 500/pkg

Article Number	151-00146
----------------	-----------

Type	WSM60
------	-------

Color	Black (BK)
-------	------------

Quantity Per	bag
--------------	-----

Product Description	When used in conjunction with a cable tie, the Weld Stud Mount significantly reduces time and labor, and eliminates the need for multiple sized P-clamps, nuts, and bolts. Simply weld the stud to the surface of any painted frame rail, and begin bundling with HellermannTyton cable ties. This eliminates the need in having to grind the surface in preparation. Adjusts to a wide variety of bundle diameters when used with HellermannTyton heavy duty T120, T250, T255 and Wide Strap Cable Ties.
---------------------	---

Short Description	Weld Stud Mount, Max Bundle Diameter 6.0", Stud Diameter .24", PA66HIRHSUV, Black, 500/pkg
Global Part Name	WSM60-PA66HIRHSUV-BK
Length L (Imperial)	1.32
Length L (Metric)	33.5
Width W (Imperial)	1.07
Width W (Metric)	27.2
Height H (Imperial)	1.06
Height H (Metric)	27.0
Cable Tie Width Max (Imperial)	0.51
Cable Tie Width Max (Metric)	13.0
Stud Diameter (Metric)	6.0 mm
Stud Diamater (Imperial)	0.24
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV

Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988