




T-WNB-3Y-208-P

WattNode 208-240VAC 2 or 3 Branch Circuit kWh Transducer Sensor

The WattNode sensor provides accurate kWh measurement at a low cost to meet your needs for sub-metering, net-metering, energy management, and performance contracting applications.

This WattNode kWh Transducer works with MagneLab AC Current Transformers and a Pulse Input Adapter, or a HOBO® Data Node pulse input port to provide True RMS kilowatt hours of energy used, even for loads with non-sinusoidal waveforms. Because these sensors tie directly into the line, they should be used only by qualified personnel. This model supports up to 3 separate 120 VAC single-phase branch circuits or individual 120 VAC phases of a 3-phase wye-connection 208/240 VAC circuit.



Key Advantages:

- Measures up to 3 separate branch circuits simultaneously, reducing complexity and cost.
- Use with wide choice of current transformers (sold separately) - ratings from 5 to 1500 amps.
- Accurate measurement of multiple single phase or each phase of 3-phase configurations.
- Easy to install and wire.
- Individual pulse outputs for each circuit - compatible with pulse input logger models.
- Small size - can be installed in existing service panels or junction boxes.
- Diagnostic LEDs - confirms proper installation for all phases.
- Line powered - no external supply required.
- Detachable terminal blocks - easy to install and remove.

HOBO T-WNB-3Y-208-P Sensor Specifications

Wye configuration ranges: 120, 208, 240 Volts AC - Neutral required

1 Phase 2 Wire 120V (with neutral)

1 Phase 3 Wire 120V/240V

3 Phase 4 Wire 120V/208V

Rating: FCC Class A

Operating: voltage range: $\pm 20\%$ of nominal

Frequency: 60 Hz

CT input: 0-0.5 VAC operating, 3 VAC maximum

Accuracy: $\pm 0.45\%$ of reading + 0.05% FS through 25th harmonic (dependent on CT used and line variation accuracy could be 1.5% to 4% of reading)

Enclosure: High impact, UL rated ABS plastic

Connectors: UL, cUL recognized, detachable screw terminals (14 AWG), 600V

Operating temp range: -30 to 60°C (-22 to 140°F)

Operating humidity range: 0 to 90% RH, non-condensing

Dimensions: 8.5 cm x 14.3 cm x 3.8 cm (3.3 in. x 5.6 in. x 1.5 in.)

Weight: 295 g (10.4 oz.)

Number of data channels: 3

Note: To download the manual from Continental Control Systems LLC [click here](#).

[Click here to view a typical installation](#)

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

▶ Email sales@onsetcomp.com

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-800-564-4377

▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

▶ Contact Product Support www.onsetcomp.com/support/contact

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation

470 MacArthur Boulevard

Bourne, MA 02532