



## HOBO<sup>®</sup> U24-002-C Data Logger

### Salt Water Conductivity/Salinity

A cost-effective data logger for measuring salinity, conductivity, and temperature in saltwater environments with relatively small changes in salinity ( $\pm 5,000$  S/cm) such as saltwater bays, or to detect salinity events such as upwelling, rainstorm, and discharge events. Data from this logger can be used with data from the HOBO U26 Dissolved Oxygen Logger for monitoring percent dissolved oxygen saturation.

Note: When monitoring salinity in waters with more than  $\pm 5,000$  uS/cm variation, refer to the accuracy shown in Plot C in the product specifications to determine if the accuracy is acceptable for your needs. Monthly field calibration readings are typically required to achieve the best accuracy.



#### Key Advantages:

- Non-contact sensor provides long life
- Provides easy access to sensor for cleaning and shedding air bubbles
- Two user-selectable ranges provide measurements from 100 to 55,000 uS/cm.
- Delrin housing will not corrode in saltwater
- HOBOware Pro software enables start/end-point calibration to compensate for any fouling and provides easy conversion to specific conductance and salinity using the Practical Salinity Scale 1978 (PSS-78)
- USB optical interface provides high-speed, reliable salinity data offload in wet environments
- Compatible with the HOBO Waterproof Shuttle for easy and reliable data retrieval and transport
- Non-contact sensor with titanium pentoxide coating, prevents the sensor from coming in contact with the water, thereby preventing tarnishing or corrosion associated with traditional electrode sensors; sensor coating is inert, so fouling can be easily wiped off the sensor

## HOBO U24-002-C Data Logger Specifications

**Measurements:** Actual Conductivity, Temperature, Specific Conductance at 25C (calculated), Salinity (calculated using PSS-78, the Practical Salinity Scale 1978)

Conductivity Measurement Range (Calibrated Range)

**High range:** 5000 to 55,000  $\mu\text{S}/\text{cm}$

**Low range:** 100 to 10,000  $\mu\text{S}/\text{cm}$

Over the range of 5 to 35C (41 to 95F)

**Temperature Measurement Range:** 5 to 35C (41 to 95F)

Specific Conductance Accuracy (in Calibrated Range using Conductivity Assistant and Calibration Measurements)

**Low range:** 3% of reading or 50  $\mu\text{S}/\text{cm}$ , whichever is greater

High range: 5% of reading, in waters within a range of  $\pm 3,000 \mu\text{S}/\text{cm}$ ; waters with greater variation can have substantially greater error (see Plot C)

Conductivity Resolution: 2  $\mu\text{S}/\text{cm}$

Temperature Accuracy: 0.1°C (0.2°F) at 25°C (77°F)

Temperature Resolution: 0.01°C (0.02°F)

**Conductivity drift:** Up to 12% sensor drift per month, exclusive of drift from fouling. Monthly start- and end-point calibration should be used with the HOBOWare Conductivity Assistant to achieve the specified Specific Conductance accuracy.

**Response time:** 1 second to 90% of change (in water)

**Operating range:** -2 to 36C (28 to 97F) – non-freezing

**Memory:** 18,500 temperature and conductivity measurements when using one conductivity range; 11,500 sets of measurements when using both conductivity ranges (64 KB total memory)

**Sample rate:** 1 second to 18 hrs, fixed or multiple-rate sampling with up to 8 user-defined sampling intervals

**Clock accuracy:** +/- 1 minute per month

**Battery life:** 3 years (@ 1 min logging)

**Maximum depth:** 70 m (225')

**Weight:** 193 gm (6.82 ounces), buoyancy in freshwater: -59.8 gm (-2.11 ounces)

**Size:** 3.18 cm diameter x 16.5 cm, with 6.3 mm mounting hole (1.25" diameter x 6.5", " hole)

**Wetted housing materials:** Delrin housing, epoxy, stainless steel retaining ring, polypropylene, Buna rubber O-ring, titanium pentoxide (inert coating over sensor) – all materials are suitable for long-term use in saltwater.

**CE compliance:** The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).

## Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email [sales@onsetcomp.com](mailto:sales@onsetcomp.com)
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

- ▶ Contact Product Support [www.onsetcomp.com/support/contact](http://www.onsetcomp.com/support/contact)
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation  
470 MacArthur Boulevard  
Bourne, MA 02532