



HOBO[®] UA-002-64 Data Logger

Pendant[®] Temperature/Light 64K

A miniature, waterproof, value-priced, two-channel temperature and relative light level data logger. Suitable for indoor, outdoor, and underwater applications, this logger holds approximately 52K measurements of 10-bit readings. For accurate temperature measurement in sunlight, a solar radiation shield is required (assembly-required RS1 Solar Radiation Shield or pre-assembled M-RSA Solar Radiation Shield). Note that using a solar radiation shield prevents the use of the light sensor.



Key Advantages:

- Low-cost temperature with alarm indication or light intensity
- Waterproof housing for wet or underwater use
- Data readout in less than 30 seconds via fast Optic USB interface

HOBO UA-002-64 Data Logger Specifications

Measurement Range

Temperature: -20° to 70°C (-4° to 158°F)

Light: 0 to 320,000 lux (0 to 30,000 lumens/ft²)

Accuracy

Temperature: ± 0.53°C from 0° to 50°C (± 0.95°F from 32° to 122°F), see Plot A in manual

Light intensity: Designed for measurement of relative light levels, see Plot D for light wavelength response

Resolution

Temperature: 0.14°C at 25°C (0.25°F at 77°F), see Plot A in manual

Drift: Less than 0.1°C/year (0.2°F/year)

Response Time

Airflow of 2 m/s (4.4 mph): 10 minutes, typical to 90%

Water: 5 minutes, typical to 90%

Time accuracy: ± 1 minute per month at 25°C (77°F), see Plot B in manual

Operating Range

In water/ice: -20° to 50°C (-4° to 122°F)

In air: -20° to 70°C (-4° to 158°F)

Water depth rating: 30 m from -20° to 20°C (100 ft from -4° to 68°F), see Plot C in manual

NIST traceable certification: Available for temperature only at additional charge; temperature range -20° to 70°C (-4° to 158°F)

Battery life: 1 year typical use

Battery Type: CR2032

Memory

UA-002-08: 8K bytes (approximately 3.5K combined temperature and light readings or events)

UA-002-64: 64K bytes (approximately 28K combined temperature and light readings or events)

Materials: Polypropylene case; stainless steel screws; Buna-N o-ring

Weight: 18 g (0.6 oz)

Dimensions: 58 x 33 x 23 mm (2.3 x 1.3 x 0.9 inches)

Environmental Rating: IP68

The CE Marking identifies this product as complying with the relevant directives in the European Union (EU).

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email sales@onsetcomp.com
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

- ▶ Contact Product Support www.onsetcomp.com/support/contact
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532