# SAFETY DATA SHEET

### 1. Identification

**Product identifier** Insulcast 125 Black - Part A

Other means of identification

SKU# IE132R Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

**ITW Performance Polymers** Company name 130 Commerce Drive **Address** Montgomeryville, PA 18936

**United States** 

**Telephone Customer Service** 215-855-8450

Website www.itwperformancepolymers.com

E-mail Not available. **EHS** Department **Contact person** 

**Emergency phone number CHEMTREC** 800-424-9300

International 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

**Health hazards** Skin corrosion/irritation Category 2

> Serious eye damage/eye irritation Category 2 Sensitization, skin Category 1 Category 2

**Environmental hazards** Hazardous to the aquatic environment,

long-term hazard

**OSHA** defined hazards Not classified.

Label elements



Signal word Warning

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to **Hazard statement** 

aquatic life with long lasting effects.

**Precautionary statement** 

Prevention Avoid breathing mist/vapor. Wash thoroughly after handling. Contaminated work clothing must not

be allowed out of the workplace. Avoid release to the environment. Wear eye protection/face

protection. Wear protective gloves.

If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Response

Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take

off contaminated clothing and wash before reuse. Collect spillage.

Store away from incompatible materials. Storage

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal** 

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: Insulcast 125 Black - Part A IE132R Version #: 03 Revision date: 06-25-2018 Issue date: 03-19-2014

#### Supplemental information

99.41% of the mixture consists of component(s) of unknown acute oral toxicity. 99.41% of the mixture consists of component(s) of unknown acute dermal toxicity. 50.97% of the mixture consists of component(s) of unknown acute inhalation toxicity. 99.41% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 50.32% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)		25068-38-6	30 - 60
Limestone		1317-65-3	30 - 60
Oxirane, Mono[(c12-14-alkyloxy)methyl] Derivatives [alkyl (c12-14) Glycidyl Ether]		68609-97-2	10 - 30
Crystalline SiO2 (Quartz)		14808-60-7	0.1 - 1
Other components below reportable le	evels		1 - < 3

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

**Specific methods**Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards**No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Insulcast 125 Black - Part A

IE132R Version #: 03 Revision date: 06-25-2018 Issue date: 03-19-2014

### Methods and materials for containment and cleaning up

Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

### **Environmental precautions**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

Components	Туре	Value	Form	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.	
Limestone (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.	
		15 mg/m3	Total dust.	
US. OSHA Table Z-3 (29 CFF	R 1910.1000)			
Components	Туре	Value	Form	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.	
		2.4 mppcf	Respirable.	
US. ACGIH Threshold Limit	Values			
Components	Туре	Value	Form	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.	
US. NIOSH: Pocket Guide to	Chemical Hazards			
Components	Туре	Value	Form	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.	
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.	
		10 mg/m3	Total	
logical limit values	No biological exposure limits noted for	or the ingredient(s).		
propriate engineering atrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.			
•	such as personal protective equipm			
Eye/face protection	Face shield is recommended. Wear s	safety glasses with side shields	(or goggles).	
Skin protection Hand protection	Wear appropriate chemical resistant	gloves.		
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.			
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.			
Thermal hazards	Wear appropriate thermal protective			

Material name: Insulcast 125 Black - Part A

SDS US

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

# 9. Physical and chemical properties

Liquid. **Appearance** Liquid. Physical state **Form** Liquid. Black. Color Slight. Odor

**Odor threshold** Not available. Not available. Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

> 200.0 °F (> 93.3 °C) Flash point

**Evaporation rate** Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Not available.

Flammability limit - upper

Explosive limit - lower (%) Not available.

Not available. Explosive limit - upper (%) Vapor pressure < 0.01 mm HgNot available. Vapor density Not available. Relative density

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** Not available. **Decomposition temperature** Not available. Not available. **Viscosity** 

Other information

13.17 Density

**Explosive properties** Not explosive.

Combustible IIIB estimated Flammability class

Not oxidizing. Oxidizing properties

Specific gravity 1.58 VOC 0

## 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Material name: Insulcast 125 Black - Part A

IE132R Version #: 03 Revision date: 06-25-2018 Issue date: 03-19-2014

SDS US

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

### 11. Toxicological information

### Information on likely routes of exposure

**Inhalation** No adverse effects due to inhalation are expected.

**Skin contact** Causes skin irritation. May cause an allergic skin reaction.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

#### Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

### Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline SiO2 (Quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Crystalline SiO2 (Quartz) (CAS 14808-60-7)

Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline SiO2 (Quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

# 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code**The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

### Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

#### DOT

Not regulated as dangerous goods.

#### IATA

UN3082 **UN number** 

Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin:--reaction Product Of **UN proper shipping name** 

Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))

Transport hazard class(es)

9 Class Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 9L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

Not established.

**IMDG** 

**UN** number UN3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:--reaction

Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)), MARINE POLLUTANT

Transport hazard class(es)

Class 9 Subsidiary risk Ш Packing group

**Environmental hazards** 


Marine pollutant Yes **EmS** F-A, S-F

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

IATA; IMDG



### Marine pollutant



General information

IMDG Regulated Marine Pollutant.

Material name: Insulcast 125 Black - Part A

SDS US

## 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Crystalline SiO2 (Quartz) (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard Skin corrosion or irritation

categories Serious eye damage or eye irritation Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

**US state regulations** 

California Proposition 65

WARNING: This product can expose you to Crystalline SiO2 (Quartz), which is known to the State of California

to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline SiO2 (Quartz) (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Crystalline SiO2 (Quartz) (CAS 14808-60-7)

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Material name: Insulcast 125 Black - Part A

SDS US

IE132R Version #: 03 Revision date: 06-25-2018 Issue date: 03-19-2014

Country(s) or region Inventory name On inventory (yes/no)\*

Taiwan Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

Issue date 03-19-2014 06-25-2018 **Revision date** 

Version # 03

Health: 2 **HMIS®** ratings

Flammability: 1 Physical hazard: 1

Health: 2 NFPA ratings

Flammability: 1 Instability: 1

ITW Performance Polymers cannot anticipate all conditions under which this information and its Disclaimer

> product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

**Revision information** This document has undergone significant changes and should be reviewed in its entirety.

IE132R Version #: 03 Revision date: 06-25-2018 Issue date: 03-19-2014