Keysight Technologies 83059 Precision 3.5 mm Coaxial Adapters DC - 26.5 GHz

Technical Overview



Introduction

Outstanding Performance

You don't have to sacrifice measurement integrity when using general purpose adapters and connector savers. The Keysight Technologies, Inc. 83059 instrument grade 3.5 mm coaxial adapters offer outstanding performance to 26.5 GHz. With SWR typically better than 1.05, these adapters are ideal for most connector saver and interconnect needs.

Applications

Out-of-spec SMA and poor quality 3.5 mm connectors can cause considerable damage to expensive test port connectors. To help protect your test port connectors from damage, use 83059 adapters. These adapters offer test port safety without compromising accuracy.

You can use the 83059 adapters to perform adapter swap calibrations when testing non-insertable devices on network analyzers.

For general purpose test and measurement applications, the 83059 adapters offer far better performance than most instrument grade adapters available today.

Features

- Low SWR
- Excellent repeatability
- Low loss
- Precision "instrument grade"
 3.5 mm coax connectors
- Ideal connector savers

Convenient Kits

Damaged adapters can damage your test ports. The 83059 adapters are available in kits of three, packaged in protective foam to help reduce damage and are supplied in an attractive wooden box you can use to store them in so there's less chance of losing your adapters.

Specifications

Specifications describe the instrument's warranted performance over the temperature range 0 to 55° C (except where noted). Supplemental Characteristics are intended to provide information useful in applying the instrument by giving typical but nonwarranted performance parameters. These are denoted as "typical," "nominal," or "approximate."

Performance characteristics¹

Model number	Connector type ²	Frequency (GHz)	Typical min. return loss	Typical max. insertion loss ^{3,4}
83059A	3.5 mm (m-m)	DC - 26.5	– 32 dB	0.074 dB
83059B	3.5 mm (f-f)	DC - 26.5	– 32 dB	0.074 dB
83059C	3.5 mm (m-f)	DC - 26.5	– 32 dB	0.074 dB
83059K (kit)	3.5 mm (m-m) (f-f), (m-f)	DC - 26.5	– 32 dB	0.074 dB


1. Typical values are defined as 2 from the mean.

2. m = plug, f = jack

3. Typical measurements were taken from the f-f 83059B; they represent the worst case for the Keysight 83059 family.

 Insertion loss values were derived using a short circuit technique; values displayed are half the measured "round trip" values.

"Instrument Grade" connectors are intended for use with precision test and measurement equipment where maintaining high performance through many connect/disconnect cycles is of paramount importance. They feature the traditional slotted female contacts, rather than the slotless design used by "Metrology Grade" connectors.



Dimensions in millimeters Net Weight: 14 Grams each

Evolving Since 1939

Our unique combination of hardware, software, services, and people can help you reach your next breakthrough. We are unlocking the future of technology. From Hewlett-Packard to Agilent to Keysight.







myKeysight

myKeysight

www.keysight.com/find/mykeysight

A personalized view into the information most relevant to you.

http://www.keysight.com/find/emt_product_registration

Register your products to get up-to-date product information and find warranty information.

KEYSIGHT SERVICES Accelerate Technology Adoption. Lower costs.

Keysight Services www.keysight.com/find/service

Keysight Services can help from acquisition to renewal across your instrument's lifecycle. Our comprehensive service offerings—one-stop calibration, repair, asset management, technology refresh, consulting, training and more—helps you improve product quality and lower costs.



Keysight Assurance Plans

www.keysight.com/find/AssurancePlans

Up to ten years of protection and no budgetary surprises to ensure your instruments are operating to specification, so you can rely on accurate measurements.

Keysight Channel Partners

www.keysight.com/find/channelpartners

Get the best of both worlds: Keysight's measurement expertise and product breadth, combined with channel partner convenience.

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: www.keysight.com/find/contactus

Americas

Canada	(877) 894 4414		
Brazil	55 11 3351 7010		
Mexico	001 800 254 2440		
United States	(800) 829 4444		

Asia Pacific

Australia 1 800 629 485 800 810 0189 China 800 938 693 Hong Kong India 1 800 11 2626 Japan 0120 (421) 345 Korea 080 769 0800 1 800 888 848 Malaysia Singapore 1 800 375 8100 0800 047 866 Taiwan Other AP Countries (65) 6375 8100

Europe & Middle East

United Kingdom

For other unlisted countries: www.keysight.com/find/contactus (BP-9-7-17)

0800 0260637



www.keysight.com/go/quality Keysight Technologies, Inc. DEKRA Certified ISO 9001:2015 Quality Management System

This information is subject to change without notice. © Keysight Technologies, 2017 Published in USA, December 2, 2017 5952-2836E www.keysight.com

