

BROCHURE

# Digital Multimeters



## Index

Model	Description	Digits of resolution	Measurement speed (reading/s at 4½ digits)	Basic 1-yr DCV accuracy	Basic measurements	Connectivity & software	Page:
 U3401A/U3402A	Benchtop DMM, dual display  Elegantly simple and affordable DMMs with basic and good capabilities	4½ (U3401A) 5½ (U3402A)	N/A	0.0120%	DCV, ACV, DCI, ACI, 2-wire resistance (4-wire on U3402A), frequency, continuity, and diode	N/A	4
 U3606A/U3606B	5.5-digit DMM with built-in 30 W power supply  Halves bench/rackspace need for two instruments	5½	26	0.0250%	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, frequency, continuity, diode, and capacitance  30-W with four output ranges, OVP/OCV, auto scan/ramp and square wave generator	USB 2.0, GPIB	5
 34450A	5.5 digit bench digital multimeter  OLED dual display	5½	190	0.0150%	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, frequency, continuity, diode, capacitance, and temperature	USB 2.0, Serial Interface (RS-232), GPIB BenchVue software enabled (page 25)	6
 34460A/34461A	Bench/System DMM  Graphical color dual-line display with histogram and trend charts	6½	300/1000	0.0075/0.0035%	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, frequency, period, continuity, diode, temperature, capacitance	USB, LAN/LXI Core, GPIB, BenchVue software enabled (page 25)	7
 34465A	Bench/System DMM  Includes 34461A features plus data logging, digitizing and auto calibration	6½	50,000	0.0030%	DCV, ACV, DCI, ACI, 2- and 4-wire, resistance, frequency, period, continuity, diode, temperature, capacitance, DC ratio	USB, LAN/LXI Core, GPIB optional, BenchVue software enabled (page 25)	8
 34470A	Bench/System DMM  Includes 34461A features plus data logging, digitizing and auto calibration	7½	50,000	0.0016%	DCV, ACV, DCI, ACI, 2- and 4-wire, resistance, frequency, period, continuity, diode, temperature, capacitance, DC ratio	USB, LAN/LXI Core, GPIB optional, BenchVue software enabled (page 25)	8
 34401A*	Bench/System DMM  Industry standard for accuracy, speed, measurement ease and versatility	6½	1000	0.0035%	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, frequency, period, continuity, and diode.	GPIB, RS-232, DMM Connectivity BenchVue software enabled (page 25)	9
 34410A/34411A*	Bench/System DMM, dual-line display  Highest through-put of benchtop DMMs	6½	10,000 (34410A) 50,000 (34411A)	0.0030%	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, frequency, period, continuity test, capacitance, temperature	USB, LAN/LXI Core, GPIB, BenchVue software enabled (page 25)	10
 34420A	Nanovolt/μΩ meter  Very accurate, low-level measurements	7½	250	0.0030%	DCV, DCI, 2- and 4-wire resistance, 2 channel scanning, temperature	GPIB, RS-232, Intuilink software	11

\*NOTICE: The 34401A, 34410A, 34411A products will be discontinued December 1, 2016. For migration details visit: [www.keysight.com/find/nextgenDMMs](http://www.keysight.com/find/nextgenDMMs)

## Index

Model	Description	Digits of resolution	Measurement speed (reading/s at 4½ digits)	Basic 1-yr DCV accuracy	Basic measurements	Connectivity & software	Page:
 3458A	Bench/System DMM The fastest, most flexible and most accurate multimeter by Keysight. Ideal multimeter for demanding applications	8½	100000 (@ 4½ digits)	0.0008% (0.0004% optional)	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, frequency, period, and temperature	GPIO	12
 U1177A/ U1117A	Infrared (IR)-to-Bluetooth Adapter Enables Bluetooth connection to compatible Keysight handhelds.	N/A	N/A	N/A	N/A	Keysight Mobile Meter  Keysight Mobile Logger	13
 U1190 Series	Handheld DMM Illuminate test area and measure in safer manner	3½	3	0.5%	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, frequency, period, continuity, diode, capacitance, temperature	N/A	14
 U1210 Series	Handheld clamp meter For convenient high current measurements	3½	7	0.5%	DCV, ACV, DCI, ACI, 2-wire resistance, frequency, continuity, diode test, capacitance, temperature	IR-USB, <i>Bluetooth</i>	15
 U1230 Series	Handheld DMM Retool your expectations with the Keysight U1230 Series handheld DMM	3½	5	0.5%	DCV, ACV, DCI, ACI, resistance, frequency, continuity, diode test, capacitance, temperature	IR-USB, <i>Bluetooth</i>	16
 U1240B Series	Handheld DMM Feature-rich and robust DMMs	4	7	0.09%	DCV, DCI, ACV, ACI, 2-wire resistance, frequency, continuity, diode test, switch counter, harmonic ratio, capacitance, temperature, 4-20 mA % scale	IR-USB, <i>Bluetooth</i>	17
 U1240C Series	Handheld DMM Perform test confidently and efficiently	4½	5	0.09%	DCV, DCI, ACV, ACI, 2-wire resistance, frequency, continuity, diode test, switch counter, harmonic ratio, capacitance, temperature, 4-20 mA % scale	IR-USB, <i>Bluetooth</i>	18
 U1250 Series	Handheld DMM Versatile, high performance DMMs	4½	7	0.025%	DCV, DCI, ACV, ACI, 2-wire resistance, frequency, continuity, diode test, dB, capacitance, temperature, frequency counter, 4-20 mA % scale	IR-USB, <i>Bluetooth</i>	19
 U1270 Series	Handheld DMM More functionality in a single tool	4½	7	0.05%	DCV, DCI, ACV, ACI, 2-wire resistance, frequency, continuity, diode test, dB, capacitance, temperature, 4-20 mA % scale	IR-USB, <i>Bluetooth</i>	20
 U1280 Series	Handheld DMM Trustworthy measurements in the palm of your hand	4½	5	0.025%	DCV, DCI, ACV, ACI, 2-wire resistance, frequency, continuity, diode test, dB, capacitance, temperature, 4-20 mA % scale	IR-USB, <i>Bluetooth</i>	21
 U1401B	Handheld multi-function calibrator/meter Calibrator and DMM in one tool	4½	3	0.003%	DCV, ACV, DCI, ACI, 2-wire resistance, temperature, frequency, diode test, continuity, pulse width, duty cycle	IR-USB	22
 U2741A	USB Modular DMM Compact, with plug-and-play simplicity	5½	100	0.02%	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, frequency and period, continuity, diode test, temperature	USB 2.0	23
 M9181A	PXI DMM - basic features. Best for functional test when there are multiple tests with range or function changes.	6½	150	.009%	DCV, DCI, ACV, ACI, 2- and 4-wire resistance	PXI module; IVI-C, IVI-COM, LabVIEW, MATLAB drivers. Signametrics compatible driver is also available	24
 M9182A/M9183A	PXI DMM - enhanced performance models. Best for functional test when there are multiple tests with range or function changes.	6½	4,500 for M9182A 15,000 for M9183A	.004%	All M9181A measurements, plus frequency/period, capacitance, and temperature. M9183A includes duty cycle, counter/totalizer, and DC source.	PXI-hybrid module; IVI-C, IVI-COM, LabVIEW, MATLAB drivers. Signametrics compatible driver is also available	24
Accessories Compatibility Chart							25 - 26
BenchVue Software							27


## Basic + good = elegant simplicity

U3400 Series 4½ and 5½ digit multimeters



### Key features

- Up to 120,000 counts resolution
- Up to six built-in math functions – dBm, Relative, Min/Max, Compare, Hold
- Dual display on bright VFD
- Selectable resolutions for variable measurement speeds
- Kensington lock slot security



### Key specifications

DCV accuracy	0.02%
Reading speed	N/A
Measurement functions	DCV, ACV, DCI, ACI, 2-wire and 4-wire resistance, frequency, diode, continuity
Type of connectivity	N/A

Technical datasheet:  
Literature number 5990-3970EN

### Ordering information

U3401A 4½ digit dual display digital multimeter  
U3402A 5½ digit dual display digital multimeter

Each U3400 Series includes:

- Quick start guide
- Product reference CD
- Certificate of calibration (CoC)
- 34138A test lead kit
- AC power cord

Options:

- U3400A-100 USB to RS232 cable
- U3400A-1CM Rack mount kit
- U3400A-1CN Dual flange kit



## Two instruments in one

U3606A/U3606B multimeter|DC power supply




### Key features

Full-featured DMM

- 8 built-in math functions
- 120,000 counts resolution
- 4-wire  $m\Omega$  measurement with 0.001  $m\Omega$  resolution

Full-featured DC power supply

- 30 W, 30 V/1 A, 100 mA/30 V, 8 V/3 A and
- 1000 mV/3 A ranges
- OVP and OCP load protection
- Auto ramp and scan for multi-level DC bias testing
- Up to 4.8 kHz square-wave output



### Key specifications

DCV accuracy	0.025%
Reading speed	26 readings/second
Measurement functions	DCV, ACV, DCI, ACI, 2-wire and 4-wire resistance, frequency, diode, continuity, and capacitance
Type of connectivity	GPIO, USB 2.0

Technical datasheet:

Literature number 5991-2849EN

### Ordering information

U3606A 5½ digit digital multimeter|DC power supply  
U3606B 5½ digit digital multimeter|DC power supply

Each unit includes:

- Quick start guide
- Product reference CD
- Keysight Technologies, Inc. IO Library Suite
- Certificate of calibration
- U8201A combo test lead kit
- USB 2.0 high-speed type A to type B cable
- AC power cord

## Turbo charge your measurements with one of the fastest tools in its class


### 34450A bench digital multimeter



#### Key features

- Fast reading speed up to 190 readings/sec
- Multiple connectivity options – USB 2.0, Serial
- Interface (RS-232) and GPIB
- Up to 50,000 memory points for data logging
- Built-in histogram function
- With Fluke 45 and Fluke 8808A code compatibility


5.5 digit OLED dual display allows clear and quick view of measurements




Fast 190 readings/sec and 0.015% DCV accuracy to help you achieve throughput breakthrough

Input terminals

Kensington lock to better secure the unit



Multiple choices of connectivity and trigger in/out capability for production data analysis



Eleven measurement functions

Up to 50,000 memory points for data logging and histogram function

Built-in math functions

#### Key specifications

DCV accuracy	0.015%
Reading speed	190 readings/s
Measurement functions	DCV, ACV, DCI, ACI, 2-wire and 4-wire resistance, frequency, diode, continuity, capacitance, temperature
Type of connectivity	USB 2.0, Serial Interface (RS-232) and GPIB

Technical datasheet:  
Literature number 5991-1133EN

#### Ordering information

34450A 5½ digit dual display digital multimeter

Each 34450A includes:

- Test lead kit
- Power cord
- USB interface cable
- Quick start guide
- Product reference CD
- Keysight IO Library Suite CD-ROM

Upgradable options:

- 3445GPBU GPIB connectivity upgrade
- 3445MEMU 50,000 memory points upgrade for data logging
- BenchVue software enabled

# The new standard for uncompromising performance in bench and system test

## 34460A/34461A 6½ digit Truevolt DMMs



### Key features

Display DMM results in ways you never have before

- Color, graphical display with built-in bar chart, histogram, trend (34461A only), math, and statistics
- Save and document your DMM's data from your PC, mobile device, or IO of choice


Measure with unquestioned Truevolt confidence

- Digital AC, lowest measurement noise, ISO/IEC derived and compliant specifications

- 1000 V max voltage input, 3 A/10 A (34461A) max current input

Move to the next generation 34401A DMM with 100% assurance

- Industry's only 100% drop-in, SCPI compatible replacement for the Keysight 34401A DMM (34461A)



### Key specifications

DCV accuracy	0.0075/0.0035%
Reading speed – 4½ Digits	300/1000 readings/s
Measurements	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, frequency, period, diode, continuity, temperature
Type of connectivity	USB, LAN/LXI Core (Option on 34460A, Std on 34461A) GPIB (Optional)

Technical datasheet:

Literature number 5991-1983EN

### Ordering information

34460A 6½ digit, basic Truevolt DMM

34461A 6½ digit, 34401A replacement, Truevolt DMM

Upgradeable options:

- 3446ACCU – Accessory kit for 34460A (documentation, test leads, USB cable)
- 3446GPBU – GPIB user installable interface module
- 3446LANU – Enable rear panel LAN/LXI web interface, external triggering for 34460A
- 3446SECU – Enable NISPOM and file security
- BenchVue software enabled (see page 25)

# The new standard for uncompromising performance in bench and system test

34465A 6½, 34470A 7½ digit performance Truevolt DMMs



## Key features

### Get more insight quickly


**Truevolt** DMM's graphical capabilities such as trend and histogram charts offer more insights quickly. Both models also provide a data logging mode for easier trend analysis and a digitizing mode for capturing transients.

### Low-current measurements

The ability to measure very low current, 1 µA range with pA resolution, allows you to make measurements on very low power devices.

### Maintaining calibration

Auto calibration allows you to compensate for temperature drift so you can maintain measurement accuracy throughout your workday.



## Key specifications

DCV accuracy	0.0030/0.0016%
Reading speed – 4½ Digits	50,000 readings/s
Measurements	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, frequency, period, diode, continuity, temperature capacitance, DC ratio
Type of connectivity	USB, LAN/LXI Core GPIB (Optional)

Technical datasheet:  
Literature number 5991-1983EN

## Ordering information

34465A 6½ digit, performance Truevolt DMM (34410A/11A replacement)

34470A 7½ digit, performance Truevolt DMM

### Upgradeable options:

- 3446GPBU – GPIB user installable interface module
- 3446SECU – Enable NISPOM and file security
- 3446DIGU – Enable digitizing and advanced triggering
- 3446MEMU – Enable 2 million readings of memory
- BenchVue software enabled



## Uncompromising performance for benchtop and system testing



34401A 6½ digit multimeter (Replaced by 34461A 61/2 digit Truevolt multimeter)

NOTICE: The 34401A DMM will be discontinued December 1, 2016.  
For migration details visit: [www.keysight.com/find/nextgenDMMs](http://www.keysight.com/find/nextgenDMMs)

### Key features

- 1000 V maximum input
- SCPI commands standard
- Intuilink Connectivity Software included



### Key specifications

DCV accuracy	0.0035%
Reading speed – DCV	1000 readings/second
Measurements	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, diode, continuity
Type of connectivity	GPIB, RS-232

Technical datasheet:

Literature number 5968-0162EN

### Ordering information

34401A 6½ digit digital multimeter

Each 34401A includes:

- Test lead kit with probe, alligator and grabber
- Operating manual
- Service manual
- Certificate of calibration
- Test report
- AC power cord

BenchVue software enabled



## Affordable yet feature-rich measurement tool

### 34410A/34411A 6½ digit multimeter

NOTICE: The 34410A/34411A DMMs will be discontinued December 1, 2016.  
For migration details visit: [www.keysight.com/find/nextgenDMMs](http://www.keysight.com/find/nextgenDMMs)




#### Key features

Keysight 34410A 6½ digit high-performance DMM

- Expanded measurement ranges
- Data logger with 50k reading non-volatile memory

Keysight 34411A 6½ digit enhanced-performance DMM

- All features of the 34410A plus:
- 50,000 readings/s at 4½ digits direct to PC
- 1 million volatile reading memory
- Analog level triggering
- Programmable pre/post triggering



#### Key specifications

DCV accuracy	0.0030%
Reading speed – DCV	34410A 10,000 readings/s 34411A 50,000 readings/s
Measurements	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, continuity, diode, capacitance, temperature
Type of connectivity	GPIB, USB 2.0, LAN (LXI Core)

Technical datasheet:

Literature number 5989-3738EN

#### Ordering information

34410A 6½ digit digital multimeter

34411A 6½ digit digital multimeter

Each 34410A/34411A includes:

- Test lead kit with probes and SMT attachments
- Test report
- AC power cord
- USB interface cable

BenchVue software enabled (see page 25)


## Nanovolt performance at a micro-volt price

34420A 7½ digit multimeter



### Key features

- 100 pV/ 100 nV/2 sensitivity
- 1.3 nVrms/8 nVpp noise performance
- Built-in low noise 2-channel scanner
- Direct SPRT, RTD, thermistor, and thermocouple measurements



Three resistance modes are included:

- Standard
- Low-power
- Voltage-limited for dry-circuit testing

Selectable analog or digital filtering

Built-in low noise two channel scanner with ratio and difference functions

### Key specifications

DCV accuracy	0.0030%
Reading speed – DCV	250 readings/s
Measurements	DCV, 2- and 4-wire resistance, temperature
Type of connectivity	GPIO, RS-232

Technical datasheet:  
Literature number 5968-0161EN

### Ordering information

34420A nanovolt/micro-ohm meter

Each 34420A includes:

- Low-thermal input cable (34102A)
- Low-thermal shorting plug (34103A)
- Kelvin clip set (11062A)
- Operating manual
- Service manual
- Quick reference guide
- Test report with cal


# Shattering performance barriers of speed and accuracy

## 3458A 8½ digit multimeter



### Key features

- Maximum sensitivity: 10 nV
- Programmable integration times from 500 ns to 1 sec
- Two-source (10 V, 10 kΩ) calibration, including AC
- Self-adjusting, self-verifying auto-calibration for all functions and ranges, including AC
- Multimeter Language (ML) compatible



### Key specifications

DCV accuracy	0.0008% (Optional 0.0004%)
Reading speed DVC	Up to 100,000 readings/second (41/2 digits)
Measurements	DCV, ACV, DCI, ACI, 2-wire and 4-wire resistance, frequency
Type of connectivity	GPIOB

Technical datasheet:  
Literature number 5965-4971E

### Ordering information

3458A multimeter

- Each 3458A includes:
- Test lead set (34118B)
  - Power cord
  - Operating manual
  - Calibration manual
  - Assembly level repair manual
  - Quick reference guide

# Go further with Keysight handheld digital multimeters

## Keysight Remote Link Solution

The remote link is Keysight Technologies, Inc. next generation wireless connectivity. With the new U1117A Infrared (IR)-to-*Bluetooth*® adapter and U1115A remote logging display, you can safely measure, view and log test measurements with an extended range of up to 100 meters. You can now log and monitor data on more display

devices such as iOS / Android-based smart devices or on a Windows-based PC. By simply attaching the U1177A / U1117A IR-to-*Bluetooth* adapter to the IR port of a Keysight handheld meter, you'll get instant wireless *Bluetooth* connection setup.


### Key features

- Extended measurement distance of up to 100 meters
- View readings of up to four handheld meters simultaneously
- Compatible across all existing Keysight U1200 series handheld meters
- 60,000 points interval logging<sup>1</sup>
- Download logged data to a PC via *Bluetooth* connection<sup>1</sup>
- Micro USB external power port<sup>1</sup>
- Indoor and outdoor viewing modes<sup>1</sup>

1. U1115A



Keysight U1177A Infrared (IR)-to-*Bluetooth* adapter



Keysight wireless remote connectivity solution



# Ergonomically designed for safer measurements

## U1190 Series handheld clamp meters



### Key features

- Vsense to perform non-contact voltage detection<sup>1</sup>
- Built-in LED flashlight to illuminate test area<sup>1</sup>
- Current measurement up to 600 A<sup>2</sup>
- Digital multimeter (DMM) with Resistance, Capacitance<sup>1</sup>, DCV, ACV, DCμA<sup>3</sup>, ACμA<sup>3</sup>, Continuity and Diode test measurements
- CAT III 600 V / CAT IV 300 V overvoltage protection

1. Only for U1192A, U1193A and U1194A

2. Only for U1193A and U1194A

3. Only for U1194A



1. Exclusive to U1192A, U1193A, and U1194A

2. Exclusive to U1194A

### Key specifications

DCV accuracy	0.5+3
Reading speed	3 readings/s
Measurement functions	DCV, ACV, DCI, ACI, resistance, capacitance, diode test, temperature, frequency, continuity
Type of connectivity	N/A

Technical datasheet:

Literature number 5990-8646EN

### Ordering information

U1191A clamp meter

U1192A clamp meter

U1193A clamp meter

U1194A clamp meter

Each handheld includes:

- Certificate of calibration
- Quick start guide
- K-type thermocouple (only for U1194A)
- 1.5 V AAA alkaline battery
- Soft carrying case
- Test leads with 4-mm tips
- Test report with cal



Built-in LED flashlight to illuminate test area



## Handle big currents – safely

### U1210 Series handheld clamp meters



#### Key features

- Large clamp opening of 52 mm or 2"
- High measurement capability of up to 1000 A for AC, DC or AC+DC
- CAT III 1000 V/CAT IV 600 V overvoltage protection
- Includes full-featured DMM with resistance, capacitance, frequency and temperature functions
- High resolution measurements – measure current as low as 0.01 A

Bluetooth wireless connectivity (optional U1177A Infrared (IR)-to-Bluetooth Adapter required)



Capacitance/diode measurement  
Temperature and audible continuity  
functions

High measurement capability of up to  
1000 A for AC, DC or AC+DC

Peak hold function for  
in-rush current testing



Large jaw opening of 2" to test  
thick current sources

Max or Min recording capability

Large LCD display with maximum  
reading of 4000 counts

Manual or auto ranging

#### Key specifications

DCV accuracy	0.50%
Reading speed	7 readings/s
Measurements	DCV, ACV, DCI, ACI, 2-wire resistance, capacitance, temperature, frequency, diode test, continuity
Type of connectivity	IR-USB and Bluetooth

Technical datasheet:  
Literature number 5990-5083EN

#### Ordering information

U1211A clamp meter  
U1212A clamp meter  
U1213A clamp meter

Each clamp meter is shipped with::

- Test leads with 4-mm tips
- Soft carrying case
- Standard alkaline 9 V battery
- Quick start guide
- Certificate of calibration

## Robust and feature-packed

### U1230 Series handheld digital multimeters



#### Key features

- Built-in LED flashlight to illuminate test area
- Flashing backlight as additional visual alert during continuity tests in noisy areas
- Vsense performs non-contact voltage detection
- Data logging capability (stores up to 10 readings)
- IR-to-USB connectivity to transfer data to PC for record

Bluetooth wireless connectivity (optional U1177A Infrared (IR)-to-Bluetooth Adapter required)



#### Key specifications

DCV accuracy	0.5%+2
Reading speed	5 readings/s
Measurement functions	DCV, ACV, ACI, DCI, diode test, capacitance, resistance, temperature*, frequency, continuity test *Applies to U1233A only
Type of connectivity	IR-USB and Bluetooth

Technical datasheet:  
Literature number 5990-7550EN

#### Ordering information

U1231A digital multimeter  
U1232A digital multimeter  
U1233A digital multimeter

Each handheld comes with:

- Quick start guide
- Certificate of calibration
- U1167A 4 mm tips probes test leads
- 4 x 1.5 V batteries

## Check more, fix more, spend less

### U1240B Series handheld multimeters



#### Key features

- True RMS AC measurement
- Advanced functions – capacitance, temperature, MINMAX recording
- Manual data logging (U1242B only)
- Built-in switch counter, harmonic ratio (U1242B only), dual/differential temperature capabilities (U1242B only)
- CAT III 1000 V and CAT IV 600 V overvoltage protection

Bluetooth wireless connectivity (optional U1177A Infrared (IR)-to-Bluetooth Adapter required)



#### Key specifications

DCV accuracy	0.09%
Reading speed	7 readings/s
Measurement functions	DCV, ACV, DCI, ACI, 2-wire resistance, frequency, capacitance, temperature, diode, continuity tests
Type of connectivity	IR-USB and Bluetooth

Technical datasheet:  
Literature number 5989-7040EN

#### Ordering information

U1241B digital multimeter  
U1242B digital multimeter

Each handheld comes with:

- Four 1.5 V AAA alkaline batteries
- Certificate of calibration
- Test probe leads (4-mm tips)
- Quick start guide
- Free test data (Option UK6)

Perform test confidently and efficiently  
over a longer period of time!

U1240C Series handheld digital multimeters



### Key features

- 10,000-count dual display
- Up to 0.09% basic DCV accuracy
- Longer battery life up to 400 hours
- Certified to IP 67 for water and dust protection and tested to withstand a 3-meter (10-ft) drop
- Built-in flashlight
- (U1242C) Vsense for non-contact voltage detection, built-in harmonic ratio, low impedance mode, T1-T2 differential temperature

Bluetooth wireless connectivity (optional U1177A Infrared (IR)-to-Bluetooth Adapter required)



### Key specifications

DCV accuracy	0.09%
Reading speed	5 readings/s
Measurement functions	Voltage, current, frequency, capacitance, resistance, continuity, diode test and temperature
Type of connectivity	IR-USB and Bluetooth

Technical datasheet:  
Literature number 5992-0848EN

### Ordering information

U1241C digital multimeter  
U1242C digital multimeter

Each handheld comes with:

- Test leads (red and black)
- Infrared (IR)-to-USB cable
- Four 1.5 V AAA alkaline batteries
- Quick start guide
- Certificate of calibration

## Be well equipped from the start

### U1250 Series handheld multimeters



#### Key features

- High contrast ratio of 2000:1 and wide viewing angle of 160°\*
- Built-in square-wave generator and frequency counter
- Includes all essential accessories for electronics troubleshooting
- Smoothing function to stabilize erratic readings\*
- Data logging to instrument and PC \*with U1253B

Bluetooth wireless connectivity (optional U1177A Infrared (IR)-to-Bluetooth Adapter required)

#### Key specifications

DCV accuracy	0.25%
Speed	100 readings/s
Measurement functions	DCV, ACV, DCI, ACI, 2-wire resistance, frequency, capacitance, temperature, diode, continuity tests
Type of connectivity	IR-USB and Bluetooth



#### Ordering information

U1251B digital multimeter  
U1252B digital multimeter  
U1253B digital multimeter

Each U1251B includes:

- One 9V size alkaline battery
- Certificate of calibration
- Test probe leads (4-mm tips)
- Quick start guide
- Free test data (Option UK6)

Each U1252B/U1253B includes:

- One 9V size rechargeable Ni-MH battery
- Certificate of calibration
- Test probe leads (4-mm tips)
- Quick start guide
- Free test data (Option UK6)

Technical datasheet:

Literature number 5989-5509EN



Best Value Portable Test Equipment, 2006



A testament to innovation and credibility, 2006



General-purpose instruments category, 2009



Category Winner, EC&M Product of the Year competition, 2009



# Shaped to fit, tailored to perform, built to last

## U1270 Series handheld digital multimeters



### Key features

- OLED display with 2000:1 contrast ratio and 160 degree viewing angle<sup>1</sup>
- Measure up to 1000 V AC/DC and 10 A (20 A for 30 s)
- Down to -40 °C operating temperature<sup>1</sup>
- Water and dust resistance (IP 54)
- CAT III 1000 V / CAT IV 600 V overvoltage protection

1. With U1273AX

Bluetooth wireless connectivity (optional U1177A Infrared (IR)-to-Bluetooth Adapter required)

### Key specifications

DCV accuracy	0.05%
Speed	7 readings/s
Measurement functions	DCV, DCI, ACV, ACI, 2-wire resistance, frequency, capacitance, continuity, diode test
Type of connectivity	IR-USB and Bluetooth

### Ordering information

U1271A digital multimeter  
U1272A digital multimeter  
U1273A digital multimeter  
U1273AX digital multimeter

Each handheld comes with:

- Standard test leads
- Test probes with 4-mm tips
- K-type thermocouple and adapter
- 4 x AAA alkaline batteries (for U1271A, U1272A, U1273A)
- 4 x AAA lithium batteries (for U1273AX)
- Certificate of calibration
- UK 6 (test report)
- Quick start guide

Technical datasheet:  
Literature number 5990-6425EN



Front panel



Back panel



## Trustworthy measurements in the palm of your hand!

### U1280 Series handheld digital multimeters



#### Key features

- 60,000-count dual display
- Up to 0.025% basic DCV accuracy
- Longer battery life up to 800 hours
- Certified to IP 67 for water and dust protection and tested to withstand a 3-meter (10-ft) drop
- (U1282A only) Vsense for non-contact voltage detection, square wave output, low pass filter, frequency counter

Bluetooth wireless connectivity (optional U1177A Infrared (IR)-to-Bluetooth adapter required)



#### Key specifications

DCV accuracy	0.025%
Speed	5 readings/s
Measurement functions	Voltage, current, frequency, capacitance, resistance, continuity, diode test and temperature
Type of connectivity	IR-USB and <i>Bluetooth</i>

Technical datasheet:

Literature number 5992-0847EN

#### Ordering information

U1281A digital multimeter

U1282A digital multimeter

Each handheld comes with:

- Test leads (red and black)
- Infrared (IR)-to-USB cable
- Four 1.5 V AA alkaline batteries
- Quick Start Guide
- Certificate of calibration

## Calibrate and measure with just one tool

### U1401B handheld multi-function calibrator/meter



#### Key features

- Dual display with bright LCD backlight
- Simultaneous source and measure
- Bipolar voltage and current, square-wave, auto scan and ramp outputs
- Full-span DMM capability, including temperature and frequency measurements
- Data logging to PC with optional



#### Key specifications

DCV accuracy	0.003%
Reading speed	3 readings/s
Measurement	DCV, ACV, DCI, ACI, 2-wire resistance, temperature, frequency, diode test, continuity, pulse width, duty cycle
Type of connectivity	IR-USB

Technical datasheet:

Literature number 5990-3459EN

#### Ordering information

U1401B multi-function calibrator/meter

Each U1401B is shipped with:

- Calibrator/meter standard test
- Lead kit
- Yellow test lead for mA simulation
- Protective holster
- Rechargeable battery pack
- AC power adapter and cord (according to country)
- Quick start guide
- Certificate of calibration
- Soft carrying case is included for U1401A

## A bench that fits into your bag

### U2741A 5½ digit USB modular multimeter



#### Key features

- Up to 300 VDC with 5½ digit resolution
- Wide measurement ranges: 100 mVDC to 300 VDC, 10 mA to 2 A
- Compatibility with high-speed USB 2.0, USBTMC-USB488 standard
- Standalone and modular capabilities



#### Key specifications

DCV accuracy	0.02%
Reading speed - DCV	100 readings/s
Measurement	DCV, ACV, DCI, ACI, 2-wire and 4-wire resistance, frequency, temperature, diode, continuity tests
Type of connectivity	USB 2.0

Technical datasheet:  
Literature number 5991-0042EN

#### Ordering information

##### U2741A digital multimeter

Each U2741A includes:

- 12 V, 2A AC/DC power adapter
- Power cord
- Standard test lead
- USB standard-A to mini-B interface cable
- L-mount kit (used with modular product chassis)
- Keysight USB modular products quick start guide
- Keysight Measurement Manager quick reference card
- Certificate of calibration
- Keysight USB modular products reference CD-ROM
- Keysight automation-ready CD-ROM (contains the Keysight IO Libraries Suite)

## Challenge the boundaries of test

M9181A/M9182A/M9183A PXI 6½ digit multimeters



Model	Description
M9181A	PXI digital multimeter, 6½ digit, basic features
M9182A	PXI-H digital multimeter, 6½ digit, high performance
M9183A	PXI-H digital multimeter, 6½ digit, enhanced performance



## Comparison of Keysight PXI DMM models

	M9181A	M9182A	M9183A
Resolution		6½ digits	
Maximum reading rate @ 4½ digits	150 readings/s	4,500 readings/s	15,000 readings/s
Maximum transactional speed (single reading interval time)	6.7 ms	222 µs	66 µs
Measurements and functions	DCV, DCI, True RMS ACV and ACI, 2- and 4-wire resistance	All M9181A measurements, plus frequency/period, temperature, and capacitance	All M9182A measurements plus duty cycle, counter/totalizer, DC source, and extended measurement ranges
Basic 1 year DCV accuracy	0.009%	0.004%	0.004%
Floating isolation (CAT II)	Up to 240 V	Up to 300 V	Up to 300 V
Triggering	Immediate	Immediate, analog level, programmable pre/post triggering, PXI trigger bus	
Reading storage	none	Circular buffer, 80 readings	
Connector capability	cPCI, PXI-1	cPCI, PXI-H, PXI-1	
<b>Software</b>			
Drivers	IVI-C, IVI-COM, LabVIEW, MATLAB		
Supported software development environments	Visual Studio (VB.NET, C#, C/C++), VEE, LabVIEW, LabWindows/CVI, MATLAB		
Included GUI	Soft front panel		
Application code examples	C/C++, Visual Basic		

M9181A Technical datasheet and flyer:  
Literature number 5990-9035EN (DS)  
Literature number 5990-9024EN (FL)

M9182A and M9183A Technical datasheet and flyer:  
Literature number 5990-7580EN (DS)  
Literature number 5990-6550EN (FL)



# Accessories Compatibility Chart


Ordering number	Description	Handheld clamp meters	Handheld DMMs								Bench DMMs											Modular DMM	Handheld calibrator/meter
		U1210 Series	U1190 Series	U1230 Series	U1240B Series	U1240C Series	U1250 Series	U1270 Series	U1280 Series	U3401A	U3402A	U3606A/B	34401A	34410A	34411A	34420A	34450A	34460A/61A	34465A/70A	3458A	U2741A	U1401B	
Kits/rack mounts																							
34137A	Deluxe test lead set																						
34190A	Rackmount kit																						
34191A	2U dual flange kit																						
34194A	Dual lock link kit																						
34307A	Thermocouple kit																						
34308A	Thermistor kit																						
E3600A-100	Test lead kit																						
U1161A	Extended test lead kit																						
U1168B	Standard test lead kit																						
U1180A	Thermocouple adapter+lead kit (for U1242B only) (for U1252/53B only) (for U1272A/73/73AX)																						
U8201A	Combo test lead kit																						
U8202A	Electronic test lead kit																						
Y1133A	Low-thermal external DMM scanning kit																						
Probes/leads/clamps/bocks/shunts/connectors																							
11059A	Kelvin prob set																						
11060A	Surface mount device probe																						
11062A	Kelvin clip set																						
34103A	Low thermal shorting plug																						
34104A	Low thermal input connector																						
34131A	Transit case																						
34133A	Precision electronic test leads																						
34134A	DC coupled current probe																						
34136A	High voltage probe																						
34138A	Test lead set																						
34171B	Input terminal block																						
34172B	Calibration short																						
34330A	30 A current shunt																						
E2308A	Thermister temperature probe																						
U1115A	Remote logging display																						
U1117A	Infrared (IR)-to-Bluetooth adapter																						
U1162A	Alligator clips																						
U1163A	SMT grabbers																						
U1164A	Fine-tip test probes																						
U1169A	Test probe leads																						
U1176A	Probe clip light																						
U1177A	Infared (IR)-to-Bluetooth adapter																						
U1580A	DMM terminal test lead set																						
U1583B	AC current clamp																						

## Accessories Compatibility Chart

Ordering number	Description	Handheld clamp meters	Handheld DMMs							Bench DMMs										Modular DMM	PXI modular DMMs	Handheld calibrator/meter
		U1210 Series	U1190 Series	U1230 Series	U1240B Series	U1240C Series	U1250 Series	U1270 Series	U1280 Series	U3401A/02A	U3606A/06B	34401A	34410A	34411A	34420A	34450A	34460A/61A	34465A/70A	3458A	U2741A	M9180 Series	U1401B
Probes/adapters/leads for temperature measurement																						
U1179A	IR connectivity/bracket				■																	
U1181A	Immersion temperature probe (for U1212A/13A only) (for U1194A only) (for U1233A only)		■	■	■	■	■	■	■													
U1182A	Industrial surface temperature probe (for U1212A/13A only) (for U1194A only) (for U1233A only)		■	■	■	■	■	■	■													
U1183A	Air temperature probe (for U1212A/13A only) (for U1194A only) (for U1233A only)		■	■	■	■	■	■	■													
U1184A	Temperature probe adapter (for U1212A/13A only) (for U1194A only) (for U1233A only)		■	■	■	■	■	■	■													■
U1185A	Thermocouple (J-type) and temperature probe adapter (for U1242A only) (for U1252A /53B only) (for U1272A/73A/73AX)					■	■	■	■	■												
U1186A	Thermocouple (K-Type) and temperature probe adapter (for U1212A/13A only) (for U1194A only) (for U1233A only)	■	■	■	■			■	■													■
U1586B	Temperature module (for U1233A only)			■				■														
U5404A	Remote test probe for U1280 Series									■												
Carry case/ hanging kit/brackets																						
34131A	Transit case											■	■	■	■	■	■	■				
34161A	Accessory pouch											■				■						
34162A	Accessory pouch											■	■	■	■		■	■	■			
34398A	RS-232 cable, 9-pin (F) to 9-pin (F)											■										
82350A	Interface card, high-performance PCI to GPIB															■						
82357B	USB/GPIB interface															■						
U1171A	Magnetic hanging kit		■	■	■	■	■		■													
U1172A	Transit case (aluminum-clad)		■	■	■	■	■		■													
U1174A	Soft carrying case			■	■	■	■	■														
U1175A	Soft carrying case	■																				
U1178A	Soft carrying case		■																			
U1594A	Hard carrying case									■												
U1595A	Rugged carrying case	■	■	■	■	■	■	■	■													
Power/cables/interface card																						
10833A/B/C/D/F/G	GPIB cable															■						
34102A	Low thermal input cable														■							
U1170A	Battery charger adapter (for U1250/52/53B only)							■														
U1173A	IR-to-USB cable	■		■	■		■	■														

## Linking up your instruments to the PC

Keysight GPIB and Instrument Control Products helps connect your instruments to PC easily, reliably and affordably. From legendary GPIB cables to the one-box connectivity gateway, see how each provides seamless integration of your instrument no matter where they are placed in your system.  
[www.keysight.com/find/gpib](http://www.keysight.com/find/gpib)



### BenchVue software

Data capture simplified.  
Click. Capture. Done.

BenchVue software for the PC makes it simple to connect, control, capture and view Keysight's DMMs simultaneously with other Keysight bench instruments and with no additional programming.

The Digital Multimeter app within BenchVue enables control of digital multimeters to visualize measurements, perform data logging<sup>1</sup> and annotate captured data (included in model BV0000A). Upgrading to the Pro version (model #B0001A) provides histograms, digitizer capability and unrestricted data logging with limit checking and alerts.

Download BenchVue software at no cost today.  
[www.keysight.com/find/benchvue](http://www.keysight.com/find/benchvue)

### Keysight handheld meter logger software

Perform measurements with U1210 Series, U1230 Series, U1240B Series<sup>2</sup>, U1240C Series, U1250 Series, U1270 Series, U1280 Series and U1450A/U1460A<sup>3</sup> using Windows-based PC.

- Connect up to 10 handheld meters - 5x IR-to-Bluetooth
- Adapter (U1177A, U1117A) and 5x IR-USB cable (U1173B)
- Meter view (live measurements) and logger view (graph with zoom and pan) mode
- Manage multi-session data logging within the software and export the data to other software (Microsoft Excel)

Keysight handheld meter logger software for PC can be downloaded from:  
[www.keysight.com/find/hhmeterlogger](http://www.keysight.com/find/hhmeterlogger)

### Keysight GPIB and instrument

Control products helps connect your instruments to PC easily, reliably and affordably. From legendary GPIB cables to the one-box connectivity gateway, see how each provides seamless integration of your instrument no matter where they are placed in your system.

[www.keysight.com/find/gpib](http://www.keysight.com/find/gpib)

1. One hour limit in no cost version.
2. For the U1240B Series, you also need to purchase the U1179A IR connectivity bracket to enable IR connectivity.
3. Only allows one connection at a time.

Learn more at: [www.keysight.com](http://www.keysight.com)

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at:  
[www.keysight.com/find/contactus](http://www.keysight.com/find/contactus)

