

Torque Wrenches And Open Ended Wrenches For RF Connectors

Connector	Coupling Torque (N-cm/in-lb)	Width Across Coupling Nut Wrench Flats	HP Torque Wrench #	HP Open Ended Wrench # and Size¹	
7 mm	135/12	3/4"	8710-1766	8710-1770	1/2"
Type N 50 ohm ²	135/12	3/4"	8710-1766	8710-1770	9/16"
Type N 75 ohm ²	135/12	3/4"	8710-1766	8710-1770	9/16"
3.5 mm standard ³	90/8	5/16"	8710-1765	8710-1761	7 mm
3.5 mm NMD ⁴				8710-0510	5/16"(8 mm)
3.5 mm m test prt	90/8	20 mm	8710-1764	8710-1770	9/16"
3.5 mm f test prt.				08513-20014	Spanner Wr.
2.92 mm standard	90/8	5/16"	8710-1765	8710-1761	7 mm
2.4 mm standard ⁴	90/8	5/16"	8710-1765	8710-1761	7 mm
2.4 mm NMD ⁵				8710-0510	5/16"(8 mm)
2.4 mm m	90/8	20 mm	8710-1764	8710-1770	1/2"
2.4 mm f NMD ⁵				08513-20014	Spanner Wr.
1.85 mm	90/8	5/16"	8710-1765	8710-0510	5/16"(8 mm)
1.0 mm	45/4	6 mm	8710-2079	8710-2156	6mm
SMA ⁷	56/5	5/16"	8710-1582		
TNC	56/5	no spec.			