

CHISELS & PUNCHES



Cold Chisels

- Heat-treated, high-carbon steel for necessary hardness and durability
- Cuts, shapes and removes metal
- Corrosion-resistant black finish
- Long length works better in hard-to-reach areas (Cat. Nos. 66174, 66177 and 66183)



66142



66177

Cat. No.	Blade Width	Overall Length
66140	0.375" (1 cm)	5" (12.7 cm)
66142	0.5" (1.3 cm)	6" (15.2 cm)
66143	0.625" (1.6 cm)	6.5" (16.5 cm)
66144	0.75" (1.9 cm)	7.5" (19.1 cm)
66145	0.875" (2.2 cm)	8" (20.3 cm)
66146	1" (2.5 cm)	8.5" (21.6 cm)
66174	0.5" (1.3 cm)	12" (30.5 cm)
66177	0.75" (1.9 cm)	12" (30.5 cm)
66183	1" (2.5 cm)	12" (30.5 cm)

Electrician's Chisel

- One-piece handle and blade forged of strong alloy steel
- Corrosion-resistant black finish extends to the polished blade edge



66100

Cat. No.	Blade Width	Overall Length
66100	2.75" (7 cm)	8" (20.3 cm)

Punches

- High-carbon steel for durability
- Rugged design for impact strength
- Heat-treated for added strength and hardness at working end
- Corrosion-resistant black finish



66324

66313

66343

Cat. No.	Punch Type	Point Diameter	Overall Length
66310	Center Punch	1/4" (6.4 mm)	4.25" (10.8 cm)
66311	Center Punch	5/16" (7.9 mm)	4.5" (11.4 cm)
66312	Center Punch	3/8" (9.5 mm)	5" (12.7 cm)
66313	Center Punch	1/2" (12.7 mm)	6" (15.2 cm)
66320	Pin Punch	1/16" (1.59 mm)	4.25" (10.8 cm)
66321	Pin Punch	3/32" (2.4 mm)	4.75" (12.1 cm)
66322	Pin Punch	1/8" (3.18 mm)	5" (12.7 cm)
66323	Pin Punch	5/32" (3.97 mm)	5.25" (13.3 cm)
66324	Pin Punch	3/16" (4.76 mm)	5.5" (14 cm)
66325	Pin Punch	1/4" (6.4 mm)	7" (17.8 cm)
66340	Drift Punch	1/8" (3.18 mm)	8" (20.3 cm)
66342	Drift Punch	3/16" (4.76 mm)	9" (22.9 cm)
66343	Drift Punch	1/4" (6.35 mm)	11" (27.9 cm)
66344	Drift Punch	5/16" (7.94 mm)	11" (27.9 cm)

Wire Rope Punches

- Used to safely drive out pins and keys in machinery
- Long, two-handed rubber handle to lessen shocks from blows
- Head attached with wire rope to reduce shock
- Urethane ring around head to reduce likelihood of chipping
- Precision heat treated to prevent shattering

Cat. No.	Point Diameter	Shank Length	Overall Length
7WRP13	1/2" (12.7 mm)	4.75" (12.1 cm)	20" (50.8 cm)
7WRP16	5/8" (15.88 mm)	4.75" (12.1 cm)	20" (50.8 cm)
7WRP19	3/4" (19.05 mm)	4.75" (12.1 cm)	20" (50.8 cm)
7WRP22	7/8" (22.23 mm)	4.75" (12.1 cm)	20" (50.8 cm)
7WRP25	1" (25.4 mm)	4.75" (12.1 cm)	20" (50.8 cm)
7WRP32	1-1/4" (31.75 mm)	4.75" (12.1 cm)	20" (50.8 cm)



7WRP22

Brass Punches

- Used where a softer punch is needed, e.g. where damage may occur from using a hardened punch
- Selected brass, correct composition for punch use
- Knurled handle for gripping easily
- Chamfered head for safety
- Sold in sets only



4BPSET5

Cat. No.	Kit Contains	
4BPSET5	Point Diameter	Overall Length
	3/8" (9.5 mm)	6" (15.2 cm)
	1/2" (12.7 mm)	7" (17.8 cm)
	5/8" (15.9 mm)	7" (17.8 cm)
	3/4" (19.1 mm)	8" (20.3 cm)
	1" (25.4 mm)	8" (20.3 cm)

Pin Punches

- Used for driving out and removing pins and keys
- Tough and resilient shaft made from quality tool steel
- Heat treated for durability and strength
- Soft head for safety; will mushroom, not chip
- Knurled handle for gripping easily
- Sold in sets only



4PPLSET8

Cat. No.	Kit Contains	
4PPLSET8	Point Diameter	Overall Length
	1/16" (2.4 mm)	2.156" (5.5 cm)
	1/8" (2.8 mm)	2.156" (5.5 cm)
	3/16" (4.76 mm)	2.359" (6 cm)
	3/16" (4.76 mm)	2.547" (6.5 cm)
	1/4" (6.35 mm)	2.547" (6.5 cm)
	1/4" (6.35 mm)	2.547" (6.5 cm)
	5/16" (7.9 mm)	2.75" (7 cm)
	3/8" (9.9 mm)	2.75" (7 cm)