

## Can Wrench

- Two tools in one; saves space in your pouch
- One end opens telephone box fasteners, the other end tightens nuts on binding-post terminals
- The 7/16" socket has a black finish and the 3/8" socket has a silver finish
- Sockets are 1-1/4" (3.2 cm) deep to fit over long binding posts and are thin-walled for easy access into tight areas
- Hex-socket design enables using a wrench to obtain extra torque
- High-impact, break-resistant handle for long and dependable service
- Sockets are heat-treated, alloy steel



68005



Cat. No.	Socket Size	Handle Diameter	Overall Length
68005	3/8", 7/16" Hex Nut	1" (2.5 cm)	7" (17.8 cm)

## Conduit Locknut Wrench

- Easily attach locknuts in tight or deep cut-in boxes
- For 1/2" and 3/4" (1.3 cm and 1.9 cm) connectors
- Direct-drive heads rotate each other when twisted
- Heavy-duty steel construction enables needed torque to loosen or tighten connectors
- Perfect for remodel work where box is filled with existing wires
- US Patent pending

**DIRECT DRIVE**


56999



Cat. No.	Size	Weight	Overall Length
56999	1/2", 3/4"	11.2 oz (318 g)	9" (22.9 cm)

## Grip-It™ Strap Wrenches

**NEW**

- Completely adjustable strap wrench
- Works in the tightest quarters
- Urethane-covered, high-strength belting attached to lightweight, I-beam handle
- Cam-action design permits uniform, high-torque application
- Under normal conditions, will not scratch, damage or deform polished pipe and fittings, plastic pipe and fittings, oil and water filters, glass pipe, PVC conduit, or polished shafts
- Also works on alternator belts, flywheels, and propeller assemblies



S6HB

S12HB

S18HB

Cat. No.	Handle Length	Diameter Capacity O. D.
★ S6HB	6" (15.2 cm)	1.5" to 4" (3.8 to 10.2 cm)
★ S12HB	12" (30.5 cm)	1.5" to 5" (3.8 to 12.7 cm)
★ S18HB	18" (45.7 cm)	1.125" to 8" (2.9 to 20.3 cm)
<b>Kit</b>	<b>Kit Includes</b>	
★ SHBKIT	S6HB, S12HB	