

SIDE-CUTTING LONG-NOSE PLIERS

Induction hardened cutting knives
for long life

FORGED STEEL

from Klein's US-made proprietary blend

Hot-riveted joint
ensures smooth action and no handle wobble

Slim head design
for working in confined areas

Knurled jaws
for grabbing and looping wire



LONG-NOSE


Side-Cutting Long-Nose Pliers

Includes core Side-Cutting Long-Nose Pliers features plus:

- Heavier design for greater cutting power
- Knurled jaws for grabbing and looping wire
- Extended handles provide added reach and greater leverage
- Curved handles provide greater tool control
- Glow-in-the-Dark grips are easily spotted in dark or low lit areas (Cat. Nos. D203-8-GLW)
- Spring-loaded action for self-opening (Cat. Nos. D203-6C and D203-7C)



D203-6C




D203-8NCR

HANDLE FINISH



Plastic-Dipped



GLOW-IN-THE-DARK
Plastic-Dipped



JOURNEYMAN™
Dual-Material



INS INSULATED
2-Layer
Protection




EINS INSULATED
3-Layer
Protection



1000 V



1000 V




12 AWG WIRE STRIPPING
D203-8N
J203-8N



12 AWG WIRE STRIPPING
AND CRIMPING
D203-8NCR



19 & 22 AWG
WIRE STRIPPING
D203-6H2



12 AWG SKINNING HOLE
D203-8N-INS

Cat. No.	Jaw Length	Jaw Width	Jaw Thickness	Point Diameter	Knife Length	Handle Color	Handle Finish	Overall Length
Heavy-Duty Design With Extended Handles								
2038EINS	2.313" (5.89 cm)	1.02" (2.59 cm)	0.5" (1.3 cm)	0.125" (0.32 cm)	0.693" (1.8 cm)	Orange/Gray	3-Layer Insulation	8.77" (22.28 cm)
D203-8	2.313" (5.89 cm)	1.02" (2.59 cm)	0.5" (1.3 cm)	0.125" (0.32 cm)	0.693" (1.8 cm)	Yellow	Plastic-Dipped	8.41" (21.36 cm)
D203-8N	2.313" (5.89 cm)	1.02" (2.59 cm)	0.5" (1.3 cm)	0.125" (0.32 cm)	0.693" (1.8 cm)	Yellow	Plastic-Dipped	8.41" (21.36 cm)
D203-8-GLW	2.313" (5.89 cm)	1.02" (2.59 cm)	0.5" (1.3 cm)	0.125" (0.32 cm)	0.693" (1.8 cm)	Glow-in-the-Dark	Plastic-Dipped	8.46" (21.49 cm)
D203-8-INS	2.313" (5.89 cm)	1.02" (2.59 cm)	0.5" (1.3 cm)	0.125" (0.32 cm)	0.693" (1.8 cm)	Orange	2-Layer Insulation	8.91" (22.63 cm)
D203-8N-INS	2.313" (5.89 cm)	1.02" (2.59 cm)	0.5" (1.3 cm)	0.125" (0.32 cm)	0.693" (1.8 cm)	Orange	2-Layer Insulation	8.91" (22.63 cm)
D203-8NCR	2.313" (5.89 cm)	1.02" (2.59 cm)	0.5" (1.3 cm)	0.125" (0.32 cm)	0.693" (1.8 cm)	Yellow	Plastic-Dipped	8.42" (21.39 cm)
J203-8	2.313" (5.89 cm)	1.02" (2.59 cm)	0.5" (1.3 cm)	0.125" (0.32 cm)	0.693" (1.8 cm)	Yellow/Black	Journeyman™ Dual-Material	8.42" (21.39 cm)
J203-8N	2.313" (5.89 cm)	1.02" (2.59 cm)	0.5" (1.3 cm)	0.125" (0.32 cm)	0.693" (1.8 cm)	Yellow/Black	Journeyman™ Dual-Material	8.42" (21.39 cm)
Standard Design With Curved Handles								
2036EINS	1.9" (4.83 cm)	0.688" (1.8 cm)	0.375" (1 cm)	.094" (0.24 cm)	0.572" (1.45 cm)	Orange/Gray	3-Layer Insulation	6.9" (17.53 cm)
2037EINS	2.42" (6.15 cm)	0.688" (1.8 cm)	0.375" (1 cm)	.094" (0.24 cm)	0.572" (1.45 cm)	Orange/Gray	3-Layer Insulation	7.43" (18.87 cm)
D203-6	1.969" (5.0 cm)	0.688" (1.8 cm)	0.375" (1 cm)	.094" (0.24 cm)	0.572" (1.45 cm)	Yellow	Plastic-Dipped	6.67" (16.94 cm)
D203-6C	1.969" (5.0 cm)	0.688" (1.8 cm)	0.375" (1 cm)	.094" (0.24 cm)	0.572" (1.45 cm)	Yellow	Plastic-Dipped	6.67" (16.94 cm)
D203-6-INS	1.969" (5.0 cm)	0.688" (1.8 cm)	0.375" (1 cm)	.094" (0.24 cm)	0.572" (1.45 cm)	Orange	2-Layer Insulation	6.9" (17.53 cm)
D203-7	2.43" (6.17 cm)	0.688" (1.8 cm)	0.375" (1 cm)	.094" (0.24 cm)	0.572" (1.45 cm)	Yellow	Plastic-Dipped	7.17" (18.21 cm)
D203-7C	2.43" (6.17 cm)	0.688" (1.8 cm)	0.375" (1 cm)	.094" (0.24 cm)	0.572" (1.45 cm)	Yellow	Plastic-Dipped	7.17" (18.21 cm)
D203-7-INS	2.43" (6.17 cm)	0.688" (1.8 cm)	0.375" (1 cm)	.094" (0.24 cm)	0.572" (1.45 cm)	Orange	2-Layer Insulation	7.37" (18.72 cm)
D203-6H2	1.876" (4.77 cm)	0.688" (1.8 cm)	0.375" (1 cm)	.094" (0.24 cm)	0.572" (1.45 cm)	Yellow	Plastic-Dipped	6.625" (16.83 cm)
J203-6	1.876" (4.77 cm)	0.688" (1.8 cm)	0.375" (1 cm)	.094" (0.24 cm)	0.572" (1.45 cm)	Yellow/Black	Journeyman™ Dual-Material	6.75" (17.15 cm)
J203-7	2.438" (6.19 cm)	0.688" (1.8 cm)	0.375" (1 cm)	.094" (0.24 cm)	0.572" (1.45 cm)	Yellow/Black	Journeyman™ Dual-Material	7.32" (18.59 cm)

