



DIGITAL MULTIMETERS



FEATURES		ET600
	Drop Protection	3.3ft (1m)
	Safety Rating	CAT IV 600V CAT III 1000V
	Test Voltages	125V, 250V, 500V, 1000V
	AC Voltage	1000V
	DC Voltage	1000V
	Insulation Resistance	4000MΩ
	Resistance	400kΩ
	Test Lock	●
	Live Circuit Detection	●
	True RMS	●
	Audible Continuity	●
	Backlight	●
	Auto Ranging	●
	Auto Zero	●
	Data Hold	●
	Max/Min Value	●
	Auto Power-Off	●
	LCD Display Count	4000
	Bar Graph	●
	Over-Range Indication	●
	Case Included	●
	Smart Mode	-

Slim Profile



FEATURES		MM325	MM420	MM450	MM460S	MM720
	Drop Protection	6.5ft (2m)	6.5ft (2m)	6.5ft (2m)	6.5ft (2m)	6.5ft (2m)
	Ingress Protection	–	–	–	-	IP42
	Safety Rating	CAT III 600V	CAT III 600V	CAT III 600V	CAT III 600V	CAT IV 600V CAT III 1000V
	AC Voltage	600V	600V	600V	600V	1000V
	DC Voltage	600V	600V	600V	600V	1000V
	AC Current	–	10A	10A	10A	10A
	DC Current	10A	10A	10A	10A	10A
	Resistance	2MΩ	50MΩ	50MΩ	50MΩ	60MΩ
	DC Millivolts	●	●	●	●	●
	AC Milliamps	–	●	●	●	●
	DC Milliamps	●	●	●	●	●
	AC Microamps	–	●	●	●	●
	DC Microamps	●	●	●	●	●
	True RMS	–	●	●	●	●
	Audible Continuity	●	●	●	●	●
	Backlight	●	●	Backlit Hi-Vis Reverse Contrast (FFSTN)	Backlit Hi-Vis Reverse Contrast (FFSTN)	Backlit Hi-Vis Reverse Contrast (FFSTN)
	Temperature	–	-40° - 1832°F (-40° - 1000°C)	-40° - 1832°F (-40° - 1000°C)	-40° - 1832°F (-40° - 1000°C)	-40° - 1832°F (-40° - 1000°C)
	Low Impedance	–	–	–	-	●
	Auto Ranging	–	●	●	●	●
	Range Hold	–	●	●	●	●
	Data Hold	●	●	●	●	●
	Diode Test	●	●	●	●	●
	Capacitance Test	–	400μF	400μF	4000μF	6000μF
	Frequency / Duty Cycle	–	10Hz-50kHz 1.0% to 99.9% (≤10kHz)	10Hz-50kHz 1.0% to 99.9% (≤10kHz)	10Hz-50kHz 1.0% to 99.9% (≤10kHz)	10Hz-50kHz 1.0% to 99.9% (≤10kHz)
	Max / Min	–	●	●	●	●
	Lead Alert Warning	●	●	●	●	–
	Magnetic Mount	Available As Accessory	Available As Accessory	Available As Accessory	Available as Accessory	Available As Accessory
	Auto-Power Off	●	●	●	●	●
	Battery Test	●	–	–	–	–
	LCD Display Count	2000	4000	4000	4000	6000
	Kickstand	●	●	–	●	●
	Case Included	–	–	●	●	●
	Smart Mode	–	–	–	●	–