



SPECIFICATION SHEET

10-K46 SERIES



KUT GARD® FR VISCOSE / KEVLAR® BLENDED SLEEVE WITH ELASTIC END & THUMB HOLE

- 60% FR Viscose / 40% Kevlar® blend
- Excellent thermal and flame protection from high heat and open flame of welding torches
- Offers cut resistance for light duty applications
- Exceptional comfort, lightweight, breathable, and shrink resistant
- Kevlar® knit wrist offers cut and heat resistance and prevent debris from entering the sleeve
- Elastic end provides a snug fit and helps eliminate debris from entering the sleeve
- Thumb hole allows protection all the way to the knuckle without sacrificing dexterity

APPLICATIONS

- Welding
- Automotive
- Aerospace
- Metal fabrication

CARE INSTRUCTIONS

Machine wash in warm water with detergent. Rinse well and spin using high speed. Tumble dry on low heat setting. Can be dry-cleaned. Do not bleach.

TECHNICAL DATA

MATERIAL	FR Viscose / Kevlar®
CUFF STYLE	Knit elastic cuff
COLOR	Yellow/Brown
SIZES	22", 26"
PACKAGING	144 each per case
CASE DIMENSIONS	18.1" x 12" x 9.1" / 46cm x 30.5cm x 23cm
CASE WEIGHT	11.5 lbs / 5.2 kg
COO	USA

CUT RESISTANCE PROPERTIES

- ASTM F2992-15 ANSI Cut Level A2 (Adopted by ANSI/ISEA 02/16)

BARCODES

ITEM	EACH	DOZEN	CASE
10-K4622	616314055560	01616314055569	02616314055568
10-K4626	616314055577	01616314055576	02616314055575



DIMENSIONS (in/cm)

	22"	26"
A	22 / 55.9	26 / 66
B	7 / 17.8	7.5 / 19

Binding Color: Blue/Gold

