



Walter G. **LEGGE** Co., Inc.  
444 Central Ave., Peekskill, NY 10566  
800-345-3443 fax 800-332-2636  
email: [info@leggesystems.com](mailto:info@leggesystems.com)  
website: [www.leggesystems.com](http://www.leggesystems.com)

DATE: 6/28/2013  
MANUFACTURER'S NAME: Walter G Legge Co., Inc.  
STREET ADDRESS: 444 Central Ave Peekskill, NY 10566-2003  
EMERGENCY TELEPHONE: CHEMTREC 800-424-9300  
INFORMATION NUMBER: 914-737-5040  
TRADE NAME: URESTAT  
DOT SHIPPING NAME: POLISHING COMPOUND  
DOT HAZARD CLASS: NOT REGULATED

#### HAZARD RATING

|      | Health | Fire | Reactivity |
|------|--------|------|------------|
| HMIS | 2      | 1    | 0          |

\*\*\*\*\*

#### SECTION II - INGREDIENTS

\*\*\*\*\*

CAS # 111-77-3 Diethylene Glycol Methyl Ether  
Pct. by Wt: 2.73 Vapor Pressure: .200 MMHG @ 68° F  
This substance is classified as a hazardous air pollutant

##### Exposure Limit:

ACGIH TLV/TWA: None Established  
OSHA PEL/TWA: None Established  
LD50, ORAL: 7128 MG/KG (mouse and rat)  
LD50, DERMAL: 9404 MG/KG (rabbit)  
LC50, INHALATION: >2000 MG/CU.M, 1 HR (rat)

CAS # 84-74-2 Dibutyl Phthalate  
Pct. by Wt: 1.32 Vapor Pressure: .100 MMGH @ 68° F

##### Exposure Limit:

ACGIH TLV/TWA 5 MG/CU.M  
OSHA PEL/TWA 5 MG/CU.M  
LD50, ORAL: 8000 MG/KG (rat)  
LD50, DERMAL: 20,940 MG/KG (rabbit)

\*\*\*\*\*

This product contains no reported carcinogens or suspected carcinogens

\*\*\*\*\*

#### SECTION III - PHYSICAL DATA

\*\*\*\*\*

BOILING POINT: 212 DEGREES F VAPOR DENSITY: Lighter than air EVAPORATION RATE:  
SLOWER THAN ETHER VAPOR PRESSURE: NE  
WEIGHT PER GALLON: 8.51 SPECIFIC GRAVITY: 1.02  
SOLUBILITY IN WATER: COMPLETE APPEARANCE: MILKY WHITE LIQ  
VOLATILES VOLUME: 80% ODOR: ACRYLIC

\*\*\*\*\*

#### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

\*\*\*\*\*

FLASH POINT: NONCOMBUSTIBLE

EXTINGUISHING MEDIA: NONE REQUIRED

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

SPECIAL FIRE FIGHTING PROCEDURES: Water may be used to cool down unopened containers in vicinity. Fire fighters should wear OSHA approved self-contained breathing apparatus and full protective clothing.

\*\*\*\*\*

#### SECTION V - HEALTH HAZARD DATA

\*\*\*\*\*EFFECTS OF

OVEREXPOSURE: ACUTE: Irritation of eyes and skin may occur with overexposure. Continued breathing of vapors may irritate respiratory tract causing headache, nausea and dizziness.

CHRONIC: None known

EMERGENCY FIRST AID PROCEDURES: INHALATION: Remove to fresh air. Restore respiration if necessary. Treat symptomatically.

EYE CONTACT: Flush immediately with copious quantities of water for 15 minutes minimum. Consult a physician.

DERMAL CONTACT: Wash affected areas with soap and water. Remove contaminated clothing. Wash clothing before reuse. Consult physician if irritation persists.

INGESTION: Drink 1 or 2 glasses of water to dilute. DO NOT INDUCE VOMITING. If spontaneous vomiting occurs keep head at or below knee level to prevent aspiration into lungs. Consult physician.

PRIMARY ROUTES OF ENTRY: Inhalation and dermal contact.

AVOID CONTAMINATION OF FOOD

\*\*\*\*\*

#### SECTION VI - REACTIVITY DATA

\*\*\*\*\*STABILITY: Stable

CONDITIONS TO AVOID: Protect from freezing

INCOMPATIBILITY (Materials to avoid): None

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion can produce carbon monoxide

\*\*\*\*\*

#### SECTION VII - SPILL AND LEAK PROCEDURES

\*\*\*\*\*

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate all ignition sources. Wear appropriate personal protection equipment and approved respirator. Contain spill with absorbent material and put into vapor tight containers. Prevent material from contacting any water sources or sewers leading to surface waters.

WASTE DISPOSAL: Dispose of in accordance with Federal, State, and local regulations.

\*\*\*\*\*

#### SECTION VIII - SPECIAL PROTECTION INFORMATION

\*\*\*\*\*

RESPIRATORY PROTECTION: In outdoor, open areas or where adequate ventilation exists none is required. In restricted ventilation areas use NIOSH/OSHA approved organic vapor cartridge type respirator designed to remove a combination of particles and vapor.

VENTILATION: In confined spaces mechanical ventilation is required to keep the air contaminant concentration below current applicable OSHA permissible exposure units.

PROTECTIVE GLOVES: Impervious type required for long or repeated exposure.

PROTECTIVE FOOTWEAR: Water proof boots are recommended for long or repeated use.

EYE PROTECTION: Use safety eye wear to protect against splash of concentrated liquids.

OTHER PROTECTIVE EQUIPMENT: Prevent prolonged skin contact with contaminated clothing.

HYGIENIC PRACTICES: Wash hands before eating, smoking or using washroom facilities.

\*\*\*\*\*

#### SECTION IX - SPECIAL PRECAUTIONS

\*\*\*\*\*

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: KEEP OUT OF REACH OF CHILDREN. Store in closed containers in compliance with good housekeeping procedures. Protect from freezing, and extreme heat. Store at temperatures above 45 degrees F.

OTHER PRECAUTIONS: Safety showers and eyewashes should be available. Train employees of safe use of this product and proper hygienic practices.

\*\*\*\*\*

#### SECTION X - Sara Title III Information

\*\*\*\*\*

##### Sara 313 Information:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

|                                |                |                  |
|--------------------------------|----------------|------------------|
| Diethylene Glycol Methyl Ether | CAS # 111-77-3 | Pct by Wt.: 2.73 |
|--------------------------------|----------------|------------------|

|                   |               |                  |
|-------------------|---------------|------------------|
| Dibutyl Phthalate | CAS # 84-77-2 | Pct by Wt.: 1.34 |
|-------------------|---------------|------------------|

\*\*\*\*\*

To the best of our knowledge, the information contained herein is accurate. However, Walter G LEGGE Co., Inc. assumes no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.