



Revision Number: 006.2

Issue date: 04/25/2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE AA H8000 B known as LOCTITE H8100 SPEED PT B 490ML	IDH number:	1056477
Product type/use:	Adhesive	Item number:	1096943_1314328
Restriction of Use:	None identified	Region:	United States
Company address:	Contact information: Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com		
Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067			

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: HEATING MAY CAUSE A FIRE.
CAUSES SKIN IRRITATION.
MAY CAUSE AN ALLERGIC SKIN REACTION.
CAUSES SERIOUS EYE IRRITATION.
MAY DAMAGE FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
ORGANIC PEROXIDE	F
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
REPRODUCTIVE TOXICITY	1B

PICTOGRAM(S)



Precautionary Statements

Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep away from clothing and other combustible materials. Keep only in original packaging. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.
Response:	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
Storage:	Store locked up. Protect from sunlight. Store at temperatures not exceeding 38 °C (100.4 °F). Keep cool. Store separately.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

IDH number: 1056477

Product name: LOCTITE AA H8000 B known as LOCTITE H8100 SPEED PT B 490ML

Page 1 of 6

Hazardous Component(s)	CAS Number	Percentage*
Benzoyl peroxide	94-36-0	10 - 30
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	10 - 30
Benzyl butyl phthalate	85-68-7	10 - 30
Ethene, homopolymer	9002-88-4	10 - 30
2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane	2095-03-6	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Danger of decomposition if exposed to heat. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Oxides of carbon. Phenolics. Toxic fumes. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

7. HANDLING AND STORAGE

Handling:	Keep away from heat, spark and flame. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Keep container closed.
Storage:	For safe storage, store at or below 38 °C (100.4 °F) Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Keep away from heat, spark and flame. Protect from direct sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Benzoyl peroxide	5 mg/m ³ TWA	5 mg/m ³ PEL	None	None
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
Benzyl butyl phthalate	None	None	None	None
Ethene, homopolymer	10 mg/m ³ TWA Inhalable particles. 3 mg/m ³ TWA Respirable particles.	15 MPPCF TWA Respirable fraction. 15 mg/m ³ TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m ³ TWA Respirable fraction. 5 mg/m ³ PEL Respirable fraction. 15 mg/m ³ PEL Total dust.	None	None
2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane	None	None	None	None

Engineering controls:

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid, Paste
Color:	Blue
Odor:	Slight, Characteristic
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Specific gravity:	1.1674
Vapor density:	Not available.
Flash point:	> 93.00 °C (> 199.4 °F) Pensky Martens closed cup
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Not available.
Partition coefficient (n-octanol/water):	Not available.
VOC content:	3.04 %
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Polymerization may occur at elevated temperature or in the presence of incompatible materials.
Hazardous decomposition products:	Oxides of carbon. Phenolics. Toxic fumes. Irritating vapors.
Incompatible materials:	Oxidizing agents. Acids. Bases.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight. Do not mix in batches greater than 100 grams (0.22 pounds) unless you plan to use immediately.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation:	May cause respiratory tract irritation.
Skin contact:	Causes skin irritation. May cause allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Benzoyl peroxide	Oral LD50 (Rat) = 7,710 mg/kg	Allergen, Irritant, Mutagen
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	Allergen, Irritant
Benzyl butyl phthalate	Oral LD50 (Rat) = 13,500 mg/kg Dermal LD50 (Mouse) = 6,700 mg/kg Dermal LD50 (Rat) = 6,700 mg/kg	Blood, Central nervous system, Irritant, Kidney, Liver, Pancreas, Reproductive
Ethene, homopolymer	None	No Target Organs
2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane	None	No Data

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Benzoyl peroxide	No	No	No
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
Benzyl butyl phthalate	No	No	No
Ethene, homopolymer	No	No	No
2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Organic peroxide type F, liquid (Dibenzoyl peroxide, stable dispersion in water, <=42%)
Hazard class or division: 5.2
Identification number: UN 3109
Packing group: None
Marine pollutant: Butyl-benzyl-phthalate
DOT Hazardous Substance(s): Butyl benzyl phthalate

International Air Transportation (ICAO/IATA)

Proper shipping name: Organic peroxide type F, liquid (Dibenzoyl peroxide)
Hazard class or division: 5.2 (HEAT)
Identification number: UN 3109
Packing group: None
Exceptions: (Not more than 490 ml)

Water Transportation (IMO/IMDG)

Proper shipping name: ORGANIC PEROXIDE TYPE F, LIQUID (DIBENZOYL PEROXIDE) (Butyl-benzyl-phthalate, Dibenzoyl peroxide)
Hazard class or division: 5.2
Identification number: UN 3109
Packing group: None
Marine pollutant: Butyl-benzyl-phthalate, Dibenzoyl peroxide
Exceptions: (Not more than 490 ml)

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis.
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Reactive, Immediate Health, Delayed Health
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Benzoyl peroxide (CAS# 94-36-0). Benzyl butyl phthalate (CAS# 85-68-7) 100 lbs. (45.4 kg)
CERCLA Reportable quantity:
California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3, 8, 11, 13

Prepared by: Product Safety and Regulatory Affairs

Issue date: 04/25/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.