

Revision Number: 001.1

Issue date: 11/05/2014

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

TECHNOMELT PA 6208 known as

Macromelt 6208

Product type: Restriction of Use:

Hotmelt adhesive None identified

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

IDH number:

114369

item number: Region:

114369 **United States** 

Contact Information: Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS.

VAPORS ABOVE MOLTEN ADHESIVE MAY CAUSE EYE, SKIN AND

RESPIRATORY TRACT IRRITATION.

STATIC CHARGES GENERATED BY EMPTYING PACKAGE IN OR NEAR

FLAMMABLE VAPORS MAY CAUSE IGNITION.

HAZARD CLAS	S HAZARD CATEGORY
None	None

# PICTOGRAM(S) None

#### **Precautionary Statements**

1DH number: 114369

Prevention:

Not prescribed

Response: Storage:

Not prescribed

Disposal:

Not prescribed Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
None	None	None

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Molten adhesive may cause severe burns. No attempt should be made to

remove material from skin or to remove contaminated clothing as damaged skin can be easily torn. Cool melted product on skin with plenty of water. Do not remove solidified product. Cover affected areas with clean sheeting or

gauze and seek immediate medical attention.

Eye contact: If eye contact occurs with molten material immediately cool with water. Do not

remove adhesive. Seek medical attention.

Ingestion: Ingestion of solid adhesive is not expected to be hazardous. If symptoms

develop and persist, get medical attention.

Symptoms: See Section 11.

#### 5. FIRE FIGHTING MEASURES

Extinguishing media: Use extinguishing measures appropriate to local circumstances and the

surrounding environment. Water spray (fog), foam, dry chemical or carbon

dioxide.

Special firefighting procedures: Not available.

Unusual fire or explosion hazards: Not available.

Hazardous combustion products: Oxides of carbon, oxides of nitrogen, irritating organic vapors.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

No special environmental precautions required. Do not allow material to

contaminate ground water system.

Clean-up methods: Sweep up spilled material. Avoid creating dust. Keep in suitable and closed

containers for disposal.

## 7. HANDLING AND STORAGE

Handling: Avoid skin contact with molten resins. Do not place wet or damp solid into melt

tank. Follow suggested application temperature. Do not wear contact lenses.

Storage: Keep cool in accordance with information on label and in Technical Data

Sheets.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
None	None	None	None	None

Engineering controls:

Use adequate ventilation to remove molten vapors or fumes.

IDH number: 114369 Product name: TECHNOMELT PA 6208 known as Macromelt 6208 Page 2 of 5

Respiratory protection:

Solid Resin: Dust safety masks are recommended when the potential for dust

inhalation exists. Molten Resin: Use a NIOSH approved air-purifying respirator

with an organic vapor cartridge.

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Do not wear

contact lenses.

Skin protection:

Insulated gloves and long sleeved clothing are strongly recommended when

working with molten adhesive.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Color: Odor:

Odor threshold:

pH: Vapor pressure: Boiling point/range: Melting point/ range:

Vapor density: Flash point:

Flammable/Explosive limits - lower: Flammable/Explosive limits - upper:

Flammable/Explosive limits -Autoignition temperature: Evaporation rate:

Solubility in water:
Partition coefficient (n-octanol/water):

VOC content: Viscosity: Decomposition temperature: Solid

Amber Slight

Not available.
Not available.
Not available.
Not available.
Not available.
Not available.

Not available. No flash point up to 200 °C

No tiash point up to 200 Not available.

Not available.
Not available.
Not available.
Not available.
Insoluble

Not available. 0.00 % Not available.

Not available.

## 10. STABILITY AND REACTIVITY

Stability:

Stable

Hazardous reactions:

Will not occur.

Hazardous decomposition

products:

Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

Incompatible materials:

Acids. Bases. Oxidizing agents.

Reactivity:

Not available.

Conditions to avoid:

Excessive heat.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Molten adhesive., Skin, Eyes

#### Potential Health Effects/Symptoms

Inhalation:

Continuous breathing of vapors above molten adhesive may irritate mucous membranes. Dusts

from solid adhesive may cause irritation.

Skin contact:

Molten adhesive may cause severe burns. Solid adhesive has no hazards.

Eye contact:

Molten adhesive in eyes will cause severe and permanant damage. Can cause mechanical

irritation if dusts are generated.

Ingestion:

Not expected under normal conditions of use.

Hazardous Component(s)	LD50s and LC50	s Immedia	mmediate and Delayed Health Effects	
None	None		None	
Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
None	None	None	None

## 12. ECOLOGICAL INFORMATION

**Ecological information:** 

Not available.

#### 13. DISPOSAL CONSIDERATIONS

#### Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number:

Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:

Not regulated

Hazard class or division:

None

Identification number:

None

Packing group:

None

International Air Transportation (ICAO/IATA)

Proper shipping name:

Not regulated

Hazard class or division: Identification number:

None

Packing group:

None

None

Water Transportation (IMO/IMDG)

Proper shipping name:

Not regulated

Hazard class or division:

None

Identification number:

None

Packing group:

None

# 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act

TSCA 12 (b) Export Notification:

None above reporting de minimis

CERCLA/SARA Section 302 EHS:

None above reporting de minimis

CERCLA/SARA Section 311/312:

Not available.

IDH number: 114369 Product name: TECHNOMELT PA 6208 known as Macromelt 6208

Page 4 of 5

CERCLA/SARA Section 313:

None above reporting de minimis

California Proposition 65:

No California Proposition 65 listed chemicals are known to be present.

**Canada Regulatory Information** 

**CEPA DSL/NDSL Status:** 

All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

# 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by:

Lou Fabrizio, Regulatory Affairs Specialist

Issue date:

IDH number: 114369

11/05/2014

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

				93	
			<b>10</b>		
			6		
	11				
		¥		127	
	e e e				
	± 41				
	*				
	74				
1.0					
					2
	20				
					76
5					T.
					a a
	8				
VL 3				7a	X 1 (p/x
				g v	we get a 188
				A 1755 A	(
			94 A		
	Fi			2.4.1	2 2 2
				. 7	£".
81					± 8 ±
			22		±8 ×