

Safety Data Sheet



Revision Number: 004.0

Issue date: 04/17/2024

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE LB 8014
Product type/use: Lubricant
Restriction of Use: None identified
Company address:
Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067

IDH number: 1170163
Item number: 1170163
Region: United States
Contact information:
Telephone: +1 (860) 571-5100
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SKIN IRRITATION.
CAUSES SERIOUS EYE DAMAGE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face protection.
Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. Take off contaminated clothing.
Storage: Not prescribed
Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
White mineral oil (petroleum), highly refined	8042-47-5	30 - 60
White mineral oil (petroleum)	8042-47-5	10 - 30
Calcium dihydroxide	1305-62-0	10 - 30
Talc	14807-96-6	5 - 10
Aluminum, (benzoato-O,O')hydroxy(octadecanoato-O,	54326-11-3	5 - 10
Calcium carbonate	471-34-1	1 - 5
Zinc sulfide	1314-98-3	1 - 5
Zinc oxide	1314-13-2	0.1 - 1

IDH number: 1170163

Product name: LOCTITE LB 8014

Quartz (SiO ₂) respirable particulates (RCS) ≥10%	14808-60-7	0.1 - 1
---	------------	---------

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
Skin contact:	Wash with soap and water. If symptoms develop and persist, get medical attention.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms develop and persist, get medical attention.
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. If symptoms develop and persist, get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Oxides of carbon. Toxic and irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Keep unnecessary personnel away. Scrape up as much material as possible. Clean residue with soap and water. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:	Avoid contact with eyes, skin and clothing. Do not breathe gas/fumes/vapor/spray. Wash thoroughly after handling. Refer to Section 8.
Storage:	Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
White mineral oil (petroleum), highly refined	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 TWA mist 5 mg/m3 PEL Mist.	None	None
White mineral oil (petroleum)	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Mist.	None	None
Calcium dihydroxide	5 mg/m3 TWA	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Talc	2 mg/m3 TWA Respirable fraction.	0.1 mg/m3 TWA Respirable. 20 MPPCF TWA 2.4 MPPCF TWA Respirable.	None	50 ppm
Aluminum, (benzoato- O,O')hydroxy(octadecanoato-O,	1 mg/m3 TWA Respirable fraction.	None	None	None
Calcium carbonate	10 mg/m3 TWA Total dust. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 15 MPPCF TWA Respirable fraction. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction.	None	None
Zinc sulfide	None	None	None	None
Zinc oxide	2 mg/m3 TWA Respirable fraction. 10 mg/m3 STEL Respirable fraction.	5 mg/m3 PEL Fume. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust.	None	None
Quartz (SiO2) respirable particulates (RCS) >=10%	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None

Engineering controls:	Use only with adequate ventilation. Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA regulations for respirator use (29 CFR 1910.134).
Eye/face protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.
Skin protection:	Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	White
Odor:	Mild
Odor threshold:	Not available.
pH:	Not applicable, Product is non-soluble (in water).
Vapor pressure:	< 1 hPa (20 °C (68°F))
Boiling point/range:	> 100 °C (> 212°F)
Melting point/ range:	Not applicable, Product is a liquid
Specific gravity:	1.18
Vapor density:	> 1 20 °C
Flash point:	154 °C (309.2 °F) calculated
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	The product is not flammable.
Evaporation rate:	Not available.
Solubility in water:	Not miscible or difficult to mix
Partition coefficient (n-octanol/water):	Not available.
VOC content:	< 3 %
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Hydrocarbons. Irritating organic vapours.
Incompatible materials:	Oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Excessive heat. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation:	This product has low volatility and is not expected to cause respiratory tract irritation during normal conditions of use. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.
Skin contact:	Causes skin irritation.
Eye contact:	Causes serious eye damage.
Ingestion:	Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
White mineral oil (petroleum), highly refined	Inhalation LC50 (Rat, 4 h) = > 5 mg/l	Irritant
White mineral oil (petroleum)	Inhalation LC50 (Rat, 4 h) = > 5 mg/l	No Data
Calcium dihydroxide	Oral LD50 (Rat) = 7,340 mg/kg	Irritant, Corrosive
Talc	None	Irritant, Lung, Some evidence of carcinogenicity
Aluminum, (benzoato-O,O')hydroxy(octadecanoato-O,	None	No Records
Calcium carbonate	Oral LD50 (Rat) = 6,450 mg/kg Oral LD50 (Mouse) = 6,450 mg/kg Inhalation LC50 (Rat, 4 h) = > 3 mg/l	Nuisance dust
Zinc sulfide	Oral LD50 (Rat) = > 15,000 mg/kg Dermal LD50 (Rat) = > 2 g/kg Inhalation LC50 (Rat, 4 h) = > 5,700 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,410 mg/m3	Blood, Gastrointestinal, Immune system, Irritant, Kidney, Metabolic, Nervous System, Pancreas, Respiratory
Zinc oxide	Oral LD50 (Mouse) = 7,950 mg/kg Oral LD50 (Rat) = > 5 g/kg Inhalation LC50 (Rat, 4 h) = > 5,700 mg/m3	Blood, Gastrointestinal, Immune system, Irritant, Kidney, Metabolic, Nervous System, Pancreas, Respiratory, Skin
Quartz (SiO2) respirable particulates (RCS) >=10%	None	No Data

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
White mineral oil (petroleum), highly refined	No	No	No
White mineral oil (petroleum)	No	No	No
Calcium dihydroxide	No	No	No
Talc	No	No	No
Aluminum, (benzoato-O,O')hydroxy(octadecanoato-O,	No	No	No
Calcium carbonate	No	No	No
Zinc sulfide	No	No	No
Zinc oxide	No	No	No
Quartz (SiO2) respirable particulates (RCS) >=10%	Known To Be Human Carcinogen.	Group 1	Yes

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis.
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health
CERCLA/SARA Section 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Zinc sulfide (CAS# 1314-98-3). Zinc oxide (CAS# 1314-13-2).
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
------------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3,8,9,11,13,15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 04/17/2024

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.