

Revision Number: 006.0

# **1. PRODUCT AND COMPANY IDENTIFICATION**

Product name:

Product type/use: Epoxy Restriction of Use: None in Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

LOCTITE ABLESTIK 85-1 known as Ablebond 85-1 (5011) (2g) Epoxy adhesive None identified

IDH number:


1199746

Region:United StatesContact information:Telephone: +1 (860) 571-5100MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW			
WARNING:	CAUSES SKIN IRRITATION.		
	MAY CAUSE AN ALLERGIC SKIN REACTION.		
	CAUSES SERIOUS EYE IRRITATION.		
	MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR		
	REPEATED EXPOSURE.		

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2



#### **Precautionary Statements**

Prevention:	Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling.
	Contaminated work clothing should not be allowed out of the workplace. Wear protective
	gloves, eye protection, and face protection.
Response:	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several
	minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical
	attention if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation
	persists: Get medical attention. Take off contaminated clothing.
Storage:	Not prescribed
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local
•	governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Conductor	Proprietary	60 - 90
Epoxy resin	Proprietary	10 - 30

IDH number: 1199746

Product name: LOCTITE ABLESTIK 85-1 known as Ablebond 85-1 (5011) (2g) Page 1 of 5

Epoxy resin modifier	Proprietary	1 - 5
dapsone	80-08-0	1 - 5

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4.	. FIRST AID MEASURES	
Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.	
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get medica attention.	
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.	
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.	
Symptoms:	See Section 11.	
5. F	IRE FIGHTING MEASURES	
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.	
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.	
Unusual fire or explosion hazards:	This product is combustible at high temperatures. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.	
Hazardous combustion products:	Oxides of carbon, oxides of nitrogen, irritating organic vapors.	
6. ACCII	DENTAL RELEASE MEASURES	
personal protection recommended in Section of the s	on 8, isolate the hazard area and deny entry to unnecessary and	
Environmental precautions:	Do not allow product to enter sewer or waterways.	
Clean-up methods:	Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean- up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.	
7. H	HANDLING AND STORAGE	
Handling:	Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Refer to Section 8.	
Storage:	For safe storage, store at or above -40.0 °C (-40°F) Keep in a cool, well ventilated area away from heat, sparks and open flame.	

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

Keep container tightly closed until ready for use.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Conductor	None	None	None	None
Epoxy resin	None	None	None	None
Epoxy resin modifier	None	None	None	None
dapsone	None	None	None	None

**Engineering controls:** 

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:** 

Eye/face protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Paste, Liquid Brown

Physical state:
Color:
Odor:
Odor threshold:
pH:
Vapor pressure:
Boiling point/range:
Melting point/ range:
Specific gravity:
Vapor density:
Flash point:
Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Flammability:
Evaporation rate:
Solubility in water:
Partition coefficient (n-octanol/water):
VOC content:
Viscosity:
Decomposition temperature:

Odorless Not available. Not available. Not applicable Not applicable Not available. 4.7 Not available. > 93 °C (> 199.4 °F) Not available. Not available. Not available. Not applicable Not available. Insoluble Not available. < 1 % 5,000 - 6,000 cp Not available.

# 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Hazardous polymerization can occur.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Irritating organic vapours.
Incompatible materials:	Ammonia. Strong acids and strong bases. Strong oxidizing agents. Halogenated compounds. Amines.
Reactivity:	Not available.
Conditions to avoid:	Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

# **11. TOXICOLOGICAL INFORMATION**

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation:	May cause respiratory tract irritation.		
Skin contact:	Causes skin irritation. May cause allergic skin reaction.		
Eye contact:	Causes serious eye irritation.		
Ingestion:	May cause gastrointestinal tract irritation if swallowed.		

Hazardous Component(s)	LD50s and LC50s Immediate and Delayed Health E	
Conductor	None	Irritant, Allergen
Epoxy resin	None	Allergen, Irritant
Epoxy resin modifier	None	Irritant, Allergen
dapsone None		Allergen, Blood, Eyes, Irritant, Kidney, Nervous System, Skin

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Conductor	No	No	No
Epoxy resin	No	No	No
Epoxy resin modifier	No	No	No
dapsone	No	No	No

#### 12. ECOLOGICAL INFORMATION

**Ecological information:** 

Not available.

### **13. DISPOSAL CONSIDERATIONS**

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

### **14. TRANSPORT INFORMATION**

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Hazard class or division: Identification number: Packing group: Not regulated None None None

Not regulated

None

None

None

International Air Transportation (ICAO/IATA)

Proper shipping name: Hazard class or division: Identification number: Packing group:

Water Transportation (IMO/IMDG)

Proper shipping name: Hazard class or division: Identification number: Packing group: Not regulated None None None

### **15. REGULATORY INFORMATION**

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status:

TSCA 12 (b) Export Notification:

All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory. None above reporting de minimis

IDH number: 1199746

Product name: LOCTITE ABLESTIK 85-1 known as Ablebond 85-1 (5011) (2g) Page 4 of 5

CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health, Delayed Health None above reporting de minimis.
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

#### **16. OTHER INFORMATION**

Please contact Regulatory Affairs for additional details.

This safety data sheet contains changes from the previous version in sections: 2,9,13,16

Prepared by: Product Safety and Regulatory Affairs

**Issue date:** 01/26/2022

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.