

Revision Number: 004.0 Issue date: 01/08/2020

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE ABLESTIK ECF 568-1-006 IDH number: 1203299

known as Ablefilm ECF568-1-006, 2 x

16

**Product type/use:** Epoxy adhesive

Restriction of Use: None identified Region: United States Company address: Contact information:

Henkel Corporation Telephone: +1 (860) 571-5100

One Henkel Way

MEDICAL EMERGENCY Phone: Poison Control Center
Rocky Hill, Connecticut 06067

1-877-671-4608 (toll free) or 1-303-592-1711

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

| HAZARD CLASS       | HAZARD CATEGORY |
|--------------------|-----------------|
| SKIN IRRITATION    | 2               |
| EYE IRRITATION     | 2A              |
| SKIN SENSITIZATION | 1               |

#### PICTOGRAM(S)



#### **Precautionary Statements**

Prevention: Avoid breathing dust or fumes. Wash affected area thoroughly after handling. Contaminated

work clothing should not be allowed out of the workplace. Wear protective gloves, eye

protection, and face protection. **Response:**IF ON SKIN: Wash with plenty of the protection.

IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off

contaminated clothing.

Storage: Not prescribed

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

IDH number: 1203299 Product name: LOCTITE ABLESTIK ECF 568-1-006 known as Ablefilm ECF568-1-006, 2 x 16

Page 1 of 6

| Hazardous Component(s)  | CAS Number  | Percentage* |  |
|-------------------------|-------------|-------------|--|
| Silver                  | 7440-22-4   | 60 - 80     |  |
| Epoxy resin             | Proprietary | 10 - 30     |  |
| Glass, oxide, chemicals | 65997-17-3  | 5 - 10      |  |
| Epoxy resin             | Proprietary | 1 - 5       |  |
| Modified epoxy resin    | Unknown     | 1 - 5       |  |

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

**Eye contact:** Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. If symptoms develop

and persist, get medical attention.

Symptoms: See Section 11.

### 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses. In case of fire, keep containers cool with water

spray.

Hazardous combustion products: Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Ensure adequate ventilation. Wear suitable protective clothing, gloves and

eye/face protection. Sweep up or gather material and place in appropriate container for disposal. Refer to Section 8 "Exposure Controls / Personal

Protection" prior to clean up.

# 7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Wear suitable protective clothing, gloves

and eve/face protection. Prevent contact with eyes, skin and clothing. Do not

breathe vapor and mist. Wash thoroughly after handling.

Keep in a cool, well ventilated area away from heat, sparks and open flame. Storage:

Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)  | ACGIH TLV   | OSHA PEL   | AIHA WEEL | OTHER |
|-------------------------|---|--|-----------|-------|
| Silver                  | 0.1 mg/m3 TWA Dust and fume.  | 0.01 mg/m3 PEL (as<br>Ag)  | None      | None  |
| Epoxy resin             | None  | None   | None      | None  |
| Glass, oxide, chemicals | 5 mg/m3 TWA Inhalable fraction. 10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction. | 15 mg/m3 TWA Total<br>dust.<br>5 mg/m3 TWA<br>Respirable fraction. | None      | None  |
| Epoxy resin             | None  | None   | None      | None  |
| Modified epoxy resin    | None  | None   | None      | None  |

**Engineering controls:** Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid, Film Color: Silver Odor: Slight Odor threshold: Not available. pH: Not available.

Vapor pressure: Not applicable Not applicable Boiling point/range: Melting point/ range: Not available. 3.3

Specific gravity:

**Decomposition temperature:** 

Vapor density: Not applicable > 100 °C (> 212°F) Flash point: Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability: Not applicable **Evaporation rate:** Not applicable Solubility in water: Insoluble Partition coefficient (n-octanol/water): Not applicable **VOC** content: < 1 % (by weight) Viscosity: Not available.

IDH number: 1203299 Product name: LOCTITE ABLESTIK ECF 568-1-006 known as Ablefilm ECF568-1-006, 2 x 16

Not available.

# 10. STABILITY AND REACTIVITY

**Stability**: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 1203299

Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics.

Incompatible materials: Strong oxidizing agents. Amines.

Reactivity: Not available.

Conditions to avoid: Elevated temperatures.

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

#### Potential Health Effects/Symptoms

**Inhalation:** Inhalation of processing fumes may be harmful.

Skin contact: Causes skin irritation. May cause allergic skin reaction. Argyria (a non-toxic, cosmetic blue-gray

discoloration of the skin and mucous membranes that is irreversible).

**Eye contact:** Causes serious eye irritation.

**Ingestion:** Not expected under normal conditions of use.

| Hazardous Component(s)  | LD50s and LC50s  | Immediate and Delayed Health Effects        |  |
|-------------------------|--|---|--|
| Silver                  | Oral LD50 (Rat) = > 5,000 mg/kg<br>Dermal LD50 (Rat) = > 2,000 mg/kg | Allergen, Eyes, Irritant, Respiratory, Skin |  |
| Epoxy resin             | None   | Irritant, Allergen                          |  |
| Glass, oxide, chemicals | None   | Allergen, Respiratory                       |  |
| Epoxy resin             | None   | Allergen, Irritant                          |  |
| Modified epoxy resin    | None   | No Data                                     |  |

| Hazardous Component(s)  | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen<br>(Specifically Regulated) |
|-------------------------|----------------|-----------------|---|
| Silver                  | No             | No              | No  |
| Epoxy resin             | No             | No              | No  |
| Glass, oxide, chemicals | No             | No              | No  |
| Epoxy resin             | No             | No              | No  |
| Modified epoxy resin    | No             | No              | No  |

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

Product name: LOCTITE ABLESTIK ECF 568-1-006 known as Ablefilm ECF568-1-006, 2 x 16

Page 4 of 6

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D011. Silver.

# 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** RQ, Environmentally hazardous substance, solid, n.o.s.

Hazard class or division: 9

Identification number:UN 3077Packing group:IIIDOT Hazardous Substance(s):Silver

International Air Transportation (ICAO/IATA)

**Proper shipping name:** RQ, Environmentally hazardous substance, solid, n.o.s.

Hazard class or division: 9
Identification number: UN 3077
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

Hazard class or division: 9
Identification number: UN 3077
Packing group: III

# 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis. CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Silver (CAS# 7440-22-4).

CERCLA Reportable quantity: Silver (CAS# 7440-22-4) 1,000 lbs. (454 kg)

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

IDH number: 1203299 Product name: LOCTITE ABLESTIK ECF 568-1-006 known as Ablefilm ECF568-1-006, 2 x 16

Page 5 of 6

Prepared by: Product Safety and Regulatory Affairs

**Issue date:** 01/08/2020

IDH number: 1203299

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.