



Revision Number: 010.0

Issue date: 08/11/2025

1. IDENTIFICATION

Product name:	LOCTITE SI 5600 A known as	IDH number:	1253201
	LOCTITE® 5600™ ADHESIVE/SEALAN		
Product type/	Silicone sealant	Item number:	1253201
Recommended use:			
Restriction of Use:	None identified	Region:	United States
Company address:		Contact information:	
Henkel Corporation		Telephone:	+1 (860) 571-5100
One Henkel Way		MEDICAL EMERGENCY Phone:	Poison Control Center
Rocky Hill, Connecticut 06067		1-877-671-4608 (toll free) or 1-303-592-1711	
		TRANSPORT EMERGENCY Phone:	CHEMTREC
		1-800-424-9300 (toll free) or 1-703-527-3887	
		MEDICAL EMERGENCY Phone:	Poison Control Center
		1-877-671-4608 (toll free) or 1-303-592-1711	
		TRANSPORT EMERGENCY Phone:	CHEMTREC
		1-800-424-9300 (toll free) or 1-703-527-3887	
		Internet:	www.henkelna.com

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW****WARNING:** H320 - CAUSES EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2B

PICTOGRAM(S)

None

Precautionary Statements

Prevention:	P264 - Wash affected area thoroughly after handling.
Response:	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313 - If eye irritation persists: Get medical attention.
Storage:	Not prescribed
Disposal:	Not prescribed

Other hazards Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Hazardous Component(s)	CAS Number	Weight %*
Calcium carbonate	471-34-1	30 - 60

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation:	Move to fresh air. If symptoms develop and persist, get medical attention.
Skin contact:	Wipe off paste with paper towel or cloth. Wash with soap and water. If skin irritation persists, call a physician.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If adverse health effects develop seek medical attention.
Ingestion:	Do not induce vomiting. In case of adverse health effects seek medical advice.
Most important symptoms and effects (acute and delayed):	The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.
Indication of any immediate medical attention / special treatment needed:	Not available.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Foam, dry chemical or carbon dioxide.
Improper extinguishing agents:	Not available.
Special firefighting procedures:	None
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Oxides of carbon. Oxides of silicon. Formaldehyde

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Scrape up as much material as possible. Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling:	Avoid contact with eyes, skin and clothing. Do not wear contact lenses.
Storage:	For safe storage, store between 8 °C (46.4 °F) and 28 °C (82.4 °F)
For information on product shelf life, please review labels on container or check the Technical Data Sheet.	

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Calcium carbonate	3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 15 MPPCF TWA Respirable fraction. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction.	None	None

Engineering controls:

General room ventilation is usually adequate. Use local exhaust ventilation if the potential for airborne exposure exists.

Respiratory protection:

No personal respiratory protective equipment normally required. Breathing apparatus only if aerosol or dust is formed.

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin contact. Use of Butyl or Nitrile Rubber gloves is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	White
Odor:	Characteristic
Odor threshold:	Not available.
pH:	Not applicable, Product is non-soluble (in water).
Vapor pressure:	< 10 mm hg (20 °C (68°F))
Boiling point/range:	> 100 °C (> 212°F)
Melting point/ range:	Not applicable, Product is a liquid
Density/Relative density:	1.25 - 1.30
Relative vapor density:	> 1 20 °C
Flash point:	> 93 °C (> 199.4 °F)
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	The product is not flammable.
Evaporation rate:	Not applicable
Solubility:	Insoluble Water
Partition coefficient n-octanol/water (logarithmic value):	Not available.
VOC content:	1.5 %; 35.2 g/l Estimated
Dynamic viscosity:	Not available.
Kinematic viscosity:	> 20.5 mm2/s
Particle characteristics:	Not applicable, Product is a liquid
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Oxides of silicon. Formaldehyde
Incompatible materials:	Acids and bases. Oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Excessive heat.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit.
Skin contact:	May cause skin irritation.
Eye contact:	Causes serious eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed. Not expected under normal conditions of use.

Hazardous Component(s)	LD50s and LC50s
Calcium carbonate	Oral LD50 (Rat) = 6,450 mg/kg Oral LD50 (Mouse) = 6,450 mg/kg Inhalation LC50 (Rat, 4 h) = > 3 mg/l

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
Calcium carbonate	Nuisance dust		

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Calcium carbonate	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Cured rubber can be incinerated or landfilled following EPA and local regulations. Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis.
CERCLA/SARA Section 311/312:	Please refer to the GHS classification in Section 2
CERCLA/SARA Section 313:	None above reporting de minimis.
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
-----------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 9, 11

Prepared by: Product Safety and Regulatory Affairs

Issue date: 08/11/2025

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.