

Revision Number: 005.0 Issue date: 08/30/2019

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE SF 7601 EQUIPMENT FLUSH IDH number: 135238

SOLVENT known as EQUIPMENT

FLUSHING SOLVENT Sol

Product type/use:CleanerItem number:12121Restriction of Use:None identifiedRegion:United States

Company address: Contact information:

Henkel Corporation Telephone: +1 (860) 571-5100
One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center

Rocky Hill, Connecticut 06067

1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

This product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal. Please contact Henkel Product Safety & Regulatory Affairs for further information.

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE DROWSINESS OR DIZZINESS.

MAY CAUSE GENETIC DEFECTS.

MAY CAUSE CANCER.

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR

REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
GERM CELL MUTAGENICITY	1B
CARCINOGENICITY	1B
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2

PICTOGRAM(S)



Precautionary Statements

IDH number: 135238

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, clothing,

eye and face protection.

Product name: LOCTITE SF 7601 EQUIPMENT FLUSH SOLVENT known as EQUIPMENT FLUSHING SOLVENT Sol

Response: IF ON SKIN: Wash with plenty of water, IF INHALED: Remove victim to fresh air and keep at

rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation occurs: Get medical attention. Take

off contaminated clothing.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Methylene chloride	75-09-2	80 - 100
Propylene oxide	75-56-9	0.1 - 1

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. Get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious

person. Get medical attention.

Symptoms: See Section 11.

IDH number: 135238

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear a self-contained breathing apparatus with a full face piece operated in

pressure-demand or other positive pressure mode.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat.

Hazardous combustion products: Oxides of carbon. Hydrochloric acid. Phosgene. Toxic and irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Product name: LOCTITE SF 7601 EQUIPMENT FLUSH SOLVENT known as EQUIPMENT FLUSHING SOLVENT Sol

Clean-up methods: Ensure adequate ventilation. Isolate area. Keep unnecessary personnel

away. Soak up with inert absorbent. Store in a closed container until ready for disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to

clean up.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Refer to Section 8.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Methylene chloride	50 ppm TWA	12.5 ppm OSHA_ACT 25 ppm TWA 125 ppm STEL	None	None
Propylene oxide	2 ppm TWA (Dermal sensitization)	100 ppm (240 mg/m3) PEL	None	None

Engineering controls: Ensure adequate ventilation. Local exhaust ventilation is recommended when

general ventilation is not sufficient to control airborne contamination below

occupational exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection:Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Viton gloves. Nitrile gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color:Clear colorlessOdor:Sweet, SolventOdor threshold:Not available.pH:Not available.

Vapor pressure: 350 mbar (20 °C (68°F))

Boiling point/range: Not available.

Melting point/ range: Not available.

Specific gravity: 1.31 at 25 °C (77°F)

Vapor density: 2.93

Flash point: No flash point up to 200 °C

Flammable/Explosive limits - lower: Not available.
Flammable/Explosive limits - upper: Not available.
Autoignition temperature: 556.00 °C (1,032.8 °F)

Flammability:

Flammability:

Not applicable

Evaporation rate:

Solubility in water:

Slightly soluble

Partition coefficient (n-octanol/water):

VOC content:

Not available.

Not available.

VOC content:

VOC content:

Not available.

IDH number: 135238 Product name: LOCTITE SF 7601 EQUIPMENT FLUSH SOLVENT known as EQUIPMENT FLUSHING SOLVENT Sol

Viscosity:Not available.Decomposition temperature:Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing.

Hazardous decomposition

products:

Oxides of carbon. Irritating and toxic gases or fumes may be released during a fire. Hydrogen

chloride. Phosgene. Irritating organic fragments.

Incompatible materials: Acids and bases. Oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Avoid excessive heat and ignition sources. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Exposure to high doses may cause central nervous system depression. Such doses may also

cause adverse effects in the liver, kidneys, and lungs. The solvent vapors can be harmful and cause headache, nausea, and intoxication. Caboxyhemoglobin levels can be elevated in persons exposed to methylene chloride and can cause substantial stress on the cardiovascular system. This elevation can be additive to the increase caused by smoking and other carbon

monoxide sources.

Skin contact: Causes skin irritation. Prolonged single exposure can result in progressively severe burning

sensation and redness.

Eye contact: Causes serious eye irritation.

Ingestion: Harmful if swallowed. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Methylene chloride	Oral LD50 (Rat) = 1,600 mg/kg	Blood, Cardiac, Central nervous system, Corrosive, Irritant, Kidney, Liver, Some evidence of carcinogenicity
Propylene oxide	Oral LD50 (Rat) = 380 mg/kg Dermal LD50 (Rabbit) = 1,245 mg/kg	Corrosive, Irritant, Mutagen, Nervous System, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Methylene chloride	Reasonably Anticipated to be a Human Carcinogen.	Group 2A	Yes
Propylene oxide	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

IDH number: 135238

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Dichloromethane

Hazard class or division: 6.1
Identification number: UN 1593
Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name: Dichloromethane

Hazard class or division: 6.1
Identification number: UN 1593
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: DICHLOROMETHANE

Hazard class or division: 6.1
Identification number: UN 1593
Packing group: III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 6 Risk Management Rules This product is not and cannot be distributed in commerce (as defined in TSCA section

3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal. Please contact Henkel Product Safety & Regulatory Affairs for further

information.

TSCA 12 (b) Export Notification: Methylene chloride (CAS# 75-09-2).

CERCLA/SARA Section 302 EHS: Propylene oxide (CAS# 75-56-9). Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Methylene chloride (CAS# 75-09-2). Propylene oxide (CAS# 75-56-9).

Methylene chloride (CAS# 75-09-2) 1,000 lbs. (454 kg) Propylene oxide (CAS# 75-56-9) 100 lbs. (45.4 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CERCLA Reportable quantity:

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

IDH number: 135238 Product name: LOCTITE SF 7601 EQUIPMENT FLUSH SOLVENT known as EQUIPMENT FLUSHING SOLVENT Sol

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 1, 15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 08/30/2019

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 135238 Product name: LOCTITE SF 7601 EQUIPMENT FLUSH SOLVENT known as EQUIPMENT FLUSHING SOLVENT Sol