

Revision Number: 006.0

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

Product type/use: Anaero Restriction of Use: None ic Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

569 Thread Sealant High Strength Hydraulic Sealant Anaerobic Sealant None identified

IDH number:135492Item number:56931Region:United StatesContact information:Telephone: +1 (860) 571-5100MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW		
WARNING:	CAUSES SKIN IRRITATION.	
	MAY CAUSE AN ALLERGIC SKIN REACTION.	
	CAUSES SERIOUS EYE IRRITATION.	
	MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR	
	REPEATED EXPOSURE.	

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2



Precautionary Statements

Prevention:	Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling.
	Contaminated work clothing should not be allowed out of the workplace. Wear protective
	gloves, eye protection, and face protection.
Response:	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several
-	minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical
	attention if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation
	persists: Get medical attention. Take off contaminated clothing.
Storage:	Not prescribed
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local
•	governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Polyglycol dioctanoate	18268-70-7	10 - 30

IDH number: 135492

Methacrylic acid, isobutyl ester, polymer with butyl methacrylate	9011-53-4	10 - 30
Cumene hydroperoxide	80-15-9	1 - 5
Cumene	98-82-8	0.1 - 1
n-butyl methacrylate	97-88-1	0.1 - 1
isobutyl methacrylate	97-86-9	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

Inhalation:Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.Skin contact:Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get medical attention.Eye contact:Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.Ingestion:Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.Symptoms:See Section 11.Extinguishing media:Water spray (fog), foam, dry chemical or carbon dioxide.Special firefighting procedures:Water spray (fog), foam, dry chemical or carbon dioxide.Unusual fire or explosion hazards:Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.Hazardous combustion products:Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vanours	4. FIF	RST AID MEASURES
Events Contaminated clothing and footwear. Wash clothing before reuse. Get medical attention. Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention. Symptoms: See Section 11. Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide. Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray. Unusual fire or explosion hazards: Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers. Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic	Inhalation:	
Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention. Symptoms: See Section 11. 5. FIRE FIGHTING MEASURES Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide. Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray. Unusual fire or explosion hazards: Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers. Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic	Skin contact:	contaminated clothing and footwear. Wash clothing before reuse. Get medical
person. Get medical attention. Symptoms: See Section 11. 5. FIRE FIGHTING MEASURES Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide. Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray. Unusual fire or explosion hazards: Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers. Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic	Eye contact:	
5. FIRE FIGHTING MEASURES Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide. Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray. Unusual fire or explosion hazards: Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers. Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic	Ingestion:	
Extinguishing media:Water spray (fog), foam, dry chemical or carbon dioxide.Special firefighting procedures:Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.Unusual fire or explosion hazards:Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.Hazardous combustion products:Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic	Symptoms:	See Section 11.
Special firefighting procedures:Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.Unusual fire or explosion hazards:Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.Hazardous combustion products:Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic	5. FIRE	FIGHTING MEASURES
turn-out gear. In case of fire, keep containers cool with water spray.Unusual fire or explosion hazards:Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.Hazardous combustion products:Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic	Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic	Special firefighting procedures:	
1	Unusual fire or explosion hazards:	
	Hazardous combustion products:	Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapours.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.	
Clean-up methods:	Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean- up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.	
7. HANDLING AND STORAGE		

Handling:	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Keep container closed. Refer to Section 8.
Storage:	For safe storage, store between 0 °C (32°F) and 32 °C (89.6 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol dioctanoate	None	None	None	None
Methacrylic acid, isobutyl ester, polymer with butyl methacrylate	None	None	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
Cumene	5 ppm TWA	50 ppm (245 mg/m3) PEL (SKIN)	None	None
n-butyl methacrylate	None	None	None	None
isobutyl methacrylate	None	None	None	None

Engineering controls:

Respiratory protection:

Eye/face protection:

Skin protection:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves. Butyl rubber gloves. Natural rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Flammability: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content: Viscosity: Decomposition temperature:

Liquid Brown Mild Not available. Not applicable < 5 mm hg (27 °C (80.6 °F)) Not available. Not available. 1.049 Not available. > 93.3 °C (> 199.94 °F) Tagliabue closed cup Not available. Not available. Not available. Not applicable Not available. Sliaht Not available. 0.81 %; 7.74 g/l Not available. Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing. Polymerization may occur at elevated temperature or in the presence of incompatible materials.
Hazardous decomposition products:	Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapours.
Incompatible materials:	Strong oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: S

Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapors or mists of the product may be irritating to the respiratory system.
Skin contact:	Causes skin irritation.
Eye contact:	Causes serious eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Polyglycol dioctanoate	None	Irritant
Methacrylic acid, isobutyl ester, polymer with butyl methacrylate	None	Irritant
Cumene hydroperoxide	None	Allergen, Central nervous system, Corrosive, Irritant, Mutagen
Cumene	Oral LD50 (Rat) = 2.91 g/kg Oral LD50 (Rat) = 1,400 mg/kg	Central nervous system, Irritant, Lung
n-butyl methacrylate	Oral LD50 (Mouse) = 15.8 g/kg Oral LD50 (Rat) = 22,600 mg/kg Oral LD50 (Rat) = 16.0 g/kg Oral LD50 (Mouse) = 12,900 mg/kg Dermal LD50 (Rabbit) = 11,300 mg/kg Inhalation LC50 (Rat, 4 h) = 4910 ppm	Irritant, Allergen
isobutyl methacrylate	Oral LD50 (Mouse) = 11,990 mg/kg	Irritant, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyglycol dioctanoate	No	No	No
Methacrylic acid, isobutyl ester, polymer with butyl methacrylate	No	No	No
Cumene hydroperoxide	No	No	No
Cumene	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No
n-butyl methacrylate	No	No	No
isobutyl methacrylate	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:		
Hazard class or division:		
Identification number:		
Packing group:		

Not regulated None None None

International Air Transportation (ICAO/IATA)

Proper shipping name: Hazard class or division: Identification number: Packing group: Not regulated None None None

Water Transportation (IMO/IMDG)

Proper shipping name: Hazard class or division: Identification number: Packing group: Not regulated None None None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health, Delayed Health This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Cumene hydroperoxide (CAS# 80-15-9). Cumene (CAS# 98-82-8).
CERCLA Reportable quantity:	Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2, 3, 8, 11, 13, 15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 08/18/2021

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.