# Safety Data Sheet



**Revision Number: 006.2** Issue date: 09/02/2022

### PRODUCT AND COMPANY IDENTIFICATION

**Product name: LOCTITE AA 330 1K GENERAL BONDING ACRYLIC known as** 

**LOCTITE DEPEND 250ML TB** 

Product type/use: Acrylic Adhesive Restriction of Use: None identified

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

IDH number: 1689700

Item number: 1689700 Region: **United States** 

Contact information: Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

### HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER: COMBUSTIBLE LIQUID.

CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE DAMAGE.

MAY CAUSE RESPIRATORY IRRITATION. SUSPECTED OF CAUSING CANCER.

MAY DAMAGE FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1
CARCINOGENICITY	2
REPRODUCTIVE TOXICITY	1B
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3





#### **Precautionary Statements**

Obtain special instructions before use. Do not handle until all safety precautions have been Prevention:

read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of

the workplace. Wear protective gloves, clothing, eye and face protection. IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at Response:

rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing. In case of

fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

IDH number: 1689700 Product name: LOCTITE AA 330 1K GENERAL BONDING ACRYLIC known as LOCTITE DEPEND

250ML TB

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Tetrahydrofurfuryl methacrylate	2455-24-5	30 - 60	
methacrylic acid	79-41-4	5 - 10	
2-Ethylhexyl methacrylate	688-84-6	5 - 10	
1,3-Butylene glycol dimethacrylate	1189-08-8	1 - 5	
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	0.1 - 1	
Talc	14807-96-6	0.1 - 1	
Methyl methacrylate	80-62-6	0.1 - 1	
Cumene hydroperoxide	80-15-9	0.1 - 1	•
1,1,2-Trichloroethane	79-00-5	0.1 - 1	•

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Wash clothing before reuse. Get medical

attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

**Ingestion:** DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

### 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers. In case of fire, keep containers

cool with water spray.

Hazardous combustion products: Oxides of carbon. Irritating organic vapours.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to

prevent entry into water system; wear full protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure

Controls / Personal Protection" prior to clean up.

IDH number: 1689700 Product name: LOCTITE AA 330 1K GENERAL BONDING ACRYLIC known as LOCTITE DEPEND

### 7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do

not taste or swallow. Refer to Section 8.

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Tetrahydrofurfuryl methacrylate	None	None	None	None
methacrylic acid	20 ppm TWA	None	None	None
2-Ethylhexyl methacrylate	None	None	None	None
1,3-Butylene glycol dimethacrylate	None	None	None	None
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
Talc	2 mg/m3 TWA Respirable fraction.	0.1 mg/m3 TWA Respirable. 20 MPPCF TWA 2.4 MPPCF TWA Respirable.	None	50 ppm
Methyl methacrylate	50 ppm TWA 100 ppm STEL (Dermal sensitization)	100 ppm (410 mg/m3) PEL	None	50 ppm
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
1,1,2-Trichloroethane	10 ppm TWA (SKIN)	10 ppm (45 mg/m3) PEL (SKIN)	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

**Skin protection:**Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Neoprene, Butyl-rubber, or nitrile-

rubber gloves.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:AmberOdor:Sharp, IrritatingOdor threshold:Not available.

**pH**: 10

**Vapor pressure:** < 10 mm hg (26.6 °C (79.9 °F))

**Boiling point/range:** > 148.9 °C (> 300°F) **Melting point/ range:** Not available.

Specific gravity: 1.16

Vapor density:Not applicable, Heavier than airFlash point:83 °C (181.4 °F) Tagliabue closed cup

Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Flammability:
Flammability:
Evaporation rate:
Solubility in water:

Not available.
Not applicable
Not available.
Slight

IDH number: 1689700 Product name: LOCTITE AA 330 1K GENERAL BONDING ACRYLIC known as LOCTITE DEPEND

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Decomposition temperature:

Not available.

Not available.

# 10. STABILITY AND REACTIVITY

**Stability**: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing. Polymerization may occur at elevated temperature or in the

presence of incompatible materials.

**Hazardous decomposition** 

products:

IDH number: 1689700

Oxides of carbon. Oxides of sulfur. Toxic chlorides. Irritating organic vapours.

Incompatible materials: Strong oxidizing agents. Strong reducing agents. Strong acids. Alkalis. Free radical initiators.

Oxygen scavengers.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials. Extremes of temperature

and direct sunlight. UV light. Freezing conditions.

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Product name: LOCTITE AA 330 1K GENERAL BONDING ACRYLIC known as LOCTITE DEPEND 250ML TB

### **Potential Health Effects/Symptoms**

**Inhalation:** Inhalation of vapors or mists of the product may be irritating to the respiratory system. May

cause irritation to nose and throat.

**Skin contact:** Causes skin irritation. May cause allergic skin reaction.

Eye contact: Causes serious eye damage.

**Ingestion:** May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects		
Tetrahydrofurfuryl methacrylate	None	Irritant, Allergen		
Oral LD50 (Mouse) = 1,332 mg/k Oral LD50 (Mouse) = 1,600 mg/k Oral LD50 (Mouse) = 1,250 mg/k Oral LD50 (Mouse) = 1,250 mg/k Oral LD50 (Rabbit) = 1,200 mg/k Oral LD50 (Rat) = 1,060 mg/kg Oral LD50 (Rat) = 2,224 mg/kg Dermal LD50 (Rabbit) = 500 mg/k		Corrosive, Irritant, Allergen		
2-Ethylhexyl methacrylate	Oral LD50 (Rat) = > 2,000 mg/kg	Irritant, Allergen		
1,3-Butylene glycol dimethacrylate	None	Irritant, Allergen		
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	Allergen, Irritant		
Talc	None	Irritant, Lung, Some evidence of carcinogenicity		
Methyl methacrylate	Oral LD50 (Rat) = 7,800 mg/kg Oral LD50 (Rabbit) = 6,000 mg/kg Oral LD50 (Rat) = 9,400 mg/kg	Allergen, Irritant, Kidney, Liver, Mutagen, Nervous System, Respiratory		
Cumene hydroperoxide	None	Allergen, Central nervous system, Corrosive, Irritant, Mutagen		
1,1,2-Trichloroethane	Oral LD50 (Rat) = 835 mg/kg Oral LD50 (Rat) = 100 - 200 mg/kg Dermal LD50 (Rabbit) = 5,377 mg/kg	Irritant, Central nervous system, Lung, Liver, Kidney, Immune system, Some evidence of carcinogenicity, Mutagen		

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Tetrahydrofurfuryl methacrylate	No	No	No
methacrylic acid	No	No	No
2-Ethylhexyl methacrylate	No	No	No
1,3-Butylene glycol dimethacrylate	No	No	No
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
Talc	No	No	No
Methyl methacrylate	No	No	No
Cumene hydroperoxide	No	No	No
1,1,2-Trichloroethane	No	No	No

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

# 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None
None

IDH number: 1689700 Product name: LOCTITE AA 330 1K GENERAL BONDING ACRYLIC known as LOCTITE DEPEND 250ML TB

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

None above reporting de minimis

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Fire, Immediate Health, Delayed Health None above reporting de minimis.

CERCLA Reportable quantity: Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3, 8, 9, 11, 13

Prepared by: Product Safety and Regulatory Affairs

**Issue date:** 09/02/2022

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 1689700 Product name: LOCTITE AA 330 1K GENERAL BONDING ACRYLIC known as LOCTITE DEPEND 250ML TB