



Revision Number: 003.0

Issue date: 04/15/2021

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE LB 8017 MO FILM AS
Product type/use: Antiseize
Restriction of Use: None identified
Company address:
 Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067

IDH number: 1786074
Item number: 1786074
Region: United States
Contact information:
 Telephone: +1 (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: EXTREMELY FLAMMABLE AEROSOL.
 CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.
 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
 CAUSES SKIN IRRITATION.
 CAUSES SERIOUS EYE IRRITATION.
 MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL	1
GASES UNDER PRESSURE	Compr. Gas
SKIN IRRITATION	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
ASPIRATION HAZARD	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, and face protection.

Response: IF SWALLOWED: Immediately call a physician or poison control center. IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
acetone	67-64-1	30 - 60
Propane/Isobutane	68476-86-8	10 - 30
Methyl acetate	79-20-9	10 - 30
Solvent naphtha (petroleum), light arom., <0.1% Benzene	64742-95-6	5 - 10
Graphite	7782-42-5	1 - 5
Molybdenum disulphide	1317-33-5	1 - 5
1,2,4-Trimethylbenzene	95-63-6	1 - 5

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If symptoms develop and persist, get medical attention.
Skin contact:	If symptoms develop and persist, get medical attention. Wash affected area immediately with soap and water.
Eye contact:	Get medical attention. Immediately flush eyes with plenty of water for at least 15 minutes.
Ingestion:	Do not induce vomiting: contains petroleum distillates and/or aromatic solvents. Aspiration may cause pulmonary edema and pneumonitis. Get immediate medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Water should be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat. Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. Do not puncture or incinerate pressurized containers.
Hazardous combustion products:	Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Eliminate ignition sources including sources of electrical, static or frictional sparks. Wipe up with adsorbent material (e.g. cloth, fleece). Rinse spill area with water. Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling:	Keep away from heat, spark and flame. Avoid contact with eyes, skin and clothing. Do not breathe gas/fumes/vapor/spray.
Storage:	Keep in a cool, well ventilated area. Store away from heat, sparks, flames, or other sources of ignition. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. For safe storage, store between 8 °C (46.4 °F) and 48 °C (118.4 °F)

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
acetone	250 ppm TWA 500 ppm STEL	1,000 ppm (2,400 mg/m3) PEL	None	None
Propane/Isobutane	None	None	None	None
Methyl acetate	200 ppm TWA 250 ppm STEL	200 ppm (610 mg/m3) PEL	None	None
Solvent naphtha (petroleum), light arom., <0.1% Benzene	None	None	None	None
Graphite	2 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Molybdenum disulphide	10 mg/m3 TWA (as Mo) Inhalable fraction. 3 mg/m3 TWA (as Mo) Respirable fraction.	15 mg/m3 PEL (as Mo) Total dust.	None	None
1,2,4-Trimethylbenzene	25 ppm TWA	None	None	None

Engineering controls:

Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.

Respiratory protection:

When workplace hazards warrant the use of a respirator, appropriate respirators must be used, and a program that follows 29 CFR 1910.134 must be followed.

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Aerosol, Liquid
Color:	Black
Odor:	Solvent
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Specific gravity:	1.3
Vapor density:	Not available.
Flash point:	< -17 °C (< 1.4 °F)
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Not available.
Partition coefficient (n-octanol/water):	Not available.
VOC content:	36.23 % (calculated)
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon.
Incompatible materials:	Oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Extremes of temperature and direct sunlight.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation. May cause central nervous system effects with nausea, dizziness and headache.
Skin contact: Causes skin irritation.
Eye contact: Causes serious eye irritation.
Ingestion: This product may be fatal if it is swallowed. Principal hazard of ingestion is aspiration into the lungs and subsequent pneumonitis.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
acetone	Oral LD50 (Mouse) = 5.2 g/kg Oral LD50 (Mouse) = 3,000 mg/kg Oral LD50 (Rabbit) = 5,340 mg/kg Oral LD50 (Rat) = 5,800 mg/kg Oral LD50 (Rat) = 9,800 mg/kg Dermal LD50 (Rabbit) = 20,000 mg/kg Inhalation LC50 (Rat, 4 h) = 76 mg/l Inhalation LC50 (Rat, 4 h) = 50.1 mg/l	Central nervous system, Irritant
Propane/Isobutane	Inhalation LC50 (Rat, 4 h) = > 13023 ppm Inhalation LC50 (Rat, 4 h) = > 13023 ppm	No Records
Methyl acetate	Oral LD50 (Rabbit) = 3.7 g/kg	Blood, Central nervous system, Eyes, Irritant
Solvent naphtha (petroleum), light arom., <0.1% Benzene	Inhalation LC50 (Rat, 4 h) = > 4,420 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,080 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,200 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5 mg/l Inhalation LC50 (Rat, 4 h) = > 5,240 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,220 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,740 mg/m3 Inhalation LC50 (Rat, 4 h) = >= 5,060 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5.1 mg/l Inhalation LC50 (Rat, 4 h) = > 5,100 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,250 mg/m3 Inhalation LC50 (Rat, 4 h) = > 4,980 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,280 mg/m3 Inhalation LC50 (Rat, 4 h) = > 7,970 mg/m3 Inhalation LC50 (Rat, 4 h) = > 4,970 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,050 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,260 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,830 mg/m3 Inhalation LC50 (Rat, 4 h) = > 4.96 mg/l Inhalation LC50 (Rat, 4 h) = > 5,160 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,000 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,300 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,300 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,610 mg/m3 Inhalation LC50 (Rat, 4 h) = > 7,630 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,000 mg/m3 Inhalation LC50 (Rat, 4 h) = > 7,300 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5.36 mg/l Inhalation LC50 (Rat, 4 h) = > 5.07 mg/l Inhalation LC50 (Rat, 4 h) = > 5,470 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,170 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,020 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,040 mg/m3 Inhalation LC50 (Rat, 4 h) = > 8,530 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,000 mg/m3	Irritant
Graphite	Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3 Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3	Lung
Molybdenum disulphide	None	No Target Organs
1,2,4-Trimethylbenzene	Oral LD50 (Rat) = 6.0 g/kg Dermal LD50 (Rabbit) = > 3,160 mg/kg Inhalation LC50 (Rat, 4 h) = 10,200 mg/m3 Inhalation LC50 (Rat, 4 h) = 18,000 mg/m3	Central nervous system, Irritant, Respiratory

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
acetone	No	No	No
Propane/Isobutane	No	No	No
Methyl acetate	No	No	No
Solvent naphtha (petroleum), light arom., <0.1% Benzene	No	No	No

Graphite	No	No	No
Molybdenum disulphide	No	No	No
1,2,4-Trimethylbenzene	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None
DOT Hazardous Substance(s): Acetone

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Fire, Pressure, Immediate Health, Delayed Health
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). 1,2,4-Trimethylbenzene (CAS# 95-63-6).
CERCLA Reportable quantity: Methyl acetate (CAS# 79-20-9) 100 lbs. (45.4 kg)
acetone (CAS# 67-64-1) 5,000 lbs. (2,270 kg)

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,8,11,13,15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 04/15/2021

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.