

EQ VA20 Volumetric Valve

2084141

PRODUCT DESCRIPTION

The Loctite® EQ VA20 Volumetric Valve is a positive displacement metering valve which dispenses a precise volumetric drop of adhesive with each cycle. The EQ VA20 is designed with a flooded chamber and a single check valve that allows for quick priming and minimizes the need for re-priming. The priming system utilizes a patent pending check valve design which improves the speed and reliability of priming. The innovative displacement rod and seal of the VA20 design provide long dispensing life before rebuild is needed. The Loctite® EQ VA20 is specifically design to dispense drops of Loctite Light Cure Adhesives with precise dosing in the range of 1.5 to 12 microliters.

Product Features

- Volumetric displacement
- Dosing range, 1.5 – 12 microliters
- Cycle rate, 180/minute
- Patent Pending priming system
- Innovative Rod and Seal design
- Slim design
- Fluid inlet fitting – barbed stainless steel
- Field Repairable
- Easily fed from syringe or pressure reservoir

Benefits

- Stroke adjusted positive displacement independent of external influences such as pressure, viscosity, and temperature.
- Quick and reliable priming
- Long Life, >1Million cycles
- Stackable configuration on 19mm [0.75"] centers
- Tool free fluid line hook up that can be oriented 360°

**Excellence is our Passion**

Technical Data:

- Total weight: .13Kg (.3 lbs)
- Size: Diameter = 19mm [0.748"] X 15.3 cm [6.0"] long
- Viscosity Range: 1 to 10000cP
- Wetted Components: PTFE, SS, TiN
- Operating Air pressure: 4 to 7 bar [60 -100 Psi]
- Operating Product pressure: 2 to 5 bar [30 to 70 Psi]
- Fluid Compatibility: Light Cure Acrylics

Items Supplied:

- Loctite® EQ VA20 Volumetric Valve, IDH 2084141
- Equipment Manual
- PTFE lined tubing, 6.4mm OD, 2 meters long
- Air Line 4mm OD, blue, 2 meters
- Air Line 4mm OD, yellow, 2 meters
- Needle Sample Kit

Accessories and Spare Parts:**Note**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits. The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Document # 8904546, Date: 07/15/2016

Henkel Americas

1-800-LOCTITE

www.equipment.loctite.com

Henkel Europe

+49.89.320800.1800

www.henkel.com/industrial

Henkel Asia Pacific

+86.21.2891.8863

www.henkel.com/industrial

For most direct access to local support sales and technical support visit: www.henkel.com/industrial

- Loctite® EQ VA20 Seal Kit, IDH 2084140
- Valve Mounting Bracket, IDH 478602 (Item# 985281)

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits. The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.