



Revision Number: 009.0

Issue date: 11/01/2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE PC 7226 known as	IDH number:	702257
	Loctite(R)Nordbak(R) Pneu Wear		
Product type/use:	Epoxy Hardener	Item number:	98382_229000
Restriction of Use:	None identified	Region:	United States
Company address:	Contact information:		
Henkel Corporation	Telephone: +1 (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
MAY CAUSE AN ALLERGIC SKIN REACTION.
FATAL IF INHALED.
MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED.
MAY CAUSE RESPIRATORY IRRITATION.
SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY INHALATION	2
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1
REPRODUCTIVE TOXICITY	2
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)



Precautionary Statements

Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust or fumes. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection. [In case of inadequate ventilation] wear respiratory protection.
Response:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

IDH number: 702257

Product name: LOCTITE PC 7226 known as Loctite(R)Nordbak(R) Pneu Wear
Page 1 of 8

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Aluminium oxide - non fibrous form	1344-28-1	30 - 60
Silicon carbide	409-21-2	10 - 30
Diethylenetriamine	111-40-0	10 - 30
Silica, vitreous	60676-86-0	5 - 10
4,4'-Isopropylidenediphenol	80-05-7	1 - 5
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	68082-29-1	1 - 5
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	68953-36-6	1 - 5
Calcium carbonate	471-34-1	1 - 5
Silica, amorphous, fumed, cryst.-free	112945-52-5	1 - 5
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	0.1 - 1
Tetraethylene pentamine	112-57-2	0.1 - 1
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Burning produces obnoxious and toxic fumes. Personnel in vicinity and downwind should be evacuated.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Ammonia. Phenolics. Nitric acid. Aldehydes. Nitric acid. Calcium oxide. Chlorine. Toxic fumes. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
-----------------------------------	---

Clean-up methods:

Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Keep container closed.

Storage:

Store in original container until ready to use. Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Keep away from heat, spark and flame.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Aluminium oxide - non fibrous form	1 mg/m3 TWA Respirable fraction. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 50 MPPCF TWA Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Silicon carbide	3 mg/m3 TWA Respirable fraction. 10 mg/m3 TWA Inhalable fraction. 0.1 FIBERS/CM3 TWA Fiber. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust.	None	None
Diethylenetriamine	1 ppm TWA (SKIN)	None	None	None
Silica, vitreous	3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m3 TWA 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust.	None	None
4,4'-Isopropylidenediphenol	None	None	None	None
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	None	None	None	None
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	None	None	None	None
Calcium carbonate	10 mg/m3 TWA Total dust. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 15 MPPCF TWA Respirable fraction. 5 mg/m3 TWA Respirable fraction.	None	None
Silica, amorphous, fumed, cryst.-free	3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m3 TWA 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None

Amines, polyethylenepoly-, triethylenetetramine fraction	None	None	None	None
Tetraethylene pentamine	None	None	1 ppm (5 mg/m3) TWA Aerosol. (SKIN) Aerosol. (Skin sensitizer.)	None
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	None	None	None	None

Engineering controls:	Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s).
Eye/face protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.
Skin protection:	Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Tan
Odor:	Ammoniacal
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	0 mm hg (20 °C (68°F))
Boiling point/range:	Not applicable
Melting point/ range:	Not available.
Specific gravity:	1.537
Vapor density:	Not available.
Flash point:	204 °C (399.2 °F) Pensky Martens closed cup
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Slight
Partition coefficient (n-octanol/water):	Not available.
VOC content:	< 1.0 %; < 10 g/l (estimated value for resin and hardener mixed together)
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Ammonia. Phenolics. Nitric acid. Aldehydes. Calcium oxide. Chlorine. Toxic fumes. Irritating vapors.
Incompatible materials:	Strong Lewis acids. Strong mineral acids. Strong bases. Strong oxidizing agents. Organic halides. Reactive metals. Sodium hypochlorite. Peroxides.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation:	May cause allergic respiratory reaction. These symptoms, which can include chest tightness, wheezing, cough, shortness of breath or asthma attack, could be immediate or delayed (up to several hours after exposure). Mists, vapors or liquid may cause severe irritation or burns.
Skin contact:	Causes skin burns. May cause allergic skin reaction.
Eye contact:	Causes serious eye damage.
Ingestion:	If ingested, severe burns of the mouth and throat may occur, as well as perforation of the esophagus and the stomach.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Aluminium oxide - non fibrous form	Inhalation LC50 (Rat, 4 h) = > 0.888 mg/l Inhalation LC50 (Rat, 4 h) = > 2.3 mg/l	Irritant, Nuisance dust, Corrosive
Silicon carbide	None	Nuisance dust
Diethylenetriamine	Oral LD50 (Rat) Approximate 1,140 mg/kg Oral LD50 (Rat) = 1,080 mg/kg Oral LD50 (Rat) = 2.33 g/kg	Allergen, Irritant, Eyes
Silica, vitreous	None	Nuisance dust
4,4'-Isopropylidenediphenol	Oral LD50 (Rat) = 4,100 mg/kg Oral LD50 (Rat) = 3,300 mg/kg	Allergen, Blood, Irritant, Kidney, Reproductive, Spleen
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	None	No Records
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	None	No Records
Calcium carbonate	Oral LD50 (Rat) = 6,450 mg/kg Oral LD50 (Mouse) = 6,450 mg/kg Inhalation LC50 (Rat, 4 h) = > 3 mg/l	Nuisance dust
Silica, amorphous, fumed, cryst.-free	None	No Data
Amines, polyethylenepoly-, triethylenetetramine fraction	None	No Data
Tetraethylene pentamine	Oral LD50 (Rat) = 3.99 g/kg Oral LD50 (Rat) = 2.1 g/kg Dermal LD50 (Rabbit) = 0.66 g/kg	Irritant, Mutagen, Allergen
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Inhalation LC50 (Rat, 4 h) = > 1.49 - < 2.44 mg/l	Irritant, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Aluminium oxide - non fibrous form	No	No	No
Silicon carbide	No	Group 2A	No
Diethylenetriamine	No	No	No
Silica, vitreous	No	No	No
4,4'-Isopropylidenediphenol	No	No	No
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	No	No	No
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	No	No	No
Calcium carbonate	No	No	No
Silica, amorphous, fumed, cryst.-free	No	No	No
Amines, polyethylenepoly-, triethylenetetramine fraction	No	No	No
Tetraethylene pentamine	No	No	No
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Amines, solid, corrosive, n.o.s. (Diethylenetriamine)
Hazard class or division: 8
Identification number: UN 3259
Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name: Amines, solid, corrosive, n.o.s. (Diethylenetriamine)
Hazard class or division: 8
Identification number: UN 3259
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (Diethylenetriamine)
Hazard class or division: 8
Identification number: UN 3259
Packing group: III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis.
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). 4,4'-Isopropylidenediphenol (CAS# 80-05-7).
California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,8,11

Prepared by: Product Safety and Regulatory Affairs

Issue date: 11/01/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.