



Revision Number: 005.0

Issue date: 12/07/2021

1. PRODUCT AND COMPANY IDENTIFICATION

| | | | |
|-------------------------------|---|---------------------|---------------|
| Product name: | LOCTITE LB N-5000 HIGH PERFORMANCE ANTI-SEIZE known as N-5000 High Purity Anti-Seize | IDH number: | 234282 |
| Product type/use: | Lubricant | Item number: | 51246 |
| Restriction of Use: | None identified | Region: | United States |
| Company address: | Contact information: | | |
| Henkel Corporation | Telephone: +1 (860) 571-5100 | | |
| One Henkel Way | MEDICAL EMERGENCY Phone: Poison Control Center | | |
| Rocky Hill, Connecticut 06067 | 1-877-671-4608 (toll free) or 1-303-592-1711 | | |
| | TRANSPORT EMERGENCY Phone: CHEMTREC | | |
| | 1-800-424-9300 (toll free) or 1-703-527-3887 | | |
| | Internet: www.henkelna.com | | |

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SKIN IRRITATION.
MAY CAUSE AN ALLERGIC SKIN REACTION.
CAUSES SERIOUS EYE IRRITATION.
SUSPECTED OF CAUSING CANCER.
CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

| HAZARD CLASS | HAZARD CATEGORY |
|--|-----------------|
| SKIN IRRITATION | 2 |
| EYE IRRITATION | 2A |
| SKIN SENSITIZATION | 1 |
| CARCINOGENICITY | 2 |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE | 1 |

PICTOGRAM(S)



Precautionary Statements

| | |
|--------------------|--|
| Prevention: | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection. |
| Response: | IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. |
| Storage: | Store locked up. |
| Disposal: | Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations. |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

IDH number: 234282

Product name: LOCTITE LB N-5000 HIGH PERFORMANCE ANTI-SEIZE known as N-5000 High Purity Anti-Seize

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* |
|------------------------|------------|-------------|
| White mineral oil~ | | 30 - 60 |
| Graphite | 7782-42-5 | 10 - 30 |
| Nickel | 7440-02-0 | 10 - 30 |
| Kaolin | 1332-58-7 | 1 - 5 |

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

| | |
|----------------------------|--|
| Inhalation: | Move to fresh air. If symptoms develop and persist, get medical attention. |
| Skin contact: | Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention. Wash clothing before reuse. |
| Eye contact: | Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention. |
| Ingestion: | Aspiration may cause pulmonary edema and pneumonitis. Get medical attention. Do not induce vomiting. |
| Symptoms: | See Section 11. |
| Notes to physician: | Aspiration may cause pulmonary edema or aspiration pneumonia. |

5. FIRE FIGHTING MEASURES

| | |
|---|--|
| Extinguishing media: | Foam, extinguishing powder, carbon dioxide. |
| Special firefighting procedures: | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray. |
| Unusual fire or explosion hazards: | None |
| Hazardous combustion products: | Oxides of carbon. Oxides of nickel. Oxides of aluminum. Metal vapors. |

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

| | |
|-----------------------------------|--|
| Environmental precautions: | Do not allow product to enter sewer or waterways. |
| Clean-up methods: | Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. |

7. HANDLING AND STORAGE

| | |
|------------------|---|
| Handling: | Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. |
| Storage: | Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|------------------------|--|---|-----------|-------|
| White mineral oil~ | 5 mg/m3 TWA mist 10 mg/m3 STEL mist | 5 mg/m3 TWA mist | None | None |
| Graphite | 2 mg/m3 TWA Respirable fraction. | 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. | None | None |
| Nickel | 1.5 mg/m3 TWA Inhalable fraction. | 1 mg/m3 PEL (as Ni) | None | None |
| Kaolin | 2 mg/m3 TWA Respirable fraction. | 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. | None | None |

Engineering controls:

Use positive down-draft exhaust ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA regulations for respirator use (29 CFR 1910.134).

Eye/face protection:

Safety goggles or safety glasses with side shields. Safety showers and eye wash stations should be available.

Skin protection:

Neoprene or oil resistant gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|-------------------------------------|
| Physical state: | Paste |
| Color: | Gray |
| Odor: | Petroleum |
| Odor threshold: | Not available. |
| pH: | Not available. |
| Vapor pressure: | < 5 mm hg (80 °F (26.7 °C)) |
| Boiling point/range: | Not available. |
| Melting point/ range: | Not available. |
| Specific gravity: | 1.2 ()GRP 1 |
| Vapor density: | Heavier than air. |
| Flash point: | 218 °C (424.4 °F) |
| Flammable/Explosive limits - lower: | Not available. |
| Flammable/Explosive limits - upper: | Not available. |
| Autoignition temperature: | Not available. |
| Flammability: | Not applicable |
| Evaporation rate: | Slower than butyl acetate. |
| Solubility in water: | Negligible |
| Partition coefficient (n-octanol/water): | Not available. |
| VOC content: | Essentially Zero (Exempt Compounds) |
| Viscosity: | Not available. |
| Decomposition temperature: | Not available. |

10. STABILITY AND REACTIVITY

| | |
|--|--|
| Stability: | Stable under normal conditions of storage and use. |
| Hazardous reactions: | Will not occur. |
| Hazardous decomposition products: | Oxides of carbon. Oxides of nickel. Oxides of aluminum. Metal oxide fumes. |
| Incompatible materials: | Strong oxidizing agents. |
| Reactivity: | Not available. |
| Conditions to avoid: | Keep away from heat, ignition sources and incompatible materials. |

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

| | |
|----------------------|---|
| Inhalation: | Inhalation of vapors or mists of the product may be irritating to the respiratory system. |
| Skin contact: | Causes skin irritation. May cause allergic skin reaction. |
| Eye contact: | Causes serious eye irritation. |
| Ingestion: | May cause gastrointestinal tract irritation if swallowed. |

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects |
|------------------------|--|--------------------------------------|
| White mineral oil~ | None | Irritant |
| Graphite | Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3 Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3 | Lung |
| Nickel | None | No Data |
| Kaolin | Oral LD50 (Rat) = > 5,000 mg/kg Dermal LD50 (Rat) = > 5,000 mg/kg | Nuisance dust |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|------------------------|---|-----------------|---|
| White mineral oil~ | No | No | No |
| Graphite | No | No | No |
| Nickel | Reasonably Anticipated to be a Human Carcinogen. | Group 2B | No |
| Kaolin | No | No | No |

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

| | |
|------------------------------------|---|
| Proper shipping name: | RQ, Environmentally hazardous substance, liquid, n.o.s. |
| Hazard class or division: | 9 |
| Identification number: | UN 3082 |
| Packing group: | III |
| DOT Hazardous Substance(s): | Nickel |

International Air Transportation (ICAO/IATA)

Proper shipping name: RQ, Environmentally hazardous substance, liquid, n.o.s.
Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Hazard class or division: 9
Identification number: UN 3082
Packing group: III

15. REGULATORY INFORMATION**United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Nickel (CAS# 7440-02-0).
CERCLA Reportable quantity: Nickel (CAS# 7440-02-0) 100 lbs. (45.4 kg)
California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3,8,11,13,14,15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 12/07/2021

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.