



Revision Number: 003.0

Issue date: 06/17/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE LB 8209 DUP OR LU PFPE	IDH number:	234339
	HIGH PERF known as Dupont®		
	Krytox® RFE PFPE Lubri		
Product type:	Lubricant	Item number:	29710
Restriction of Use:	None identified	Region:	United States
Company address:	Contact information:		
Henkel Corporation	Telephone: (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.

HAZARD CLASS	HAZARD CATEGORY
None	None

PICTOGRAM(S)

None

Precautionary Statements

Prevention:	Not prescribed
Response:	Not prescribed
Storage:	Not prescribed
Disposal:	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
None	None	None

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Remove contaminated clothing and footwear. Wash with soap and water. If symptoms develop and persist, get medical attention. Wash clothing before reuse.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	Do not induce vomiting. Immediately give large quantities of water to drink. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.
Notes to physician:	If ingested, irrigate the stomach using activated charcoal in addition. Note: to prepare activated charcoal slurry, mix thoroughly 50 g of activated charcoal in 400 ml (about 2 cups) water. Administer 5mg/kg, or 350 ml for an average adult.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Will not burn. Use media appropriate for surrounding material.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Not available.
Hazardous combustion products:	Toxic fluorine compounds.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not flush with water. Do not allow product to enter sewer or waterways.
Clean-up methods:	Ensure adequate ventilation. Remove all sources of ignition. Scrape up as much material as possible. Remove the absorbed material, and place in an appropriate chemical waste container for disposal.

7. HANDLING AND STORAGE

Handling:	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not store or consume food, drink, or tobacco products in areas where they may become contaminated with this material. Refer to Section 8.
Storage:	Keep container closed. Keep away from heat and flames to avoid decomposition products.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
None	None	None	None	None

Engineering controls:	Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.
Respiratory protection:	Where the potential exists for exposure to decomposition products due to heating or elevated temperatures, wear NIOSH approved respiratory protection as appropriate.
Eye/face protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.
Skin protection:	Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Solid, Waxy, Grease
Color:	White
Odor:	Odorless
Odor threshold:	Not available.
pH:	Neutral
Vapor pressure:	0.0000001 mm hg (20 °C (68°F))
Boiling point/range:	Not available.
Melting point/ range:	320 °C (608°F)
Specific gravity:	1.89 - 1.93
Vapor density:	Not available.
Flash point:	Does not ignite.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Evaporation rate:	Not available.
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	Essentially Zero (Exempt Compounds)
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Heating above 260-290°C (500-554°F) may form potentially toxic fluorine compounds.
Incompatible materials:	Not available.
Reactivity:	Not available.
Conditions to avoid:	Avoid heating above temperatures of 260-290°C (500-554°F). Depolymerization may occur in the presence of some metal oxides above 288°C (550°F). Decomposition occurs at increasing rates as temperature is raised above 355°C (670°F).

11. TOXICOLOGICAL INFORMATION

Product toxicity data: A single inhalation exposure to PTFE caused irritation of the lungs. A repeated ingestion exposure caused no significant toxicological effects. Long term ingestion exposure altered white blood cell counts.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: Inhalation of Fluorine containing compounds released as decomposition products above 290°C, (554°F) may cause lung irritation and pulmonary edema which require medical attention. Inhalation of fumes or smoke from overheating or burning may cause polymer fume fever, a temporary flu-like illness accompanied by fever, chills, and sometimes coughing. These symptoms generally last approximately 24 hours. Repeated episodes of polymer fume fever may cause lung damage.

Skin contact: May cause skin irritation with discomfort or rash. Prolonged skin contact may cause redness and inflammation of the hair follicles without skin sensitization.

Eye contact: Contact with eyes will cause irritation. Blurred vision. Excess tearing.

Ingestion: Not expected under normal conditions of use.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
None	None	None

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
None	None	None	None

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION**United States Regulatory Information**

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	Ethene, tetrafluoro-, homopolymer (CAS# 9002-84-0).
CERCLA/SARA Section 302 EHS:	None above reporting de minimis
CERCLA/SARA Section 311/312:	Immediate Health
CERCLA/SARA Section 313:	None above reporting de minimis
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
-----------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Catherine Bimler, Regulatory Affairs Specialist

Issue date: 06/17/2014

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.