

# LOCTITE® SF 7611

Known as LOCTITE® Pro Strength Parts Cleaner  
October 2022

## PRODUCT DESCRIPTION

LOCTITE® SF 7611 provides the following product characteristics:

<b>Technology</b>	Solvent based
Chemical Type	Perchloroethylene methyl chloroform
Appearance	Clear liquid
Propellant	Carbon dioxide
<b>Cure</b>	Non-curing
<b>Application</b>	Cleaners
Specific Benefits	<ul style="list-style-type: none"> <li>● Eliminates contamination</li> <li>● No ozone-depleting solvents</li> <li>● Leaves no residue</li> <li>● Fast evaporation</li> <li>● No flash point</li> <li>● Non-corrosive</li> </ul>

LOCTITE® SF 7611 is an industrial strength aerosol formulation specifically designed to aggressively penetrate, dissolve and remove contaminants (i.e. fluid, grease, oil, undercoating and asphalt) from all types of metal assemblies. Typical applications include rotors, drums, caliper units, brake cylinders, springs, clutch discs, and CV joint assemblies.

LOCTITE® SF 7611 can also be used for cleaning parts prior to bonding with Loctite® adhesives.

## TYPICAL PROPERTIES

Specific Gravity @ 25 °C	1.53
Drying Time @ 25 °C, minutes	1.0

## GENERAL INFORMATION

**This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.**

**For safe handling information on this product, consult the Safety Data Sheet (SDS).**

## Handling Precautions

LOCTITE® SF 7611 is aggressive toward paint and certain plastics. These areas must be protected. Any lingering over-spray must be rinsed away.

## Directions for use

### For Disassembly

1. Cover all rubber, plastic and painted areas.
2. Place catch basin on drop cloth under brake assembly.
3. Shake can vigorously.
4. Hold can upright 30 to 45 cm away from area to be cleaned. Spray in a circular motion to, fully saturate the area to be cleaned.
5. Once wetted down, attach the extension tube to spray head to begin cleaning. Start from the top down, making sure all the solvent that runs off the item being cleaned is captured in the catch pan.

### Clean-up

1. After thoroughly washing down the assembly, rags may be used to clean-up as needed, use gloves if required.
2. Contaminants in the catch basin and on the rags should be disposed of properly.

## Not for product specifications

The technical data contained herein are intended as reference only. Please contact your local quality department for assistance and recommendations on specifications for this product.

## Storage

The product is classified as flammable and must be stored in an appropriate manner in compliance with relevant regulations. Do not store near oxidizing agents or combustible materials. Store product in the unopened container in a dry location. Storage information may also be indicated on the product container labelling.

**Optimal Storage: 8 °C to 21 °C. Storage below 8 °C or greater than 28 °C can adversely affect product properties.** Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

## Conversions

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$   
 $\text{kV/mm} \times 25.4 = \text{V/mil}$   
 $\text{mm} / 25.4 = \text{inches}$   
 $\mu\text{m} / 25.4 = \text{mil}$   
 $\text{N} \times 0.225 = \text{lb}$   
 $\text{N/mm} \times 5.71 = \text{lb/in}$   
 $\text{N/mm}^2 \times 145 = \text{psi}$   
 $\text{MPa} \times 145 = \text{psi}$   
 $\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$   
 $\text{N}\cdot\text{m} \times 0.738 = \text{lb}\cdot\text{ft}$   
 $\text{N}\cdot\text{mm} \times 0.142 = \text{oz}\cdot\text{in}$   
 $\text{mPa}\cdot\text{s} = \text{cP}$



**Disclaimer**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

**In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Corporation or Henkel Canada, Inc. the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

**Trademark usage**

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.1

