



Revision Number: 006.0

Issue date: 02/20/2023

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: FIXMASTER FLOOR FILL 40 LB KIT
Product type/use: Epoxy Hardener
Restriction of Use: None identified
Company address:
 Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067

IDH number: 702281
Item number: 99365_1103372
Region: United States
Contact information:
 Telephone: +1 (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: HARMFUL IF SWALLOWED OR IN CONTACT WITH SKIN.
 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
 MAY CAUSE AN ALLERGIC SKIN REACTION.
 FATAL IF INHALED.
 MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING
 DIFFICULTIES IF INHALED.
 MAY CAUSE RESPIRATORY IRRITATION.
 SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

| HAZARD CLASS | HAZARD CATEGORY |
|--|-----------------|
| ACUTE TOXICITY ORAL | 4 |
| ACUTE TOXICITY INHALATION | 2 |
| ACUTE TOXICITY DERMAL | 4 |
| SKIN CORROSION | 1B |
| SERIOUS EYE DAMAGE | 1 |
| RESPIRATORY SENSITIZATION | 1 |
| SKIN SENSITIZATION | 1 |
| REPRODUCTIVE TOXICITY | 2 |
| SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE | 3 |

PICTOGRAM(S)



Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection. [In case of inadequate ventilation] wear respiratory protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

IDH number: 702281

Product name: FIXMASTER FLOOR FILL 40 LB KIT

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* |
|-----------------------------|------------|-------------|
| Diethylenetriamine | 111-40-0 | 60 - 80 |
| 4,4'-Isopropylidenediphenol | 80-05-7 | 30 - 60 |

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

| | |
|----------------------|--|
| Inhalation: | Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. |
| Skin contact: | Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse. |
| Eye contact: | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention. |
| Ingestion: | DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention. |
| Symptoms: | See Section 11. |

5. FIRE FIGHTING MEASURES

| | |
|---|--|
| Extinguishing media: | Water spray (fog), foam, dry chemical or carbon dioxide. |
| Special firefighting procedures: | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. |
| Unusual fire or explosion hazards: | In case of fire, keep containers cool with water spray. Sudden reaction and fire may result if product is mixed with an oxidizing agent. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. |
| Hazardous combustion products: | Oxides of carbon. Oxides of nitrogen. Ammonia. Nitric acid. Irritating organic fragments. Aldehydes. Nitrosamines. |

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

| | |
|-----------------------------------|---|
| Environmental precautions: | Do not allow product to enter sewer or waterways. |
| Clean-up methods: | Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. |

7. HANDLING AND STORAGE

| | |
|------------------|---|
| Handling: | Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8. |
| Storage: | Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Store away from heat, sparks, flames, or other sources of ignition. |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|-----------------------------|------------------|----------|-----------|-------|
| Diethylenetriamine | 1 ppm TWA (SKIN) | None | None | None |
| 4,4'-Isopropylidenediphenol | None | None | None | None |

| | |
|--------------------------------|---|
| Engineering controls: | Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits. |
| Respiratory protection: | Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists. |
| Eye/face protection: | Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available. |
| Skin protection: | Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene, Butyl-rubber, or nitrile-rubber gloves. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---|
| Physical state: | Liquid |
| Color: | Amber |
| Odor: | Ammoniacal |
| Odor threshold: | Not available. |
| pH: | > 7 |
| Vapor pressure: | 0 mm hg (20 °C (68°F)) |
| Boiling point/range: | > 200 °C (> 392°F) |
| Melting point/ range: | Not applicable, Product is a liquid |
| Specific gravity: | 1.03 |
| Vapor density: | > 1 20 °C |
| Flash point: | 102.78 °C (217°F) Pensky Martens closed cup |
| Flammable/Explosive limits - lower: | Not available. |
| Flammable/Explosive limits - upper: | Not available. |
| Autoignition temperature: | Not available. |
| Flammability: | The product is not flammable. |
| Evaporation rate: | Not available. |
| Solubility in water: | Soluble |
| Solubility in water: | Slightly soluble |
| Partition coefficient (n-octanol/water): | Not available. |
| VOC content: | < 1.0 %; < 10 g/l (value for resin and hardener together) (estimated) |
| Viscosity: | Not available. |
| Decomposition temperature: | Not available. |

10. STABILITY AND REACTIVITY

| | |
|--|--|
| Stability: | Stable under normal conditions of storage and use. |
| Hazardous reactions: | None under normal processing. |
| Hazardous decomposition products: | Oxides of carbon. Oxides of nitrogen. Ammonia. Nitric acid. Irritating organic fragments. Aldehydes. Nitrosamines |
| Incompatible materials: | Strong Lewis acids. Strong mineral acids. Strong bases. Strong oxidizing agents. Organic halides. |
| Reactivity: | Not available. |
| Conditions to avoid: | Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials. |

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

| | |
|----------------------|---|
| Inhalation: | May cause allergic respiratory reaction. These symptoms, which can include chest tightness, wheezing, cough, shortness of breath or asthma attack, could be immediate or delayed (up to several hours after exposure). May cause irritation to nose and throat. |
| Skin contact: | Corrosive to skin. Causes skin burns. May cause allergic skin reaction. Rash. Redness. |
| Eye contact: | Causes serious eye damage. Redness. Tissue damage. Excess tearing. Pain and discomfort. Corneal edema may give appearance of "blue haze" or "fog" around lights. |
| Ingestion: | Harmful if swallowed. May cause burns of mouth and throat if swallowed. |

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects |
|-----------------------------|---|---|
| Diethylenetriamine | Oral LD50 (Rat) Approximate 1,140 mg/kg Oral LD50 (Rat) = 1,080 mg/kg Oral LD50 (Rat) = 2.33 g/kg | Allergen, Irritant, Eyes |
| 4,4'-Isopropylidenediphenol | Oral LD50 (Rat) = 4,100 mg/kg Oral LD50 (Rat) = 3,300 mg/kg | Allergen, Blood, Irritant, Kidney, Reproductive, Spleen |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|-----------------------------|----------------|-----------------|--|
| Diethylenetriamine | No | No | No |
| 4,4'-Isopropylidenediphenol | No | No | No |

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

| | |
|----------------------------------|--|
| Proper shipping name: | Amines, liquid, corrosive, n.o.s. (Diethylenetriamine) |
| Hazard class or division: | 8 |
| Identification number: | UN 2735 |
| Packing group: | III |

International Air Transportation (ICAO/IATA)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (Diethylenetriamine)
Hazard class or division: 8
Identification number: UN 2735
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Diethylenetriamine, 4,4'-Isopropylidenediphenol)
Hazard class or division: 8
Identification number: UN 2735
Packing group: III
Marine pollutant: 4,4'-Isopropylidenediphenol

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). 4,4'-Isopropylidenediphenol (CAS# 80-05-7).
California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,9,13

Prepared by: Product Safety and Regulatory Affairs

Issue date: 02/20/2023

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.