

Revision Number: 005.1

Issue date: 06/17/2020

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:LOCTProduct type/use:EpoxyRestriction of Use:NoneCompany address:Henkel CorporationOne Henkel WayRocky Hill, Connecticut 06067

LOCTITE EA E-20HP B HARDENER Epoxy Hardener None identified

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1

PICTOGRAM(S)

### **Precautionary Statements**

Prevention:	Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.
Response:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

### See Section 11 for additional toxicological information.

Hazardous Component(s)	CAS Number	Percentage*
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	10 - 30
Trifluoromethanesulphonic acid, compound with diethylamine (1:1)	60933-18-8	5 - 10
Glycerol	56-81-5	1 - 5
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	1 - 5
Amorphous fumed silica	68611-44-9	1 - 5

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

IDH number: 701984

Diethyleneglycol monoethyl ether	111-90-0	1 - 5
Bis[(dimethylamino)methyl]phenol	71074-89-0	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES			
4,			
Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.		
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.		
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.		
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Giv a conscious person several glasses of water. Never give anything by mouth an unconscious person. Get medical attention.		
Symptoms:	See Section 11.		
5. FIRE FIGHTING MEASURES			
Extinguishing media:	Foam, dry chemical or carbon dioxide.		
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.		
Unusual fire or explosion hazards:	Personnel in vicinity and downwind should be evacuated. Burning produces obnoxious and toxic fumes.		
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Acrolein. Ammonia. Hydrogen fluoride. Nitric acid. Toxic fumes. Irritating vapors.		
6. ACCI	DENTAL RELEASE MEASURES		
personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and rotected personnel.			
Environmental precautions:	Do not allow product to enter sewer or waterways.		
Clean-up methods:	Ensure adequate ventilation. Wear appropriate personal protective equipmer Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean u Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal		

7. HANDLING AND STORAGE

container for disposal.

Handling:	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Keep container closed.
Storage:	Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Keep away from heat, spark and flame. Do not store in reactive metal containers.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	None	None	None	None
Trifluoromethanesulphonic acid, compound with diethylamine (1:1)	None	None	None	None
Glycerol	None	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
2,4,6-tris(dimethylaminomethyl)phenol	None	None	None	None
Amorphous fumed silica	None	0.8 mg/m3 TWA 20 MPPCF TWA	None	None
Diethyleneglycol monoethyl ether	None	None	25 ppm (140 mg/m3) TWA	None
Bis[(dimethylamino)methyl]phenol	None	None	None	None

### **Engineering controls:**

Respiratory protection:

Eye/face protection:

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Flammability: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content: Viscosity: Decomposition temperature:

Liquid Light yellow Mild Not available. Not applicable Not available. Not available. Not available. 1.15 Not available. > 93.4 °C (> 200.12 °F) Setaflash Closed Cup Not available. Not available. Not available. Not applicable Not available. Partially soluble Not available. < 1.0 %; < 10 g/l Estimated Not available. Not available.

#### **10. STABILITY AND REACTIVITY** Stable under normal conditions of storage and use. Hazardous reactions: None under normal processing. Ovidee of control Ovidee of rite - 141 -..... . .. .

Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Acrolein. Ammonia. Nitric acid. Hydrogen fluoride. Toxic fumes. Irritating vapors.
Incompatible materials:	Oxidizing agents. Organic acids. Mineral acids. Peroxides. Sodium hypochlorite. This product slowly corrodes copper, aluminum, zinc and galvanized surfaces.
Reactivity:	Not available.

Conditions to avoid:

Stability:

# **11. TOXICOLOGICAL INFORMATION**

Keep away from heat, ignition sources and incompatible materials.

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

### Potential Health Effects/Symptoms

Inhalation:	Mists, vapors or liquid may cause severe irritation or burns.
Skin contact:	Causes skin burns. May cause allergic skin reaction.
Eye contact:	Causes serious eye damage.
Ingestion:	If ingested, severe burns of the mouth and throat may occur, as well as perforation of the esophagus and the stomach.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	None	Corrosive
Trifluoromethanesulphonic acid, compound with diethylamine (1:1)	None	No Records
Glycerol	None	Irritant, Nuisance dust
2,4,6-tris(dimethylaminomethyl)phenol	None	Irritant, Allergen
Amorphous fumed silica	None	No Target Organs
Diethyleneglycol monoethyl ether	Oral LD50 (Rat) = 1,920 mg/kg   Oral LD50 (Rat) = 5,54 g/kg   Oral LD50 (Rat) = 5,900 mg/kg   Oral LD50 (Rat) = 5,900 mg/kg   Oral LD50 (Mouse) = 6.58 g/kg   Oral LD50 (Rabbit) = 3,620 mg/kg   Oral LD50 (Rat) = 6,500 mg/kg   Oral LD50 (Mouse) = 7,863 mg/kg   Oral LD50 (Mouse) = 7,863 mg/kg   Oral LD50 (Mouse) = 12,400 mg/kg   Oral LD50 (Rabbit) = 4,450 mg/kg   Oral LD50 (Rabbit) = 4,450 mg/kg   Oral LD50 (Rat) = 7,500 mg/kg   Oral LD50 (Mouse) = 7,248 mg/kg   Dermal LD50 (Mouse) = 6,000 mg/kg   Dermal LD50 (Rabbit) = 10,300 mg/kg   Dermal LD50 (Rabbit) = 11,176 mg/kg   Dermal LD50 (Rabbit) = 8,500 mg/kg   Dermal LD50 (Rabbit) = 8,500 mg/kg	Blood, Central nervous system, Irritant, Kidney
Bis[(dimethylamino)methyl]phenol	None	No Records

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	No	No	No
Trifluoromethanesulphonic acid, compound with diethylamine (1:1)	No	No	No
Glycerol	No	No	No
2,4,6-tris(dimethylaminomethyl)phenol	No	No	No
Amorphous fumed silica	No	No	No
Diethyleneglycol monoethyl ether	No	No	No
Bis[(dimethylamino)methyl]phenol	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** 

Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Hazardous waste number:

Dispose of according to Federal, State and local governmental regulations.

It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)	
Proper shipping name:	Amines, liquid, corrosive, n.o.s. (Polyglycol diamine)
Hazard class or division:	8
Identification number:	UN 2735
Packing group:	II
International Air Transportation (ICAO/IATA)	
Proper shipping name:	Amines, liquid, corrosive, n.o.s. (Polyglycol diamine)
Hazard class or division:	8
Identification number:	UN 2735
Packing group:	II
Water Transportation (IMO/IMDG)	
Proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Polyglycol diamine)
Hazard class or division:	8
Identification number:	UN 2735
Packing group:	II

## 15. REGULATORY INFORMATION

### **United States Regulatory Information**

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Diethyleneglycol monoethyl ether (CAS# 111-90-0).
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

## **16. OTHER INFORMATION**

#### This safety data sheet contains changes from the previous version in sections: 3,7,8,11,15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 06/17/2020

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.