



Revision Number: 002.0

Issue date: 01/06/2021

## 1. PRODUCT AND COMPANY IDENTIFICATION

|   |   |
|---|---|
| <b>Product name:</b> LOCTITE ABLESTIK G 757 known as ECCOBOND G-757(8.5LB), 3.86KG<br><b>Product type/use:</b> Epoxy adhesive<br><b>Restriction of Use:</b> None identified<br><b>Company address:</b><br>Henkel Corporation<br>One Henkel Way<br>Rocky Hill, Connecticut 06067 | <b>IDH number:</b> 1188753<br><b>Item number:</b> 1188753<br><b>Region:</b> United States<br><b>Contact information:</b><br>Telephone: +1 (860) 571-5100<br>MEDICAL EMERGENCY Phone: Poison Control Center<br>1-877-671-4608 (toll free) or 1-303-592-1711<br>TRANSPORT EMERGENCY Phone: CHEMTREC<br>1-800-424-9300 (toll free) or 1-703-527-3887<br>Internet: www.henkelna.com |
|---|---|

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER:** CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.  
 MAY CAUSE AN ALLERGIC SKIN REACTION.  
 SUSPECTED OF CAUSING CANCER.  
 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

| HAZARD CLASS                                       | HAZARD CATEGORY |
|--|-----------------|
| SKIN CORROSION                                     | 1C - Corrosive  |
| SERIOUS EYE DAMAGE                                 | 1               |
| SKIN SENSITIZATION                                 | 1               |
| CARCINOGENICITY                                    | 2               |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE | 2               |

### PICTOGRAM(S)



### Precautionary Statements

|                    |  |
|--------------------|--|
| <b>Prevention:</b> | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.   |
| <b>Response:</b>   | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse. |
| <b>Storage:</b>    | Store locked up.   |
| <b>Disposal:</b>   | Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.  |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

IDH number: 1188753

Product name: LOCTITE ABLESTIK G 757 known as ECCOBOND G-757(8.5LB), 3.86KG  
 Page 1 of 6

| Hazardous Component(s)  | CAS Number  | Percentage* |
|---|-------------|-------------|
| Epoxy resin   | Proprietary | 30 - 60     |
| Polyoxyalkylene amine   | Proprietary | 10 - 30     |
| Epoxy resin   | Proprietary | 10 - 30     |
| 1-Chloro-2,3-epoxypropane, polymer with polypropyleneglycol   | 9072-62-2   | 1 - 5       |
| Epoxy resin   | Proprietary | 1 - 5       |
| Siloxanes and Silicones, di-Me, reaction products with silica | 67762-90-7  | 1 - 5       |
| Diuron  | 330-54-1    | 1 - 5       |
| Titanium dioxide  | 13463-67-7  | 1 - 5       |

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

|                      |   |
|----------------------|---|
| <b>Inhalation:</b>   | Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.                                      |
| <b>Skin contact:</b> | Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). Get medical attention. Wash clothing before reuse. |
| <b>Eye contact:</b>  | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.   |
| <b>Ingestion:</b>    | Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.   |
| <b>Symptoms:</b>     | See Section 11.   |

## 5. FIRE FIGHTING MEASURES

|   |  |
|---|--|
| <b>Extinguishing media:</b>               | Water spray (fog), foam, dry chemical or carbon dioxide.   |
| <b>Special firefighting procedures:</b>   | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray. |
| <b>Unusual fire or explosion hazards:</b> | Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.  |
| <b>Hazardous combustion products:</b>     | Oxides of carbon. Oxides of nitrogen. Toxic and irritating vapors.   |

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

|                                   |  |
|-----------------------------------|--|
| <b>Environmental precautions:</b> | Do not allow product to enter sewer or waterways.  |
| <b>Clean-up methods:</b>          | Remove all sources of ignition. Ensure adequate ventilation. Isolate area. Keep unnecessary personnel away. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a closed container until ready for disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. |

## 7. HANDLING AND STORAGE

|                  |   |
|------------------|---|
| <b>Handling:</b> | Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Refer to Section 8.                              |
| <b>Storage:</b>  | For safe storage, store between 2 °C (35.6 °F) and 8 °C (46.4 °F). Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. |

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)  | ACGIH TLV  | OSHA PEL   | AIHA WEEL | OTHER |
|---|--|--|-----------|-------|
| Epoxy resin   | None   | None   | None      | None  |
| Polyoxyalkylene amine   | None   | None   | None      | None  |
| Epoxy resin   | None   | None   | None      | None  |
| 1-Chloro-2,3-epoxypropane, polymer with polypropyleneglycol   | None   | None   | None      | None  |
| Epoxy resin   | None   | None   | None      | None  |
| Siloxanes and Silicones, di-Me, reaction products with silica | 10 mg/m3 TWA<br>Inhalable dust.<br>3 mg/m3 TWA<br>Respirable fraction. | 15 mg/m3 TWA Total dust.<br>5 mg/m3 TWA<br>Respirable fraction.  | None      | None  |
| Diuron  | 10 mg/m3 TWA   | None   | None      | None  |
| Titanium dioxide  | 10 mg/m3 TWA   | 15 mg/m3 PEL Total dust.<br>15 MPPCF TWA<br>Respirable fraction.<br>15 mg/m3 TWA Total dust.<br>50 MPPCF TWA<br>Total dust.<br>5 mg/m3 TWA<br>Respirable fraction. | None      | None  |

### Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

### Respiratory protection:

Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

### Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

### Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|  |                       |
|--|-----------------------|
| Physical state:                          | Liquid                |
| Color:                                   | Gray                  |
| Odor:                                    | Mild                  |
| Odor threshold:                          | Not available.        |
| pH:                                      | Not available.        |
| Vapor pressure:                          | Not available.        |
| Boiling point/range:                     | Not available.        |
| Melting point/ range:                    | Not available.        |
| Specific gravity:                        | 1.2 (Water = 1)       |
| Vapor density:                           | Not available.        |
| Flash point:                             | > 200 °F (> 93.33 °C) |
| Flammable/Explosive limits - lower:      | Not available.        |
| Flammable/Explosive limits - upper:      | Not available.        |
| Autoignition temperature:                | Not available.        |
| Flammability:                            | Not applicable        |
| Evaporation rate:                        | Not available.        |
| Solubility in water:                     | Insoluble             |
| Partition coefficient (n-octanol/water): | Not available.        |
| VOC content:                             | Not available.        |
| Viscosity:                               | Not available.        |
| Decomposition temperature:               | Not available.        |

## 10. STABILITY AND REACTIVITY

|  |  |
|--|--|
| <b>Stability:</b>                        | Stable under normal conditions of storage and use.   |
| <b>Hazardous reactions:</b>              | None under normal processing. Polymerization may occur at elevated temperature or in the presence of incompatible materials. |
| <b>Hazardous decomposition products:</b> | Oxides of carbon. Oxides of nitrogen. Irritating organic vapours.  |
| <b>Incompatible materials:</b>           | Strong oxidizing agents. Strong acids and strong bases.  |
| <b>Reactivity:</b>                       | Not available.   |
| <b>Conditions to avoid:</b>              | High temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.               |

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes

### Potential Health Effects/Symptoms

|                      |   |
|----------------------|---|
| <b>Inhalation:</b>   | May cause respiratory tract irritation. Coughing. Shortness of breath.  |
| <b>Skin contact:</b> | Corrosive to the skin. Contact with the skin or mucous membranes may cause severe irritation and burns. May cause allergic skin reaction. |
| <b>Eye contact:</b>  | Causes serious eye damage. This product is severely irritating to the eyes and may cause eye burns.                                       |
| <b>Ingestion:</b>    | Irritation and corrosive action can occur in the mouth, stomach tissue and digestive tract if swallowed.                                  |

| Hazardous Component(s)  | LD50s and LC50s  | Immediate and Delayed Health Effects                                |
|---|--|---|
| Epoxy resin   | None   | Allergen, Irritant  |
| Polyoxyalkylene amine   | None   | Corrosive, Irritant   |
| Epoxy resin   | None   | Irritant, Allergen  |
| 1-Chloro-2,3-epoxypropane, polymer with polypropyleneglycol   | None   | Allergen, Blood, Bone Marrow, Immune system, Irritant, Reproductive |
| Epoxy resin   | None   | Irritant  |
| Siloxanes and Silicones, di-Me, reaction products with silica | None   | No Data   |
| Diuron  | Oral LD50 (Rat) = 3,400 mg/kg<br>Oral LD50 (Rat) = 1,017 mg/kg   | Irritant, Developmental, Liver                                      |
| Titanium dioxide  | Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l | Irritant, Respiratory, Some evidence of carcinogenicity             |

| Hazardous Component(s)  | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|---|----------------|-----------------|--|
| Epoxy resin   | No             | No              | No                                       |
| Polyoxyalkylene amine   | No             | No              | No                                       |
| Epoxy resin   | No             | No              | No                                       |
| 1-Chloro-2,3-epoxypropane, polymer with polypropyleneglycol   | No             | No              | No                                       |
| Epoxy resin   | No             | No              | No                                       |
| Siloxanes and Silicones, di-Me, reaction products with silica | No             | No              | No                                       |
| Diuron  | No             | No              | No                                       |
| Titanium dioxide  | No             | Group 2B        | No                                       |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Corrosive liquid, basic, organic, n.o.s. (Polyoxy propylene diamine)  
**Hazard class or division:** 8  
**Identification number:** UN 3267  
**Packing group:** III  
**DOT Hazardous Substance(s):** Diuron

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Corrosive liquid, basic, organic, n.o.s. (Polyoxy propylene diamine)  
**Hazard class or division:** 8  
**Identification number:** UN 3267  
**Packing group:** III

### Water Transportation (IMO/IMDG)

**Proper shipping name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Polyoxy propylene diamine, Epoxy resin)  
**Hazard class or division:** 8  
**Identification number:** UN 3267  
**Packing group:** III  
**Marine pollutant:** Epoxy resin

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

**TSCA 12 (b) Export Notification:** None above reporting de minimis

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.  
**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health  
**CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Diuron (CAS# 330-54-1).  
**CERCLA Reportable quantity:** Diuron (CAS# 330-54-1) 100 lbs. (45.4 kg)

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2, 3, 4, 7, 10, 11, 14

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 01/06/2021

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.