



Revision Number: 006.0

Issue date: 08/15/2025

1. IDENTIFICATION

Product name: LOCTITE EA E-30CL HARDENER known as Hysol E-30CL Epoxy ADH Ultra
Product type/Recommended use: Epoxy Hardener
Restriction of Use: None identified
Company address: Henkel Corporation, One Henkel Way, Rocky Hill, Connecticut 06067


IDH number: 701996
Item number: 29329_209539
Region: United States
Contact information: Telephone: +1 (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887
 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: H302 - HARMFUL IF SWALLOWED.
 H314 - CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
 H317 - MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY ORAL	4
SKIN CORROSION	1
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1



Precautionary Statements

Prevention: P261 - Avoid breathing mist/vapours.
 P264 - Wash affected area thoroughly after handling.
 P270 - Do not eat, drink or smoke when using this product.
 P272 - Contaminated work clothing should not be allowed out of the workplace.
 P280 - Wear protective gloves, clothing, eye and face protection.

Response: P301+P312+P330 - IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.
 P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing.
 P304+P340+P310 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 - If skin irritation or rash occurs: Get medical attention.
 P362+P364 - Take off contaminated clothing and wash it before reuse.
 P405 - Store locked up.

Storage: P405 - Store locked up.

Disposal: P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Other hazards Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, reaction products with 3,3'-[oxybis(2,1-ethanediyloxy)]	68585-28-4	60 - 80
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	30 - 60

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin contact:	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical attention.
Most important symptoms and effects (acute and delayed):	The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.
Indication of any immediate medical attention / special treatment needed:	Not available.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Foam, dry chemical or carbon dioxide.
Improper extinguishing agents:	Not available.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	In case of fire, keep containers cool with water spray. Personnel in vicinity and downwind should be evacuated. Burning produces obnoxious and toxic fumes.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Phenolics. Ammonia. Toxic fumes. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
-----------------------------------	---

Clean-up methods:

Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Keep container closed.

Storage:

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Keep away from heat, spark and flame. Store in original container until ready to use.

Shelf Life Statement: Not available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
None	None	None	None	None

Engineering controls:

Use local exhaust ventilation if the potential for airborne exposure exists.

Respiratory protection:

Use a NIOSH approved respirator if ventilation is inadequate.

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Colourless / Colorless to light yellow
Odor:	Amine
Odor threshold:	Not available.
pH:	11
Vapor pressure:	< 700 mbar (21 °C (69.8 °F))
Boiling point/range:	294.8 °C (562.6 °F)
Melting point/ range:	Not applicable, Product is a liquid
Density/Relative density:	0.9 - 1.1
Relative vapor density:	> 1 20 °C
Flash point:	121 °C (249.8 °F)
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	The product is not flammable.
Evaporation rate:	Not available.
Solubility:	largely soluble Water
Solubility:	Partially miscible ketones
Partition coefficient n-octanol/water (logarithmic value):	Not available.
VOC content:	< 1.0 %; < 10 g/l Estimated
Dynamic viscosity:	1,500 - 3,000 mPa.s
Kinematic viscosity:	2,000 mm ² /s
Particle characteristics:	Not applicable, Product is a liquid
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Phenolics. Ammonia. Toxic fumes. Irritating vapors.
Incompatible materials:	Organic acids. Sodium hypochlorite. This product slowly corrodes copper, aluminum, zinc and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. Oxidizing agents. Strong acids and strong bases.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Mists, vapors or liquid may cause severe irritation or burns. May cause respiratory tract irritation.
Skin contact:	Mists, vapors or liquid may cause severe irritation or burns. May cause allergic skin reaction. Causes skin burns.
Eye contact:	Causes serious eye damage.
Ingestion:	If ingested, severe burns of the mouth and throat may occur, as well as perforation of the esophagus and the stomach. Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, reaction products with 3,3'-[oxybis(2,1-ethanedioxy)]	None
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	None

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, reaction products with 3,3'-[oxybis(2,1-ethanedioxy)]			
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Corrosive		

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, reaction products with 3,3'-[oxybis(2,1-ethanedioxy)]	No	No	No
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (Polyglycol diamine)
Hazard class or division: 8
Identification number: UN 2735
Packing group: II

International Air Transportation (ICAO/IATA)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (Polyglycol diamine)
Hazard class or division: 8
Identification number: UN 2735
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Polyglycol diamine)
Hazard class or division: 8
Identification number: UN 2735
Packing group: II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Please refer to the GHS classification in Section 2
CERCLA/SARA Section 313: None above reporting de minimis.
California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,8,9,10,11

Prepared by: Product Safety and Regulatory Affairs

Issue date: 08/15/2025

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.