



Revision Number: 006.2

Issue date: 09/20/2021

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	<b>LOCTITE EA 9460 A HIGH SHEAR STRENGTH EPOXY</b>	<b>IDH number:</b>	475442
<b>Product type/use:</b>	Epoxy resin	<b>Item number:</b>	83134
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	United States
<b>Company address:</b>	<b>Contact information:</b>		
Henkel Corporation	Telephone: +1 (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER:** CAUSES SKIN IRRITATION.  
MAY CAUSE AN ALLERGIC SKIN REACTION.  
CAUSES SERIOUS EYE IRRITATION.  
CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	1

### PICTOGRAM(S)



### Precautionary Statements

<b>Prevention:</b>	Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.
<b>Response:</b>	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
<b>Storage:</b>	Not prescribed
<b>Disposal:</b>	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	60 - 80

IDH number: 475442

Product name: LOCTITE EA 9460 A HIGH SHEAR STRENGTH EPOXY

Quartz (SiO <sub>2</sub> ) respirable particulates (RCS) ≥10%	14808-60-7	10 - 30
Oxirane, 2,2'-[1,4-cyclohexanedilbis (methyleneox	14228-73-0	5 - 10
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	5 - 10
Titanium dioxide	13463-67-7	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
<b>Skin contact:</b>	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
<b>Eye contact:</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
<b>Ingestion:</b>	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
<b>Symptoms:</b>	See Section 11.

## 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
<b>Unusual fire or explosion hazards:</b>	In case of fire, keep containers cool with water spray. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
<b>Hazardous combustion products:</b>	Oxides of carbon. Acids. Aldehydes. Irritating vapors.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Keep container closed.
<b>Storage:</b>	Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Keep away from heat, spark and flame. Store in original container until ready to use.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
Quartz (SiO <sub>2</sub> ) respirable particulates (RCS) >=10%	0.025 mg/m <sup>3</sup> TWA Respirable fraction.	0.05 mg/m <sup>3</sup> TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m <sup>3</sup> OSHA_ACT (Respirable dust.) 0.05 mg/m <sup>3</sup> PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m <sup>3</sup> TWA Respirable.	None	None
Oxirane, 2,2'-[1,4-cyclohexanedilbis (methyleneox	None	None	None	None
Siloxanes and Silicones, di-Me, reaction products with silica	10 mg/m <sup>3</sup> TWA Inhalable dust. 3 mg/m <sup>3</sup> TWA Respirable fraction.	15 mg/m <sup>3</sup> TWA Total dust. 5 mg/m <sup>3</sup> TWA Respirable fraction.	None	None
Titanium dioxide	10 mg/m <sup>3</sup> TWA	15 mg/m <sup>3</sup> PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m <sup>3</sup> TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m <sup>3</sup> TWA Respirable fraction.	None	None

### Engineering controls:

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

### Respiratory protection:

Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

### Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

### Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid, Paste
<b>Color:</b>	White
<b>Odor:</b>	Mild
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not applicable
<b>Vapor pressure:</b>	Negligible
<b>Boiling point/range:</b>	Not available.
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	> 1
<b>Vapor density:</b>	Not available.
<b>Flash point:</b>	> 149 °C (> 300.2 °F) Tagliabue open cup
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Autoignition temperature:</b>	Not available.
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not available.
<b>Solubility in water:</b>	Insoluble
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	< 1 %; < 10 g/l (value for resin and hardener together) (estimated)
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

IDH number: 475442

Product name: LOCTITE EA 9460 A HIGH SHEAR STRENGTH EPOXY

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	None under normal processing.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Acids. Aldehydes. Irritating vapors.
<b>Incompatible materials:</b>	Strong acids. Strong bases. Strong oxidizing agents. Amines. Water.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight. Avoid mixing resin (Part A) and curing agent (Part B) unless you plan to use immediately. Failure to observe these precautions may result in excessive heat build-up causing an exotherm.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes

### Potential Health Effects/Symptoms

<b>Inhalation:</b>	May cause irritation to nose and throat. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.
<b>Skin contact:</b>	Causes skin irritation. May cause allergic skin reaction.
<b>Eye contact:</b>	Causes serious eye irritation.
<b>Ingestion:</b>	Not expected under normal conditions of use.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	Allergen, Irritant
Quartz (SiO <sub>2</sub> ) respirable particulates (RCS) >=10%	None	No Data
Oxirane, 2,2'-[1,4-cyclohexanedilbis (methylenedioxy)]	None	Allergen, Blood, Bone Marrow, Immune system, Irritant, Reproductive
Siloxanes and Silicones, di-Me, reaction products with silica	None	No Data
Titanium dioxide	Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l	Irritant, Respiratory, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
Quartz (SiO <sub>2</sub> ) respirable particulates (RCS) >=10%	Known To Be Human Carcinogen.	Group 1	Yes
Oxirane, 2,2'-[1,4-cyclohexanedilbis (methylenedioxy)]	No	No	No
Siloxanes and Silicones, di-Me, reaction products with silica	No	No	No
Titanium dioxide	No	Group 2B	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

<b>Proper shipping name:</b>	Not regulated
<b>Hazard class or division:</b>	None
<b>Identification number:</b>	None
<b>Packing group:</b>	None

#### International Air Transportation (ICAO/IATA)

<b>Proper shipping name:</b>	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrin resin)
<b>Hazard class or division:</b>	9
<b>Identification number:</b>	UN 3082
<b>Packing group:</b>	III

#### Water Transportation (IMO/IMDG)

<b>Proper shipping name:</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrin resin)
<b>Hazard class or division:</b>	9
<b>Identification number:</b>	UN 3082
<b>Packing group:</b>	III
<b>Marine pollutant:</b>	Bisphenol-A Epichlorhydrin resin

### 15. REGULATORY INFORMATION

#### United States Regulatory Information

<b>TSCA 8 (b) Inventory Status:</b>	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
<b>TSCA 12 (b) Export Notification:</b>	None above reporting de minimis
<b>CERCLA/SARA Section 302 EHS:</b>	None above reporting de minimis.
<b>CERCLA/SARA Section 311/312:</b>	Immediate Health, Delayed Health
<b>CERCLA/SARA Section 313:</b>	None above reporting de minimis.
<b>California Proposition 65:</b>	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

#### Canada Regulatory Information

<b>CEPA DSL/NDL Status:</b>	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
-----------------------------	---

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3,8,11,15

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 09/20/2021

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.