

Safety Data Sheet



Revision Number: 001.2

Issue date: 03/27/2025

1. IDENTIFICATION

Product name: LOCTITE UR 3371
Product type/ 1-component-polyurethane adhesive
Recommended use:
Restriction of Use: None identified
Company address:
Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067

IDH number: 2795005

Region: United States
Contact information:
Telephone: +1 (860) 571-5100
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: H315 - CAUSES SKIN IRRITATION.
H319 - CAUSES SERIOUS EYE IRRITATION.
H335 - MAY CAUSE RESPIRATORY IRRITATION.
H373 - MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2

PICTOGRAM(S)



Precautionary Statements

Prevention: P260 - Do not breathe dust.
P264 - Wash affected area thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.

Response: P280 - Wear protective gloves, eye protection, and face protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P304+P340+P312 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 - Get medical attention if you feel unwell.
P332+P313 - If skin irritation occurs: Get medical attention.
P337+P313 - If eye irritation persists: Get medical attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

Storage: P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.

Disposal: P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Other hazards Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Polyvinyl chloride	9002-86-2	10 - 30
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	68515-49-1	10 - 30
Xylenes	1330-20-7	5 - 10
Carbon black	1333-86-4	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Most important symptoms and effects (acute and delayed):	The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.
Indication of any immediate medical attention / special treatment needed:	Not available.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray mist or foam. Dry chemical.
Improper extinguishing agents:	High pressure waterjet.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Oxides of carbon, oxides of nitrogen, irritating organic vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
-----------------------------------	---

Clean-up methods:

Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.

Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

Shelf Life Statement: Not available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyvinyl chloride	1 mg/m3 TWA Respirable fraction.	0.5 ppm OSHA ACT (as vinyl chloride monomer) 5 ppm STEL (as vinyl chloride monomer) 1 ppm TWA (as vinyl chloride monomer) (as vinyl chloride monomer) 15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Xylenes	20 ppm TWA	100 ppm (435 mg/m3) PEL	None	None
Carbon black	3 mg/m3 TWA Inhalable fraction.	3.5 mg/m3 PEL 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Black
Odor:	Mild
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Density/Relative density:	1.08
Relative vapor density:	Not available.
Flash point:	Product is a solid
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility:	Not available.
Partition coefficient n-octanol/water (logarithmic value):	Not available.
VOC content:	< 30 g/l
Dynamic viscosity:	Not available.
Kinematic viscosity:	Not available.
Particle characteristics:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Irritating vapors.
Incompatible materials:	Strong oxidizing agents. Strong acids and strong bases.
Reactivity:	Not available.
Conditions to avoid:	Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure:	Skin, Inhalation, Eyes, Ingestion
----------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapors or mists of the product may be irritating to the respiratory system.
Skin contact:	Causes skin irritation. May cause allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s
Polyvinyl chloride	None
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	None
Xylenes	Oral LD50 (Rat) = 6,670 mg/kg Oral LD50 (Rat) = 3,523 - 8,600 mg/kg Oral LD50 (Rat) = 4,300 mg/kg Dermal LD50 (Rabbit) = > 43 g/kg Inhalation LC50 (Rat, 4 h) = 6580 ppm Inhalation LC50 (Rat, 4 h) = 6247 ppm Inhalation LC50 (Rat, 4 h) = 5922 ppm Inhalation LC50 (Rat, 4 h) = 6700 ppm Inhalation LC50 (Rat, 4 h) = 6350 ppm
Carbon black	Oral LD50 (Rat) = > 8,000 mg/kg

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
Polyvinyl chloride			Respiratory
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	Irritant		
Xylenes	Irritant		Cardiac Central nervous system Kidney Liver
Carbon black			Respiratory Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyvinyl chloride	No	No	Yes
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	No	No	No
Xylenes	No	No	No
Carbon black	Known To Be Human Carcinogen.	Group 2B	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	RQ, Environmentally hazardous substance, solid, n.o.s.
Hazard class or division:	9
Identification number:	UN 3077
Packing group:	III
DOT Hazardous Substance(s):	Xylene (mixed)

International Air Transportation (ICAO/IATA)

Proper shipping name: RQ, Environmentally hazardous substance, solid, n.o.s.
Hazard class or division: 9
Identification number: UN 3077
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Hazard class or division: 9
Identification number: UN 3077
Packing group: III

15. REGULATORY INFORMATION**United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Please refer to the GHS classification in Section 2
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Xylenes (CAS# 1330-20-7).
CERCLA Reportable quantity: Xylenes (CAS# 1330-20-7) 100 lbs. (45.4 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 03/27/2025

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.