

SL Series		
Hardware Options		
Option Name	Model Suffix	Description
High Slew Rate Output	+HS	A hardware and control modification that replaces the standard output stage with one of low capacitance film and/or high RMS current rated aluminum electrolytic capacitors. This option provides higher bandwidth with faster output rise and fall times.
IEEE-488 GPIB	+GPIB	An integrated IEEE-488 GPIB communications port, allowing the product to be fully controlled and monitored using supported commands, as well as adding some additional interface specific commands.
LXI TCP/IP Ethernet	+LXI	An integrated TCP/IP Ethernet communications port, certified to the LXI Class C standard, allowing the product to be fully controlled and monitored using supported commands, as well as adding some additional interface specific commands.
Ruggedized	+RUG	Internal product ruggedization, which has been independently tested to comply with select MIL-STD-810G shock and vibration specifications.
Software Options		
Option Name	Order Code	Description
Photovoltaic Power Profile Emulation	PPPE	This software interface for Magna-Power programmable DC power supplies utilizes EN50530 modeling to generate and transfer non-linear solar array profiles as a function of temperature and sunlight for the power supply to emulate a solar array and vary characteristics over time.
Photovoltaic Power Profile Emulation License	PPPE-1	A software license for an additional power supply for users who have already purchased PPPE. Licensed by product serial number with unlimited seats.
Accessories		
Option Name	Order Code	Description
Cabinet and Integration	CAB	Various size cabinets, including 12U, 24U, 30U, 36U, 30Ux2 and 36Ux2, with casters, fans and product integration.
RS485 Converter	RS485	Industrial RS232 to Addressable RS485 Converter. Plugs into product's RS232 port.
UID46: Universal Interface Device 46	UID46	Master-slave interface device for load sharing. Includes interface device and (2) D-Sub 37 cables.
UID47: Universal Interface Device 47	UID47	Master-slave interface device for load sharing. Includes interface device and (2) D-Sub 37 cables.
USB Edgeport Converter	USB	Industrial Plug and Play USB to RS232 Converter. Adapter plugs into product's RS232 port.