## **Electric Heat Guns**



Master-Mite Heat Gun								
Model No.	Description							
10008	650°F	343°C	120V	60 Hz	4.5A	475W		
10009	650°F	343°C	220V	50 Hz	2.0A	450W		

Optional Replacement Heating Elements									
Part No.	Description								
20012	Blue	500°F	260°C	120V	340W				
20013	Silver	650°F	343°C	120V	475W				
20014	Black	800°F	427°C	120V	525W				
20033	Blue	500°F	260°C	220V	400W				
20034	Silver	650°F	343°C	220V	450W				
20035	Black	800°F	427°C	220V	500W				
20160	Blue	500°F	260°C	240V	400W				
20161	Silver	650°F	343°C	240V	450W				
20162	Black	800°F	427°C	240V	500W				

## **Specifications**

- Air Volume: 3.8 CFM
- Air Velocity: 700 FPM
- Motor: Shaded Pole
- Nozzle Opening: .99" I.D., 1.03 O.D."
- Cordset: 6 ft., 3-wire grounded
- **NOTE:** Users should independently evaluate the suitability of the product for their application.

■ **Dimensions:** 8.8" L x 3.3" W x 7" H

• 120V Models

• Net Weight: 1.7 lbs.

• Shipping Weight: 3 lbs.

## Continuous-duty Bench-top Heating System

- Complete system comes standard with 650°F/343°C heating element, adjustable stand and heat shrink attachment
- · Quiet-running shaded pole motor, eliminates noisy production areas
- 3 optional easy-to-change plug-in heating elements available: 500°, 650° & 800°F
- Ideal heat & air flow (3.8 CFM), performs benchtop heating jobs without blowing components around the work station
- Use to activate adhesive, cure epoxies, dry components, melt solder preforms, remove decals, shrink tubing and more