DLRO TEST LEADS Digital Microhmmeter

DUPLEX PROBES



6111-022 DH1

2.5 m/8 inch Duplex handspikes (2 incl.) with helical sprung contacts.

6111-023 DH2 6m/20 inch as DH1 but only 1 included

6111-024 DH3 9.0m as DH1 but only 1 included

Description

Duplex handspikes with sprung loaded tips that both compress and rotate, to ensure good contact. Maximum current capacity 20 A for DH1, 10 A for longer lead lengths.

10mm spacing between P and C tips on each probe.

Will fit: BT51, 247000 series, DLRO10 and DLRO10X



6111-503 DH4

1.2m Duplex handspikes (2 off), one with indicator lights

6111-517 DH5 - as DH4, 2.5m

6111-518 DH6 - as DH4, 600 V rated

Description

Duplex handspikes with sprung loaded tips. One probe has lights that operate with the DLRO10 for connection indication and live warning. With the DLRO10X, can indicate test limit pass/fail.

Maximum current capacity 10 A.

6mm spacing between P and C tips on each probe.

Will fit:

BT51 (not using indicator lights) 247000 series (not using indicator lights) DLRO10 and 10X (DH4 supplied as standard)

Spare parts

- 25940-012 Replacement tips for DH4, 5 & 6 handspikes needle
- 25940-014 Replacement tips for DH4, 5 & 6 handspikes serrated



242003-7 Heavy duty fixed point hand spikes - replaceable tips

2m leads

242002-30 Heavy duty fixed point hand spikes 9m leads

Description

Lightweight and built for durability. Spikes are not spring loaded.

Rated 10 A.

9mm spacing between C and P probe tips.

Spare parts

5119 Replaceable needle points.

Will fit:

BT51, DLRO10, DLRO10X and 247000 series.



242002-7 Heavy duty fixed point hand spikes 2m leads

242002-30 Heavy duty fixed point hand spikes 9m leads

Description

Lightweight and built for durability. Spikes are not spring loaded.

Rated 10 A.

9mm spacing between C and P probe tips.

Will fit:

BT51, DLRO10, DLRO10X and 247000 series.

KELVIN CLIPS AND CLAMPS



241005-7 Kelvin Clips

2m leads - gold plated clips

Description

Kelvin clips, current connection to one jaw, potential connection to other jaw. Clips have 1.3 cm. jaw capacity. Easy connection to cables and small wires.

Rated to 10 A.

Gold plated clips for good contact and reduction in thermal EMFs

Will fit:

BT51, DLRO10, DLRO10X and 247000 series





242005-7 Kelvin Clips

2m leads - Silver plated clips

Description

Kelvin clips, current connection to one jaw, potential connection to other jaw. Clips have 1.3 cm. jaw capacity. Easy connection to cables and small wires.

Rated to 10 A.

Will fit:

BT51, DLRO10, DLRO10X and 247000 series

242006-7 Kelvin Clips 2m leads

242006-18 Kelvin Clips 5.5m leads

242006-30 Kelvin Clips 9m leads

Description

Kelvin clips, current connection to one jaw, potential connection to other jaw. Clips have 4 cm. jaw capacity. Easy connection to cables and small wires.

Rated to 10 A.

Will fit:

BT51, DLRO10, DLRO10X and 247000 series.

242004-7 Heavy duty C-clamps

2m leads

242004-18 Heavy duty C-clamps 5.5m leads

242004-30 Heavy duty C-clamps 9m leads

Description

Kelvin clamps, current passes through the C-clamp and screw thread, the potential passes through a four point anvil insulated from the clamp.

Clamps have a capacity of 5 cm and current rating of 10 A.

Will fit:

BT51, DLRO10, DLRO10X and 247000 series.





242104-2-16 Heavy duty C-clamps 5m leads 242104-2-26 Heavy duty C-clamps 8m leads

Description

Kelvin clamps, current passes through the C-clamp and screw thread, the potential passes through a four point anvil insulated from the clamp.

Clamps have a capacity of 10 cm and current rating of 100 A.

Will fit:

DLRO200 and DLRO600 **only to 100A**. 247120

SEPARATE CURRENT AND POTENTIAL LEADS



242041-7 Current clip leadset 2m leads

242041-18 Current clip leadset 5.5m leads

242041-30 Current clip leadset 9m leads

Description

Used in combination with 242021 potential leads.

Separates the C and P connections.

Rated 10 A.

Will fit:

BT51, DLRO10, DLRO10X and 247000 series.



242021-7 Potential spike leadset 2m leads

242021-18 Potential spike leadset 5.5m leads

242021-30 Potential spike leadset 9m leads

Description

Used in combination with 2420041 current leads.

Separates the C and P connections.

Will fit:

BT51, DLRO10, DLRO10X and 247000 series.

HIGH CURRENT LEADSETS



6220-755 5m Lead set

 $2 \ x \ 50 \ mm^2$ current leads with clamps and $2 \ x$ potential leads with clips.

6220-787 5m Lead set

as above but 25mm² cable fitted.

Description

Lead set consists of pair of flexible high current capacity (600 A cont.) leads, together with a separate pair of light-weight potential leads.

Current leads are fitted with heavy duty sprung clamps (60 mm jaw capacity).

Potential leads fitted with smaller HD crocodile clips 22 mm jaw capacity).

Will fit:

DLRO200 (6220-755 supplied as standard) DLRO600 (6220-755 supplied as standard) DLRO200-115 (6220-787 supplied as standard)



6220-756 10m Lead set

 $2 \ x \ 70 mm^2 \ current$ leads with clamps and $2 \ x \ potential$ leads with clips.

6220-757 15m Lead set

 $2 \ x \ 95 mm^2 \ current$ leads with clamps and $2 \ x \ potential$ leads with clips.

Description

Lead set consists of pair of flexible high current capacity (600 A cont.) leads, together with a separate pair of light-weight potential leads.

Current leads are fitted with heavy duty sprung clamps (60 mm jaw capacity).

Potential leads fitted with smaller HD crocodile clips 22 mm jaw capacity).

Will fit:

DLRO200 (6220-755 supplied as standard) DLRO600 (6220-755 supplied as standard)

UK

Archcliffe Road Dover CT17 9EN England T +44 (0) 1304 502101 F +44 (0) 1304 207342

UNITED STATES

4271 Bronze Way Dallas TX 75237-1019 USA T 800 723 2861 (USA only) T +1 214 333 3201 F +1 214 331 7399

OTHER TECHNICAL SALES OFFICES Norristown USA, Toronto CANADA, Mumbai INDIA, Trappes FRANCE, Sydney AUSTRALIA and the

Kingdom of BAHRAIN.

Registered to ISO 9001:2000 Cert. no. Q 09290 Registered to ISO 14001-1996 Cert. no. EMS 61597

DLRO_TL_DS_en_V01

www.megger.com Megger is a registered trademark