



Item # \_\_\_\_\_

Job \_\_\_\_\_

## SUPER ERECTA SHELF® DOLLY TRUCKS — WIRE “N” Series

- **Dolly Trucks** combine the features of Super Erecta Shelf® wire shelving with the mobility of casters and dollies to provide a high-quality, strong and versatile material handling truck.
- **Variety of Casters & Dollies Available:**  
Select the casters and dolly that allows the right combination of durability and maneuverability to suit your requirements. Dollies can be ordered in many sizes with choice of casters, finish and bumper. Casters are available in swivel, rigid, brake and brake/lock types. And all Metro casters are non-marking.  
**Note:** Refer to sheets 11.37 (Plate Casters) and 11.36 (Truck Dollies) for additional information.
- **Unique Design:** Open Wire surfaces minimize dust accumulation and allow a free circulation of air and greater visibility.
- **Fast, Secure Assembly:** Post has rolled, circular grooves along its entire height at 1" (25mm) intervals. A patented, tapered split sleeve (plastic or aluminum) snaps together around each post. Tapered sleeves providing a positive lock.
- **Versatile Construction:** Super Erecta Shelf® wire shelving can change quickly as your needs change. By using various accessories, hundreds of configurations become possible.



**InterMetro Industries Corporation**  
North Washington Street  
Wilkes-Barre, PA 18705  
[www.metro.com](http://www.metro.com)

  
**EMERSON**  
Commercial & Residential Solutions



SUPER ERECTA SHELF®  
**Dolly Trucks** — Wire “N” Series

**11.25**

# SUPER ERECTA SHELF® DOLLY TRUCKS — WIRE “N” Series



## Specifications

**Standard Units:** Standard wire shelf trucks consist of four shelves, posts, plastic split sleeves,\* truck dolly with wraparound bumper and designated casters.

## Dimensions

**With Chrome Shelves, Plated Posts & Aluminum Dolly** 63" (1600mm) Posts

Two B5DN Two B5DNB	Model No. with Casters		Shelf Width		Shelf Length	
	Two B5P Two B5PB	Two 6P Two BL6P	(in.)	(mm)	(in.)	(mm)
N536JC	N536LC	N536MC	24	610	36	914
N556JC	N556LC	N556MC	24	610	48	1219
N566JC	N566LC	N566MC	24	610	60	1524

Actual Dimensions: Width = Nominal Width + 3<sup>3</sup>/<sub>8</sub>" (85mm)  
Length = Nominal Length + 3<sup>1</sup>/<sub>8</sub>" (79mm)

	Actual Height		Load Rating	
	(in.)	(mm)	(lbs.)	(kg)
-JC Models	68 <sup>7</sup> / <sub>16</sub>	1739	800	363
-LC Models	68 <sup>7</sup> / <sub>16</sub>	1739	900	408
-MC Models	70 <sup>1</sup> / <sub>16</sub>	1800	1,000	454

### TO ORDER BY COMPONENTS:

- Order shelves and posts from sheet #10.01 or price list. (Shelves will be packed with plastic split sleeves.\*)
- Order truck dolly frame from sheet #11.37 or price list.
- Order plate casters from sheet #11.37 or price list.  
For more information on brake/lock caster sets see sheet #11.70.

### IMPORTANT:

- Specify “staked posts” to ensure that die casting does not separate from dolly.
- If truck will be towed, transported over the road or otherwise subjected to vibration and jolting, specify aluminum split sleeves. (See sheet #11.40 or price list.)
- Remember that stability decreases as the ratio of height to width increases. Units should be kept as wide and low as possible.

## Accessories

### Aluminum Split Sleeves

Recommended when the unit will be towed, transported over-the-road, or otherwise subjected to vibration or jolting. One bag needed per shelf.

Model No. 9986Z  
Bag of four aluminum sleeves with C-rings.



### Handles

Can be added to stem caster carts to improve maneuverability and ergonomics. (Split sleeves are included)



**Note:** Handles fit unit widths only. Push handles add roughly 1" (25mm) to the length of the unit. Extended handles add 6" (153mm) to the length of the unit.

Fits Shelf Width (in.)	(mm)	Push Handle		Extended Handle	
		Chrome Model No.	Approx. Pkd. Wt. (lbs.) (kg)	Chrome Model No.	Approx. Pkd. Wt. (lbs.) (kg)
24	610	PH24NC		EH24NC	

All Metro Catalog Sheets are available on our website: [www.metro.com](http://www.metro.com)



**InterMetro Industries Corporation**  
North Washington Street, Wilkes-Barre, PA 18705  
Phone: 570-825-2741  
Product Information. U.S. and Canada: 1.800.992.1776  
Outside U.S. and Canada: [www.metro.com/contactus](http://www.metro.com/contactus)

L02-042  
Printed in U.S.A. Rev. 01/13

Information and specifications are subject to change without notice. Please confirm at time of order

Copyright © 2014 InterMetro Industries Corp.

