



We put space to work.

Item # _____

Job _____

Super Erecta® Sterile Wrap Rack

- Solves Storage Problem: Sterile wrap racks provide a safe, convenient place to hold wrap. Most sizes can be displayed prominently so that they are easy to locate. One sheet, or several sheets, at a time can be removed quickly and neatly. The solid bottom shelf, standard on all units, can be used to hold extra wrap, or less frequently used sizes.
- Adjustable: The carrier assembly which supports the bars is adjustable in 1" (25mm) increments along the height of the posts so that it can be positioned at a comfortable level for users. The four bars can also be positioned in any of 18 slots along the carrier assembly.
- Four Bars Standard: All models come with four square bars as standard. Additional bars can be added as accessories, if needed.
- Mobile: 5" (127mm) polyurethane tread swivel casters provide easy maneuverability.
- Two Sizes: Sterile wrap racks come in 24" x 48" (610 x 1220mm) size and 24" x 60" (610 x 1525mm) size. All models are 68" (1730mm) in overall height. The 60" (1525mm) models will hold wrap up to 54" x 72" (1372 x 1829mm).



Super Erecta® Sterile Wrap Rack

All Metro Catalog Sheets are available on our website: www.metro.com



InterMetro Industries Corporation
North Washington Street, Wilkes-Barre, PA 18705
Product Information. U.S. and Canada: 1.800.992.1776
Outside U.S. and Canada: www.metro.com/contactus

L02-173
Printed in U.S.A. 8/21

Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2021 InterMetro Industries Corp.

33-22

Super Erecta® Sterile Wrap Rack

We put space to work.®

Specifications

Sterile Wrap Racks consist of four posts, four casters, a solid bottom shelf, three-sided top and intermediate frames, a two-piece carrier assembly, and four square support bars.

- **Posts:** Units have four 1" (25mm) diameter Super Erecta Shelf posts, chrome-plated with rolled grooves in 1" (25mm) increments along entire height.
- **Casters:** Models SWR556EG and SWR566EG have four 5" (127mm) polyurethane tread casters as standard. Two swivel, two swivel with brake.
- **Bottom Shelf:** Solid galvanized.
- **Top and Intermediate Frames:** Top and intermediate frames are three-sided, chrome-plated snake frames.
- **Carrier Assembly:** Two piece assembly is stainless steel with welded collars.
- **Support Bars:** Support bars are 1" (25mm) square stainless steel.



Close-up of Carrier Assembly

Dimensions

Cat. No.	Shelf		Length		Overall Height		Bottom Shelf Material	Frame Material	Post Material	Approx. Pkd. Wt.	
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)				(lbs.)	(kg)
SWR556EG	24	610	48	1220	68	1730	Galvanized	Chrome	Chrome	88	38
SWR566EG	24	610	60	1525	68	1730	Galvanized	Chrome	Chrome	94	43

Accessories

Additional Support Bars

Cat. No.	Length		Approx. Pkd. Wt.	
	(in.)	(mm)	(lbs.)	(kg)
SWRB5S	48	1220	4	2
SWRB6S	60	1525	5	2.3

Covers - Covers are available in white and a variety of colors in both coated and uncoated styles. Refer to spec sheet 11.80 for additional information.

Coated Cat. No.	Uncoated Cat. No.	Width		Length		Height	
		(in.)	(mm)	(in.)	(mm)	(in.)	(mm)
24x48x62C	24x48x62UC	24	610	48	1220	62	1575
24x60x62C	24x60x62UC	24	610	60	1525	62	1575

an Ali Group Company



The Spirit of Excellence