

408A RUBBER RENUE™

408A-LIQUID

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: 408A Rubber Renue™**SDS Code:** 408A-Liquid**Related Part #** 408A-125ML, 408A-250ML, 408A-1L

Recommended Use and Restriction on Use

Use: Liquid for rejuvenating and reconditioning rubber**Uses Advised Against:** Not available

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADAMG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA**☎** +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** support@mgchemicals.com**WEB** www.mgchemicals.com**☎** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** info@mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY—leaks, spills, fires, exposures or accidentsUSA or CANADA: Call CHEMTREC ☎: **+1-800-424-9300****For emergencies involving dangerous goods;** Collect 24/7CANADA: Call CANUTEC ☎: **+1-613-996-6666** or ***666** on cellular phones

408A RUBBER RENUE™

408A-LIQUID

Section 2: Hazard(s) Identification




Classification of Hazardous Chemical

GHS Categories

Criteria	Category	Signal Word	Pictograms
Aspiration Hazard	1	Danger	Health
Carcinogenicity	2	Warning	Health
Specific Target Organ Toxicity Repeated Exposure	2	Warning	Health
Flammable Liquids	3	Warning	Flame
Skin irritation	2	Warning	Exclamation
Eye irritation	2	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation
Hazardous to the Aquatic Environment Chronic	3	none	none

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H304: May be fatal if swallowed and enters airways H351: Suspected of causing cancer H373: May cause damage to organs (inner ear, liver) through prolonged or repeated exposure
	H226: Flammable liquid and vapor
	H319: Causes serious eye irritation H315: Causes skin irritation H335: May cause respiratory irritation H336: May cause drowsiness or dizziness

Section continued on the next page

408A RUBBER RENUE™

408A-LIQUID

Continued...

Pictograms	Hazard Statements
<i>No symbol mandated</i>	H412: Harmful to aquatic life with long lasting effects
Prevention	Precautionary Statements
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe mist/vapors/spray.
P271	Use only outdoors or in a well-ventilated area.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P241	Use explosion-proof equipment.
P243	Take action to prevent static discharges.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection.
Response	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P301 + P310, P331	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.
P303 + P361 + P352	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with plenty of water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.

Section continued on the next page

408A RUBBER RENUE™

408A-LIQUID

Continued...

Storage	Precautionary Statements
P403 + P235	Store in well-ventilated place. Keep cool.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents/container in accordance to local/regional/international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
1330-20-7	xylene (mixture)	60-68%
100-41-4	ethylbenzene	17-26%
119-36-8	methyl salicylate	15%

408A RUBBER RENUE™**408A-LIQUID****Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF SWALLOWED	P301 + P310, P331, P308 + P313
Immediate Symptoms	<i>nausea, weakness, headache, abdominal pain, drowsiness, dizziness, unconsciousness</i>
Response	Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF exposed or concerned: Get medical advice/attention.
IF ON SKIN (or hair)	P303 + P361 + P352, P332 + P313, P363, P308 + P313
Immediate Symptoms	<i>dry skin, redness, irritation</i>
Response	Take off immediately all contaminated clothing. Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF exposed or concerned: Get medical advice/attention.
IF IN EYES	P305 + P351 + P338, P308 + P313
Immediate Symptoms	<i>redness, irritation, pain</i>
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention.
IF INHALED	P304 + P340, P312, P308 + P313
Immediate Symptoms	<i>nausea, weakness, headache, drowsiness, dizziness, respiratory irritation, unconsciousness</i>
Delayed Symptoms	<i>deep and rapid breathing, nausea</i>
Response	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF exposed or concerned: Get medical advice/attention.

408A RUBBER RENUE™**408A-LIQUID****Section 5: Fire-Fighting Measures**

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish. Use water spray to cool containers.
Specific Hazards	The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion. Prevent fire-fighting wash from entering waterway or sewer system.
Combustion Products	Produces carbon oxides (CO, CO ₂).
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Remove or keep away all sources of extreme heat or open flames. Do not breathe the mist/spray/vapors.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	Contain with inert and non-flammable absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue. RECOMMENDATION: Use a grounded stainless steel or carbon steel container.
Disposal Methods	Dispose of spill waste according to Section 13.

408A RUBBER RENUE™

408A-LIQUID

Section 7: Handling and Storage

Prevention

Keep out of reach of children.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take action to prevent static discharges.

Do not breathe mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep container tightly closed.

Handling

Wear protective gloves/protective clothing/eye protection.

Wash hands thoroughly after handling.

Avoid release to the environment.

Storage

Store in well ventilated place. Keep cool.

Store locked up.

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
xylene (mixed isomers)	ACGIH	100 ppm	150 ppm
	U.S.A. OSHA PEL	100 ppm	150 ppm
	Canada AB	100 ppm	150 ppm
	Canada BC	100 ppm	150 ppm
	Canada ON	100 ppm	150 ppm
	Canada QC	100 ppm	150 ppm
ethylbenzene	ACGIH	100 ppm	Not established
	U.S.A. OSHA PEL	100 ppm	125 ppm
	Canada AB	100 ppm	125 ppm
	Canada BC	20 ppm	Not established
	Canada ON	100 ppm	125 ppm
	Canada QC	100 ppm	125 ppm

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from by RTECS database² and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

Section continued on the next page

408A RUBBER RENUE™**408A-LIQUID****Engineering Controls**

Ventilation Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety goggles.

Recommendation: Ensure that glasses have side shields for lateral protection.

Skin Protection For likely contacts, use polyvinyl alcohol (PVA), viton, or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

Respiratory Protection For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

408A RUBBER RENUE™
408A-LIQUID
Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	1%
Appearance	Clear, orange tint	Upper Flammability Limit	7%
Odor	Aromatic	Vapor Pressure @20 °C	9.5 hPa [7.1 mmHg]
Odor Threshold	Not available	Vapor Density	>2 (Air =1)
pH	Not available	Specific Gravity @15.5 °C	0.91
Freezing/Melting Point	Not available	Solubility in Water	Immiscible
Boiling Point	>137 °C [>279 °F]	Partition Coefficient	Not available
Flash Point ^{a)}	27 °C [81 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability (solid, gas)	Not applicable	Viscosity @40 °C	<20.5 mm ² /s

a) Closed cup flash point

Section 10: Stability and Reactivity

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Avoid flames, sparks, other ignition sources and incompatible substances.
Incompatibilities	Strong oxidizing agents, strong bases
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

408A RUBBER RENUE™**408A-LIQUID****Section 11: Toxicological Information****Routes of Exposure**

Eye Contact, Ingestion, Inhalation, and Skin Contact

Symptoms Summary

Eyes	Cause redness, eye irritation, and pain.
Skin	Cause dry skin, redness, and irritation.
Inhalation	May cause nausea, weakness, headache, drowsiness, dizziness, unconsciousness. May cause irritation of the nose and throat.
Ingestion	May cause nausea, weakness, headache, abdominal pain, drowsiness, dizziness, unconsciousness (also see inhalation symptoms).
Chronic	<p>Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin.</p> <p>Prolonged and repeated exposure is possibly carcinogenic based on inhalation studies on rats.</p> <p>Long term exposure with co-exposure to loud noise may cause hearing loss.</p>

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
xylene	4 350 mg/kg Rat	>1 700 mg/kg Rabbit	5 000 ppm 4 h Rat
ethylbenzene	3 500 mg/kg Rat	>5 000 mg/kg Rabbit	35 500 mg/m ³ 2h Mouse
methyl salicylate	887 mg/kg Rabbit	>5 000 mg/kg Rat ^{a)}	Not available

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier (M)SDS were also consulted.

a) Source Sigma-Aldrich SDS version 4.2, Date: 02/20/2013

Section continued on the next page

408A RUBBER RENUE™**408A-LIQUID****Other Toxicological Effects**

Skin corrosion/irritation	Causes skin irritation based on Draize tests on animals.
Serious eye damage/irritation	Causes serious irritation. Studies on rabbits suggest that conjunctiva (redness) effect that is fully reversible in seven days.
Sensitization (allergic reactions)	Based on available data, the classification criteria are not met.
Carcinogenicity (risk of cancer)	Ethylbenzene [100-41-4] IARC Group 2B: Possibly carcinogenic to humans ACGIH A3: Confirmed animal carcinogen with unknown relevance to humans CA Prop 65: Listed as a carcinogen NTP: Not listed
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	Xylene isomers can affect the central nervous system by inhalation causing drowsiness or dizziness. They are a respiratory system irritant.
STOT-repeated exposure	Prolonged or repeated over-exposure to p-xylene and ethylbenzene and noise can lead to hearing loss (cochlear impairment) according to rat inhalation studies.
Aspiration hazard	The mixture is classified as Cat 1 aspiration hazards.

408A RUBBER RENUE™**408A-LIQUID****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

The xylene isomers mixture is acutely toxic to the aquatic environment of category 2 with a minimal LC50 96 h of 2.5 mg/L for *Oncorhynchus mykiss* (rainbow trout).

Ethylbenzene is acutely toxic to the aquatic environment of category 2 with minimal LC50 96 h of 4.2 mg/L for *Oncorhynchus mykiss* (rainbow trout); EC50 48 h 2.9 mg/L *Daphnia magna* (water flea).

Insufficient data is available to classify the aquatic toxicity of methyl salicylate.

Acute Ecotoxicity

See chronic

Chronic Ecotoxicity

Category 3

Harmful to aquatic life with long lasting effects

Biodegradability

Readily biodegradable. Product is volatile and only slightly soluble in water. In water and soil, it is biodegradable under both aerobic and anaerobic condition. Photooxidation in the atmosphere are typically in the range of 0.5 to 1.5 days.

Other Effects

Actual VOC (Volatile Organic Compounds) content according to the US (EPA) and Canadian (CEPA) authorities.

Actual VOC = 100% [908 g/L]

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

408A RUBBER RENUE™

408A-LIQUID

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations);
USA DOT 49 CFR (Parts 100 to 185) **Regulations.**

Sizes 5 L and under
Limited Quantity



Sizes up to 60 L (Passenger) or more (Cargo)

UN number: UN1307

Shipping Name: XYLENES

Class: 3

Packing Group: III

Marine Pollutant: No

Flash Point = 27 °C [80 °F]



Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 5 L and under
Limited Quantity
Max Net Qty/Pkg
=10 L



Sizes up to 60 L (Passenger), 220 L (Cargo)

UN number: UN1307

Shipping Name: XYLENES

Class: 3

Packing Group: III

Marine Pollutant: No

Flash Point = 27 °C [80 °F]



Sea

Refer to IMDG regulations.

Sizes 5 L and under
Limited Quantity



Sizes greater than 5 L

UN number: UN1307

Shipping Name: XYLENES

Class: 3

Packing Group: III

Marine Pollutant: No

Flash Point = 27 °C [80 °F]



Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

408A RUBBER RENUE™

408A-LIQUID

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.


USA

Other Classifications

HMIS® RATING

HEALTH:	*	2
FLAMMABILITY:		3
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product contains ethylbenzene and xylene that are listed as hazardous air pollutants.

Section continued on the next page

408A RUBBER RENUE™**408A-LIQUID****EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains ethylbenzene (CAS # 100-41-4; reportable quantity = 1000 lb) and xylene (CAS# 1330-20-7, reportable quantity = 100 lb), which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, June 06, 2014 revision, USA).

This product contains ethylbenzene (CAS # 100-41-4), which is listed as a carcinogen.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by Michel Hachey

Date of Review 28 June 2016

Supersedes 24 March 2016

Reason for Changes: Reclassification due to new information in compliance with HCS 2012 and WHMIS 2015.

Reference

1) ACGIH 2013 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2013).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page

408A RUBBER RENUE™**408A-LIQUID****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.