

PREMIUM POLYURETHANE CONFORMAL COATING 4223F-LIQUID

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: Premium Polyurethane Conformal Coating **SDS Code:** 4223F-Liquid

Related Part # 4223F-1L, 4223F-4L, 4223F-20L

Recommended Use and Restriction on Use

Use: Protective dielectric coating for printed circuit boards

Uses Advised Against: Not available

Details of Manufacturer or Importer

Manufacturer

MG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

MG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA

☎ +1-800-340-0772

FAX +1-800-340-0773

E-MAIL support@mgchemicals.com

WEB www.mgchemicals.com

☎ +1-905-331-1396

FAX +1-905-331-2682

E-MAIL info@mgchemicals.com

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY—leaks, spills, fires, exposures or accidents

USA or CANADA: Call CHEMTREC ☎: **+1-800-424-9300**

For emergencies involving dangerous goods; Collect 24/7

CANADA: Call CANUTEC ☎: **+1-613-996-6666** or ***666** on cellular phones

PREMIUM POLYURETHANE CONFORMAL COATING 4223F-LIQUID

Section 2: Hazard(s) Identification

Classification of Hazardous Chemical

GHS Categories

Criteria	Category	Signal Word	Pictograms
Flammable liquid	2	Danger	Flame
Skin Irritation	2	Warning	Exclamation
Specific target organ toxicity Single exposure	3	Warning	Exclamation
Environmental Hazard Chronic Aqua. Tox.	2	none	Environment


Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Other Classifications

HMIS® RATING

HEALTH:	* 2
FLAMMABILITY:	3
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES






Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

Section continued on the next page

PREMIUM POLYURETHANE CONFORMAL COATING 4223F-LIQUID

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H225: Highly flammable liquid and vapor
	H315: Cause skin irritation H336: May cause dizziness or drowsiness
	H411: Toxic to aquatic life with long lasting effects
Prevention	Precautionary Statements
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P261 + P271	Avoid breathing mist/vapors/spray/fumes. Use only outdoors or in well ventilated area.
P240	Ground and bond container and receiving equipment.
P241	Use explosion proof equipment.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/eye protection/face protection.
P273	Avoid release to the environment.
Response	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P303 + P361 + P364 + P352	IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.
P391	Collect spillage

Section continued on the next page

PREMIUM POLYURETHANE CONFORMAL COATING 4223F-LIQUID

Continued...

Storage	Precautionary Statements
P403 + P235	Store in well ventilated place. Keep cool.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents/container in accordance to local/regional/international regulations.

Other Hazards

Repeated exposure may cause skin dryness or cracking.

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	Wt%
8052-41-3	stoddard solvent	40-50%
78-93-3	butan-2-one	7-13%

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF ON SKIN (or hair)	P303 + P361 + P364, P352, P332 + P313
Immediate Symptoms	<i>irritation, dry skin, redness</i>
Response	IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of water. If skin irritation occurs: Get medical advice/attention.
IF INHALED	P304 + P340, P312, P308 + P313
Immediate Symptoms	<i>cough, irritation of the respiratory track, dizziness, drowsiness, headaches</i>
Response	Remove person to fresh air (out of the contaminated zone) and keep comfortable for breathing. If feeling unwell: Call a doctor.

Section continued on the next page

PREMIUM POLYURETHANE CONFORMAL COATING 4223F-LIQUID*Continued...*

IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>mild irritation, redness</i>
Response	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
IF SWALLOWED	P301 + P330 + P331, P312, 308 +P313
Immediate Symptoms	<i>abdominal pain, nausea, headaches, dizziness, drowsiness, vomiting</i>
Response	Rinse mouth. Do NOT induce vomiting. If feeling unwell or concerned: Get medical advice.

Section 5: Fire-Fighting Measures

In case of fire	P370 + P378
Extinguishing Media	Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
Specific Hazards	Vapors are heavier than air, and may travel to sources of ignition near the ground. They can cause flash fire or ignite explosively.
Combustion Products	Produces CO and CO ₂ .
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

PREMIUM POLYURETHANE CONFORMAL COATING 4223F-LIQUID**Section 6: Accidental Release Measures**

Personal Protection	Use personal protection recommended in Section 8.
Precautions for Response	Remove all sources of ignition. Avoid breathing the vapors/mist/fumes. Do not flush to sewer.
Environmental Precautions	Avoid release to the environment. Prevent spill from entering drains and waterways. Collect spillage.
Containment Methods	Contain with inert absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue. Recommendation: Use a grounded stainless steel or carbon steel container.
Disposal Methods	Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention	Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. For metal containers, ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilating/lighting equipment. Avoid breathing mist/vapors/spray/fumes. Use only outdoors or in well ventilated area. Do not eat, drink, or smoke when using this product.
Handling	Wear protective gloves/clothing/eye protection. Wash hands thoroughly after handling. Avoid release to the environment.
Storage	Store in a well-ventilated and dry area. Keep cool. Store locked up.

PREMIUM POLYURETHANE CONFORMAL COATING 4223F-LIQUID

Section 8: Exposure Controls/Personal Protection

Routes of Entry

Eyes, ingestion, inhalation, and skin

Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
stoddard solvent	ACGIH	100 ppm	Not established
	U.S.A. OSHA PEL	500 ppm	Not established
	Canada AB	100 ppm	Not established
	Canada BC	290 mg/m ³	580 mg/m ³
	Canada ON	100 ppm	Not established
	Canada QC	100 ppm	Not established
butan-2-one	ACGIH	200 ppm	Not established
	U.S.A. OSHA PEL	200 ppm	300 ppm
	Canada AB	200 ppm	300 ppm
	Canada BC	50 ppm	100 ppm
	Canada ON	200 ppm	300 ppm
	Canada QC	150 ppm	300 ppm

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH², OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from by RTECS database¹ of the Canadian Centre for Occupational Health and Safety (CCOHS) a data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

Engineering Controls

Ventilation Keep airborne concentrations below exposure limits, =.

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety goggles.

Skin Protection Use of protective gloves chemically resistant gloves if skin contact is likely.

For incidental exposure, you may use nitrile gloves.

Section continued on the next page

PREMIUM POLYURETHANE CONFORMAL COATING 4223F-LIQUID

Respiratory Protection If exposed to vapors above the exposure limit, wear respirator such as a half-mask respirator with organic vapor cartridge.

RECOMMENDATION: Consult your local safety supply store to ensure your respirator has filter cartridges appropriate for the ingredients listed in section 3 of this SDS, and that the respirator is fitted to the employee by a professional.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit ^{a)}	1%
Appearance	Clear	Upper Flammability Limit ^{a)}	11%
Odor	Mild petroleum	Vapor Pressure @20 °C	Not available
Odor Threshold	Not available	Vapor Density	>2.5 (Air =1)
pH	Not available	Specific Gravity @25 °C	0.88
Freezing/Melting Point	Not available	Solubility in Water	Partially soluble
Boiling Point ^{a)}	80 °C [176 °F]	Partition Coefficient	Not available
Flash Point ^{a)}	-3 °C [27 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability (solid, gas)	Not available	Viscosity @40 °C	>20.5 mm ² /s

a) Lowest component literature value, which corresponds to butan-2-one

PREMIUM POLYURETHANE CONFORMAL COATING 4223F-LIQUID

Section 10: Stability and Reactivity

Reactivity	Not available.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Ignition sources, extreme temperatures, and incompatible substances
Incompatibilities	oxidizing agents, strong reducing agents, strong acids
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5

Section 11: Toxicological Information

Routes of Exposure

Eyes, ingestion, inhalation, and skin

Symptoms Summary

Eyes	May cause eye redness or mild irritation.
Skin	May causes mild to moderate skin irritation.
Inhalation	Overexposure may lead to visual impairment and central nervous system effects such as dizziness, drowsiness, or weakness.
Ingestion	Harmful if swallowed. It may cause irritation and burning sensation. See inhalation symptoms.
Chronic	Prolonged and repeated exposure may cause dermatitis, defatting of the skin and adverse central nervous systems effects.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation	TCLo inhalation
stoddard solvent	15 400 mg/kg Rat	>3 160 mg/kg Rabbit	Not available	Not available
2-butanone	2 737 mg/kg Rat	6 480 mg/kg Rabbit	23 500 mg/m ³ 8h Rat	100 ppm 5 m Human

Note: Representative toxicity data from by RTECS database of the Canadian Centre for Occupational Health and Safety (CCOHS)¹ data from supplier (M)SDS were also consulted.

Section continued on the next page

PREMIUM POLYURETHANE CONFORMAL COATING 4223F-LIQUID**Other Toxicological Effects**

Skin corrosion/irritation	The Stoddard is a mild to moderate skin irritant.
Serious eye damage/irritation	Mild eye irritant that is not classifiable under HCS 2012
Sensitization (allergic reactions)	No sensitization effects known
Carcinogenicity (risk of cancer)	Not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	The Stoddard solvent and butan-2-one can affect the central nervous system by inhalation causing drowsiness or dizziness.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Viscosity at 40 °C is >20.5 mm ² /s, thus not classified as aspiration hazard.

Section 12: Ecological Information

The IMDG Code criteria and the raw-material (M)SDS along with supporting data for the classification of registered substances from the European Chemical Agency database (<http://echa.europa.eu>) were used.

The Stoddard solven is a chronic category 2 environmental toxicant.

Butan-2-one (MEK) is not classifiable as an environmental toxicant (with minimal LC50 of >100 mg/L).

Acute Ecotoxicity

Category 2 (H401): Toxic to aquatic life

Chronic Ecotoxicity

Category 2 (H411): Toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

Biodegradability

Not available

Section continued on the next page

PREMIUM POLYURETHANE CONFORMAL COATING 4223F-LIQUID

Other Effects

VOC (EPA, WHIMS, and Europe) = 55% [489 g/L]

*VOC = Volatile Organic Content

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes 5 liters and under

Limited Quantity



Sizes greater than 5 liters

UN number: UN1263
Shipping Name: PAINT
Class: 3
Packing Group: II
Marine Pollutant: Yes



Flash Point = -3 °C [27 °C]

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes up to 5 L (passenger), 60 L (cargo)

UN number: UN1263
Shipping Name: PAINT
Class: 3
Packing Group: II
Marine Pollutant: Yes






Flash Point = -3 °C [27 °C]

Section continued on the next page

PREMIUM POLYURETHANE CONFORMAL COATING 4223F-LIQUID

Sea

Refer to IMDG regulations.	
<p>Sizes 5 liters and under</p> <p>Limited Quantity</p> 	<p>Sizes greater than 5 liters</p> <p>UN number: UN1263 Shipping Name: PAINT Class: 3 Packing Group: II Marine Pollutant: Yes</p>   <p>Flash Point = -3 °C [27 °C]</p>

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information

Canada

WHMIS Classification



B2 – Flammable Liquid;
D2B – Toxic Material (Skin Irritation)

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL/NDSL.

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.

Health Canada

Products produced by MG Chemicals intended for retail display conform to the Canadian Consumer Labeling Regulations.

Section continued on the next page

PREMIUM POLYURETHANE CONFORMAL COATING 4223F-LIQUID**USA****CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains 2-butanone (CAS# 78-93-3, reportable quantity = 5000 lb), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, Sept 2, 2011 revision, USA).

This product does not contain any substances known to be listed in California.

Europe**RoHS**

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

PREMIUM POLYURETHANE CONFORMAL COATING 4223F-LIQUID**Section 16: Other Information**

SDS Prepared by Michel Hachey
Date of Creation 05 May 2015
Date of Issue 05 May 2015
Supersedes Not applicable
Reason for Changes: New product.

Reference

- 1) ACGIH 2013 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2013).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
NOELR	No observable effect loading ratio
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Section continued on the next page



Quality System Certified to ISO 9001:2008

SAI Global File #004008
Burlington, Ontario, Canada

PREMIUM POLYURETHANE CONFORMAL COATING 4223F-LIQUID

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.