

8309-P

CONFORMAL COATING STRIPPER PEN

# Safety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

**Product Identifier:** 8309-P**Other Means of Identification:** Conformal Coating Stripper Pen**Related Part #** 8309-P

### Recommended Use and Restriction on Use

**Use:** Coating stripper**Uses Advised Against:** Not applicable

### Details of Manufacturer or Importer

#### Manufacturer

MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADAMG Chemicals (Head Office)  
9347-193 Street  
Surrey, British Columbia V4N 4E7  
CANADA**☎** +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)**WEB** [www.mgchemicals.com](http://www.mgchemicals.com)**☎** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** [info@mgchemicals.com](mailto:info@mgchemicals.com)**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number



**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)  
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**  
(Service access code: 335388)**For emergencies involving the transport of dangerous goods;** 24/7 service  
CANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

**8309-P**
**CONFORMAL COATING STRIPPER PEN**
**Section 2: Hazard(s) Identification**
**Classification of Hazardous Chemical**
**GHS Categories**

Criteria	Category	Signal Word	Pictograms
Flammable Liquid	2	Danger	Flame
Eye Irritation	2	Warning	Exclamation
Specific Target Organ Toxicity    Single Exposure	3	Warning	Exclamation

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity). Severity categories rankings do not allow comparisons between classes.

**Label Elements**

<b>Signal Word</b>	<b>DANGER</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H225: Highly flammable liquid and vapor
	H319: Causes serious eye irritation H336: May cause drowsiness or dizziness
<b>Prevention</b>	<b>Precautionary Statements</b>
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.
P261	Avoid breathing vapors.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves.
P264	Wash hands thoroughly after handling.

*Section continued on the next page*

**8309-P**
**CONFORMAL COATING STRIPPER PEN**
*Continued...*

<b>Response</b>	<b>Precautionary Statements</b>
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P304 + P340, P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.
<b>Storage</b>	<b>Precautionary Statements</b>
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

**Hazards Not Otherwise Classified**

<b>Other Criteria</b>	<b>Hazard Statements/Precautionary Statement</b>	<b>Signal Word</b>	<b>Pictograms</b>
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

**Section 3: Composition/Information on Ingredients**

<b>CAS #</b>	<b>Chemical Name</b>	<b>%(weight)</b>
67-64-1	acetone	50%
646-06-0	1,3-dioxolane	34%
109-87-5	dimethoxymethane	16%

## 8309-P

## CONFORMAL COATING STRIPPER PEN

**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
<b>IF ON SKIN (or hair)</b>	P303 + P361 + P353
<b>Immediate Symptoms</b>	<i>dry skin, redness, pain, (see also inhalation symptoms)</i>
<b>Response</b>	Take off immediately all contaminated clothing. Rinse skin with water or shower.
<b>IF IN EYES</b>	P305 + P351 + P338, P337 + P313
<b>Immediate Symptoms</b>	<i>severe irritation, redness, pain, blurred vision</i>
<b>Response</b>	Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  If eye irritation persists: Get medical advice or attention
<b>IF INHALED</b>	P304 + P340, P312
<b>Immediate Symptoms</b>	<i>cough, sore throat, headache, drowsiness, dizziness, confusion, unconsciousness</i>
<b>Response</b>	Remove person to fresh air (out of the contaminated zone) and keep comfortable for breathing.  Call a POISON CENTRE or doctor if you feel unwell.
<b>IF SWALLOWED</b>	P301 + P330, P331, P308 + P313
<b>Immediate Symptoms</b>	<i>nausea, weakness, abdominal pain, vomiting, (see also inhalation symptoms)</i>
<b>Response</b>	Rinse mouth. Do NOT induce vomiting.  IF exposed or concerned: Get medical advice or attention.

**Section 5: Fire-Fighting Measures**

<b>Extinguishing Media</b>	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
<b>Specific Hazards</b>	The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ).
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

**8309-P****CONFORMAL COATING STRIPPER PEN****Section 6: Accidental Release Measures**

<b>Personal Protection</b>	See personal protection equipment in Section 8.
<b>Precautions for Response</b>	Avoid breathing the vapors. Remove or keep away all sources of ignition or extreme heat.
<b>Environmental Precautions</b>	Prevent spill from entering drains and waterways.
<b>Containment</b>	Not applicable
<b>Cleaning</b>	Place inert absorbent pads directly on the spill. Let absorb and wipe clean. Collect the contaminated pad in a sealable, solvent-resistant container. Wash the spill area with soap and water to remove remaining residues.  <b>RECOMMENDATION:</b> Use a grounded stainless steel or carbon steel container.
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

**Section 7: Handling and Storage**

<b>Prevention</b>	Keep out of reach of children.  Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.  Avoid breathing vapors. Use only outdoors or in a well-ventilated area.  Keep cap tightly closed.
<b>Handling</b>	Wear protective gloves.  Wash hands thoroughly after handling.
<b>Storage</b>	Store in a well-ventilated area. Keep cool.  Store locked up.

**Section 8: Exposure Controls/Personal Protection**
**Substances with Occupational Exposure Limit Values**

<b>Chemical Name</b>	<b>Country</b>	<b>Long Term Exposure Limits (PEL)</b>	<b>Short Term Exposure Limits (STEL)</b>
acetone	ACGIH	500 ppm	750 ppm
	U.S.A. OSHA PEL	1 000 ppm	Not established
	Canada AB	500 ppm	750 ppm
	Canada BC	250 ppm	500 ppm
	Canada ON	500 ppm	750 ppm
	Canada QC	750 ppm	1 000 ppm
1,3-dioxolane	ACGIH <sup>a)</sup>	20 ppm	Not established
	U.S.A. OSHA PEL	Not established	Not established
	Canada AB	20 ppm	Not established
	Canada BC <sup>b)</sup>	20 ppm	Not established
	Canada ON	20 ppm	Not established
	Canada QC	Not established	Not established
dimethoxymethane	ACGIH <sup>c)</sup>	1 000 ppm	Not established
	U.S.A. OSHA PEL	1 000 ppm	3 100 ppm
	Canada AB	1 000 ppm	3 100 ppm
	Canada BC	1 000 ppm	1 250 ppm
	Canada ON	1 000 ppm	Not established
	Canada QC	1 000 ppm	3 110 ppm

*Note:* The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS<sup>2</sup> database and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

- a) Hematologic effect
- b) Adverse reproductive effect
- c) Eye irritation; CNS impairment

**Engineering Controls**
**Ventilation**

Keep airborne concentrations below the occupational exposure limits (OEL).

*Section continued on the next page*

**8309-P****CONFORMAL COATING STRIPPER PEN****Personal Protective Equipment****Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Use safety glasses with lateral protection (side shields).

**Skin Protection**

For incidental contacts, use neoprene, natural latex rubber, or other chemically resistant gloves.

**Respiratory Protection**

For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

**General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

**8309-P**
**CONFORMAL COATING STRIPPER PEN**
**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid	<b>Lower Flammability Limit</b> <sup>c)</sup>	2.7%
<b>Appearance</b>	Colorless	<b>Upper Flammability Limit</b> <sup>c)</sup>	16.5%
<b>Odor</b>	Ketone-like	<b>Vapor Pressure @20 °C</b> <sup>b)</sup>	221 hPa [166 mmHg]
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	>2.01 (Air = 1)
<b>pH</b>	Not available	<b>Relative Density @25 °C</b>	0.89
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Miscible
<b>Initial Boiling Point</b>	42 °C [107 °F]	<b>Partition Coefficient n-octanol/water</b>	Not available
<b>Flash Point</b> <sup>a)</sup>	-30 °C [-22 °F]	<b>Auto-ignition Temperature</b>	250 °C [482 °F]
<b>Evaporation Rate</b>	Not available	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Flammable	<b>Viscosity @40 °C</b>	<20.5 mm <sup>2</sup> /s

a) Closed cup value

b) Calculated using Raoult's Law

c) Calculated using LeChatelier Principal

**Section 10: Stability and Reactivity**

<b>Reactivity</b>	Not available
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Avoid flames, sparks, other ignition sources and incompatible substances.
<b>Incompatibilities</b>	Phosphorous oxychloride, strong oxidizing agents, strong bases, strong acids
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.



## 8309-P

## CONFORMAL COATING STRIPPER PEN

## Section 11: Toxicological Information

## Summary of Effects and Symptoms by Routes of Exposure

<b>Eyes</b>	Causes redness, serious eye irritation, pain and/or blurred vision.
<b>Skin</b>	May cause dry skin, redness, and/or pain. (see also inhalation symptoms).
<b>Inhalation</b>	May cause cough, sore throat, headache, drowsiness, dizziness, and/or confusion. Severe overexposure may lead to unconsciousness.
<b>Ingestion</b>	May cause nausea, weakness, abdominal pain, and/or vomiting. (see also inhalation symptoms)
<b>Chronic</b>	Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin.

## Acute Toxicity (Lethal Exposure Concentrations)

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
acetone	5 800 mg/kg Rat	20 mL/kg Rabbit <sup>a)</sup>	16 000 ppm 4 h Rat <sup>a)</sup>
1,3-dioxolane	5 200 mg/kg Rat	15 000 mg/kg Rat	20 650 mg/m <sup>3</sup> 4 h Rat
dimethoxymethane	6 423 mg/kg Rat	Not available	57 mg/L 7 h Rat

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA were consulted. The data from supplier SDS were also consulted.

a) Supplier safety data sheet

**8309-P****CONFORMAL COATING STRIPPER PEN****Other Toxicological Effects**

<b>Skin corrosion/irritation</b>	Based on available data, the classification criteria are not met.
<b>Serious eye damage/irritation</b>	Acetone and 1,3-dioxolane are known serious eye irritants.
<b>Sensitization</b> (allergic reactions)	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b> (risk of cancer)	None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity</b> (risk to sex functions)	Based on available data, the classification criteria are not met.
<b>Teratogenicity</b> (risk of fetus malformation)	Based on available data, the classification criteria are not met.
<b>STOT-single exposure</b>	Acetone can affect the central nervous system by inhalation causing drowsiness or dizziness.
<b>STOT-repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met. There are no category 1 components.

**Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Acetone does not meet classification criteria for aquatic environmental toxicants with LC50 and EC50 of >100 mg/L.

- Acetone has a minimal LC50 96 h of 5 540 mg/L for *Oncorhynchus mykiss* (rainbow trout) and an EC50 48 h of 13 500 mg/L for *Daphnia magna* (water flea).

1,3-dioxolane and dimethoxymethane is not classifiable as an environmental toxicant.

**Acute Ecotoxicity**

Available toxicity data does not meet classification thresholds.

*Section continue on the next page*

**8309-P****CONFORMAL COATING STRIPPER PEN****Chronic Ecotoxicity**

Available toxicity data does not meet classification thresholds.

**Biodegradability**

Not available

**Other Effects**

Volatile Organic Compound (VOC) content = 50% [446 g/L] by VOC-Exemption

**Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

**Section 14: Transport Information****Ground****Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations);  
**USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes 30 mL and under

**Excepted Quantity**Document as class **E2***FOR REFERENCE ONLY***UN number:** UN1993**Shipping Name:** Flammable liquid, n.o.s.  
(acetone, 1,3-dioxolane, dimethoxymethane)**Class:** 3**Packing Group:** II**Marine Pollutant:** No**Air****Refer to ICAO-IATA Dangerous Goods Regulations.**

Sizes 30 mL and under

**Excepted Quantity**Document as class **E2**On air waybill, write:  
"Dangerous Goods in  
Excepted Quantities".*FOR REFERENCE ONLY***UN number:** UN1993**Shipping Name:** Flammable liquid, n.o.s.  
(acetone, 1,3-dioxolane, dimethoxymethane)**Class:** 3**Packing Group:** II**Marine Pollutant:** No*Section continued on the next page*

**8309-P**

**CONFORMAL COATING STRIPPER PEN**

Sea

**Refer to IMDG regulations.**

Sizes 30 mL and under  
**Excepted Quantity**  
Document as class **E2**



*FOR REFERENCE ONLY*

**UN number:** UN1993  
**Shipping Name:** Flammable liquid, n.o.s.  
(acetone, 1,3-dioxolane, dimethoxymethane)  
**Class:** 3  
**Packing Group:** II  
**Marine Pollutant:** No

**Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.**

**Section 15: Regulatory Information**

**Canada**

**Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL.

**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.


**USA**

**Other Classifications**

**HMIS® RATING**

<b>HEALTH:</b>	<b>*</b>	<b>2</b>
<b>FLAMMABILITY:</b>		<b>3</b>
<b>PHYSICAL HAZARD:</b>		<b>0</b>
<b>PERSONAL PROTECTION:</b>		

**NFPA® 704 CODES**



*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

*Section continued on the next page*

**8309-P****CONFORMAL COATING STRIPPER PEN****CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains acetone (CAS# 67-64-1), which is subject to the CERCLA reporting requirements at the 5 000 lb (2 268 kg) threshold.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any substances known to be listed in California.

**Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

**Section 16: Other Information**

<b>SDS Prepared by</b>	MG Chemical's Regulatory Department
<b>Date of Revision</b>	06 March 2020
<b>Supersedes</b>	06 May 2019
<b>Reason for Changes:</b>	Update to the emergency phone number information.

**Reference**

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

*Section continued on the next page*

**8309-P****CONFORMAL COATING STRIPPER PEN****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

*Head Office*  
9347-193rd Street  
Surrey, British Columbia, Canada  
V4N 4E7

**Disclaimer**

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.