

RTV122

SAFETY DATA SHEET

1. Identification

Product identifier: RTV122

Other means of identification

Synonyms: SILICONE RUBBER SEALANT-WHITE

Recommended use and restriction on use

Recommended use: Silicone Elastomer

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information : Momentive Performance Materials USA LLC
2750 Balltown Road,
Niskayuna, NY 12309

Contact person : commercial.services@momentive.com

Telephone : General information
+1-800-295-2392

Emergency telephone number
Supplier : CHEMTREC
1-800-424-9300

2. Hazard(s) identification

Hazard Classification

Health Hazards

Skin sensitizer	Category 1
Toxic to reproduction	Category 2

Unknown toxicity - Health

Acute toxicity, oral	0 %
Acute toxicity, dermal	0 %
Acute toxicity, inhalation, vapor	0 %
Acute toxicity, inhalation, dust or mist	0 %

Label Elements

Hazard Symbol:

RTV122



Signal Word: Warning

Hazard Statement: H317; May cause an allergic skin reaction.
H361; Suspected of damaging fertility or the unborn child.

Precautionary Statements

Prevention: Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Response: IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result in GHS classification: None.

Substance(s) formed under the conditions of use: Generates methanol during cure.

3. Composition/information on ingredients
--

RTV122

Mixtures

Chemical Identity	CAS number	Content in percent (%)*	Notes
(1) TITANIUM DIOXIDE	13463-67-7	1 - <5%	# This substance has workplace exposure limit(s).
Hexamethyldisilazane	999-97-3	1 - <5%	No data available.
Octamethylcyclotetrasiloxane	556-67-2	0.1 - <1%	# This substance has workplace exposure limit(s).
Aminoethyl aminopropyl trimethoxy silane	1760-24-3	0.1 - <1%	# This substance has workplace exposure limit(s).
Dibutyltin Diacetate(34% as Tin)	1067-33-0	0.1 - <1%	# This substance has workplace exposure limit(s).
(1) Silica	7631-86-9	0.1 - <1%	# This substance has workplace exposure limit(s).
(1) Aluminum oxide	1344-28-1	0.1 - <1%	# This substance has workplace exposure limit(s).

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

(1) The respirable particle(s) listed above are inextricably bound within the polymer matrix, and therefore does not present an inhalation hazard during normal use of this product. Tooling or machining of the cured product (sanding, cutting, milling) may release hazardous, respirable substances.

4. First-aid measures

Ingestion:	If swallowed, do NOT induce vomiting. Give a glass of water. Do not give victim anything to drink if he is unconscious. Get medical attention if any discomfort continues.
Inhalation:	If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.
Skin Contact:	To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water.
Eye contact:	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

RTV122

Most important symptoms/effects, acute and delayed

Symptoms:	Treatment is symptomatic and supportive.
Hazards:	No data available.

Indication of immediate medical attention and special treatment needed

Treatment:	No data available.
-------------------	--------------------

5. Fire-fighting measures

General Fire Hazards:	No data available.
------------------------------	--------------------

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	All standard extinguishing agents are suitable.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:	No data available.
--	--------------------

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Avoid contact with skin and eyes. Use only in well-ventilated areas. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the finger and hands. Keep out of reach of children. See Section 8 of the SDS for Personal Protective Equipment.
Methods and material for containment and cleaning up:	Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

7. Handling and storage

Precautions for safe handling:	Sensitivity to static discharge is not expected.
---------------------------------------	--

RTV122

Conditions for safe storage, including any incompatibilities: Keep container closed.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
(1) TITANIUM DIOXIDE	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2015)
(1) TITANIUM DIOXIDE - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	10 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	10 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
(1) TITANIUM DIOXIDE - Particulate.	ST ESL	50 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
	AN ESL	5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
(1) TITANIUM DIOXIDE - Total dust.	TWA PEL	10 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
(1) TITANIUM DIOXIDE - Respirable fraction.	TWA PEL	5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
(1) TITANIUM DIOXIDE - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
(1) TITANIUM DIOXIDE - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
(1) TITANIUM DIOXIDE - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
(1) TITANIUM DIOXIDE	IDLH	5,000 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
Dibutyltin Diacetate(34% as Tin) - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2015)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2015)
	REL	0.1 mg/m3	US. NIOSH. Pocket Guide to Chemical Hazards, as amended (2010)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	0.1 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	0.1 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
Dibutyltin Diacetate(34% as Tin) - Particulate.	ST ESL	1 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
	AN ESL	0.1 µg/m3	US. Texas. Effects Screening Levels (Texas

RTV122

			Commission on Environmental Quality), as amended (11 2016)
Dibutyltin Diacetate(34% as Tin) - as Sn	TWA PEL	0.1 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	STEL	0.2 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
Dibutyltin Diacetate(34% as Tin)	IDLH	25 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
(1) Silica	REL	6 mg/m3	US. NIOSH. Pocket Guide to Chemical Hazards, as amended (2010)
	TWA	6 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	6 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
(1) Silica - Particulate.	ST ESL	27 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
	AN ESL	2 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
(1) Silica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	IDLH	3,000 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
(1) Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2015)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
(1) Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
(1) Aluminum oxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
(1) Aluminum oxide - Total dust.	TWA	10 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
(1) Aluminum oxide - Respirable fraction.	TWA	5 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
(1) Aluminum oxide - Total dust.	TWA	10 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
(1) Aluminum oxide - Particulate.	AN ESL	5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
	ST ESL	50 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
(1) Aluminum oxide - Respirable fraction.	TWA PEL	5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
(1) Aluminum oxide - Total dust.	TWA PEL	10 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
(1) Aluminum oxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)

RTV122

		air	
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
(1) Aluminum oxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Octamethylcyclotetrasiloxane	TWA	5 ppm	
Octamethylcyclotetrasiloxane - Vapor.	ST ESL	1,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
	AN ESL	100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
Octamethylcyclotetrasiloxane	TWA	10 ppm	US. OARS. WEELs Workplace Environmental Exposure Level Guide, as amended (2014)

This product contains one or more substances with an occupational exposure limit. However, the respirable particle(s) of this/these substance(s) are inextricably bound within the polymer matrix. Therefore, we do not expect an exposure to this/these substance(s) during normal use of this product. Tooling or machining of the cured product (sanding, cutting, milling) may release hazardous, respirable substances.

Appropriate Engineering Controls

Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

General information: No data available.

Eye/face protection: Safety glasses with side shields

Skin Protection

Hand Protection: Use chemical-resistant, impervious gloves.

Other: Wear suitable protective clothing and eye/face protection.

Respiratory Protection: If inhalation exposure is expected, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

Hygiene measures: It is good practice in industrial hygiene to avoid contact with solvents by using appropriate protective measures whenever possible.

9. Physical and chemical properties

Appearance

Physical state: solid

Form: Paste

Color: White

Odor: Ammonia.

Odor threshold: No data available.

pH: Not applicable

Melting point/freezing point: Not applicable

Initial boiling point and boiling range: Not applicable

RTV122

Flash Point:	ca. 165.5 °C (Tagliabue Open Cup)
Evaporation rate:	< 1
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper:	No data available.
Explosive limit - lower:	No data available.
Heat of combustion:	No data available.
Vapor pressure:	No data available.
Vapor density:	Negligible
Density:	ca. 1.04 g/cm ³
Relative density:	ca. 1.04
Solubility(ies)	
Solubility in water:	Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water) Log Pow:	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
SADT:	No data available.
Viscosity, dynamic:	No data available.
Viscosity, kinematic:	> 20.5 mm ² /s (40 °C)
VOC:	20 g/l ;

10. Stability and reactivity

Reactivity:	No dangerous reaction if used as recommended.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid:	None known.
Incompatible Materials:	None known.
Hazardous Decomposition Products:	Carbon dioxide Silicon dioxide. Ammonia. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.

RTV122

11. Toxicological information

Information on likely routes of exposure

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 38,243.44 mg/kg

Specified substance(s):

(1) TITANIUM DIOXIDE LD 50 (Rat): > 10,000 mg/kg

Hexamethyldisilazane LD 50 (Rat): 870 mg/kg

Octamethylcyclotetrasiloxane LD 50 (Rat): > 4,800 mg/kg

Aminoethyl aminopropyl trimethoxy silane LD 50 (Rat): 2,995 mg/kg

(1) Silica LD 50 (Rat): > 15,000 mg/kg

Dermal

Product: ATEmix: 13,187.39 mg/kg

RTV122

Specified substance(s):

(1) TITANIUM DIOXIDE LD 50 (Rabbit): > 10,000 mg/kg

Octamethylcyclotetrasiloxane LD 50 (Rat): > 2,375 mg/kg

Aminoethyl aminopropyl trimethoxy silane LD 50 (Rabbit): > 2,000 mg/kg

Inhalation

Product: ATEmix: 483.54 mg/l

Specified substance(s):

(1) TITANIUM DIOXIDE LC50 (Rat): > 6.8 mg/l

Octamethylcyclotetrasiloxane LC50 (Rat): 36 mg/l

Repeated dose toxicity

Product: No data available.

Specified substance(s):

Aminoethyl aminopropyl trimethoxy silane NOAEL (Rat, Oral, 28 d): ≥ 500 mg/kg

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Octamethylcyclotetrasiloxane OECD-Guideline 404 (Acute Dermal Irritation/Corrosion) (Rabbit): Slightly irritating.

Specified substance(s):

Aminoethyl aminopropyl trimethoxy silane OECD Test Guideline 404 (Rabbit): No skin irritation

Specified substance(s):

(1) Silica (Rabbit): No skin irritation

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

(1) TITANIUM DIOXIDE No eye irritation

Specified substance(s):

RTV122

Octamethylcyclotetrasiloxane	OECD-Guideline 405 (Acute Eye Irritation/Corrosion) (Rabbit): Non irritating
Specified substance(s):	
Aminoethyl aminopropyl trimethoxy silane	OECD Test Guideline 405 (Rabbit): Strongly irritating.

Respiratory or Skin Sensitization

Product: Bühler-Patch-Test skin sensitisation on guinea pigs, OECD Test Guideline 406 (Guinea Pig): negative Test results are based on analogy with a similar material.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified **US. National Toxicology Program (NTP) Report on Carcinogens:**
No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:
No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

Specified substance(s):
Octamethylcyclotetrasiloxane
Ames-Test (OECD-Guideline 471 (Genetic Toxicology: Salmonella typhimurium, Reverse Mutation Assay)): negative (not mutagenic)
Mouse Lymphoma Assay (OECD Guideline 476): negative (not mutagenic)

In vivo
Product: No data available.

Specified substance(s):
Octamethylcyclotetrasiloxane
Chromosomal aberration (OECD-Guideline 474 (Genetic Toxicology: Micronucleus Test)) Inhalation (Rat, male and female): negative

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

RTV122

Product: No data available.

RTV122

Other effects:

This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive. ,Ammonia released during curing.,Contains octamethylcyclotetrasiloxane which may cause reproductive effects based on animal data.

Octamethylcyclotetrasiloxane

Ingestion: Rodents given large doses via oral gavages of Octamethylcyclotetrasiloxane (1600 mg/kg day, 14 days) developed increased liver weights relative to unexposed control animals due to hepatocellular hyperplasia (increased number of liver cells which appear normal) as well as hypertrophy (increased cell size).

Inhalation: In inhalation studies, laboratory rodents exposed to Octamethylcyclotetrasiloxane (300 ppm five days week, 90 days) developed increased liver weights in female animals relative to unexposed control animals. When the exposure was stopped, liver weights returned to normal. Microscopic examination of the liver cells did not show any evidence of pathology. Inhalation studies utilizing laboratory rabbits and guinea pigs showed no effects on liver weights. Inhalation exposures typical of industrial usage (5-10 ppm) showed no toxic effects in rodents.

Range finding reproductive studies were conducted (whole body inhalation, 70 days prior to mating, through mating, gestation and lactation) with Octamethylcyclotetrasiloxane (D4). Rats were exposed to 70 and 700 ppm. In the 700 ppm group, there was a statistically significant reduction in mean litter size and in implantation sites. No D4 related clinical signs were observed in the pups and no exposure related pathological findings were found.

Interim results from a two generation reproductive study in rats exposed to 500 and 700 ppm D4 (whole body inhalation, 70 days prior to mating, through mating, gestation and lactation) resulted in a statistically significant decrease in live mean litter size as well as extended periods of off-spring delivery (dystocia). These results were not observed at the 70 and 300ppm dosing levels.

Preliminary results from an ongoing 24-month combined chronic/oncogenicity study in rats exposed to 10, 30, 150, or 700 ppm D4 showed test-article related effects in the kidney (male and female) and uterus of rats exposed for 12 to 24 months. These effects include increased kidney weight and severity of chronic nephropathy, increased uterine weight, increased incidence of endometrial cell hyperplasia, and an increased incidence of endometrial adenomas. All of these effects are limited to the 700 ppm exposure group.

These results have been shown to be rat-specific. Further studies are ongoing.

In developmental toxicity studies, rats and rabbits were exposed to Octamethylcyclotetrasiloxane at concentrations up to 700 ppm and 500 ppm respectively. No teratogenic effects (birth defects) were observed in either study.

RTV122

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

(1) TITANIUM DIOXIDE LC0 (Leuciscus idus, 48 h): > 1,000 mg/l

Aminoethyl aminopropyl trimethoxy silane LC50 (Lepomis macrochirus): > 100 mg/l

(1) Silica LC0 (Brachydanio rerio, 96 h): 5,000 mg/l

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Aminoethyl aminopropyl trimethoxy silane EC50 (Daphnia magna, 48 h): 87.4 mg/l

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

(1) Silica LC0 (Brachydanio rerio, 4 d): 5,000 mg/l

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Specified substance(s):

Aminoethyl aminopropyl trimethoxy silane EC50 (Algae (Pseudokirchneriella subcapitata), 96 h): 8.8 mg/l
NOEC (Algae (Pseudokirchneriella subcapitata)): 3.1 mg/l

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

(1) TITANIUM DIOXIDE 0 %

RTV122

Octamethylcyclotetrasiloxane 3.7 % (29 d, 310 Ready Biodegradability - CO₂ in Sealed Vessels (Headspace Test)) Not readily biodegradable.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Octamethylcyclotetrasiloxane Fathead Minnow, Bioconcentration Factor (BCF): 12.40

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Hexamethyldisilazane Log Kow: Not applicable

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

(1) TITANIUM DIOXIDE No data available.
Hexamethyldisilazane No data available.
Octamethylcyclotetrasiloxane No data available.
Aminoethyl aminopropyl trimethoxy silane No data available.
Dibutyltin Diacetate(34% as Tin) No data available.
(1) Silica No data available.
(1) Aluminum oxide No data available.

Other adverse effects: No data available.

13. Disposal considerations

General information:

The generation of waste should be avoided or minimized wherever possible. Do not discharge into drains, water courses or onto the ground. See Section 8 for information on appropriate personal protective equipment.

Disposal instructions:

Disposal should be made in accordance with federal, state and local regulations.

Contaminated Packaging:

No data available.

RTV122

14. Transport information

DOT

Not regulated.

IMDG

Not regulated.

IATA

Not regulated.

Special precautions for user:

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Serious eye damage or eye irritation

Respiratory or Skin Sensitization

Reproductive toxicity

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

None present or none present in regulated quantities.

SARA 311/312 Hazardous Chemical

Chemical Identity

Threshold Planning Quantity

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

RTV122

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING: This product can expose you to chemicals including Methanol, which is [are] known to the State of California to cause birth defects or other reproductive harm.

For more information go to www.P65Warnings.ca.gov.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

METHYLPOLYSILOXANE

Treated Fumed Silica

Polydimethylsiloxane

(1) TITANIUM DIOXIDE

Siloxanes and Silicones, di-Me, polymers with Me silsesquioxanes,
hydroxy-terminated

Hexamethyldisilazane

US. Massachusetts RTK - Substance List

Chemical Identity

1,2-Ethylenediamine

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

(1) TITANIUM DIOXIDE

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

RTV122

Inventory Status:

Australia AICS:	y (positive listing)	Remarks: None.
Canada DSL Inventory List:	y (positive listing)	Remarks: None.
EU EINECS List:	y (positive listing)	Remarks: None.
Japan (ENCS) List:	n (Negative listing)	Remarks: None.
China Inventory of Existing Chemical Substances:	y (positive listing)	Remarks: None.
Korea Existing Chemicals Inv. (KECI):	y (positive listing)	Remarks: None.
Canada NDSL Inventory:	n (Negative listing)	Remarks: None.
Philippines PICCS:	y (positive listing)	Remarks: None.
US TSCA Inventory:	y (positive listing)	Remarks: None.
New Zealand Inventory of Chemicals:	y (positive listing)	Remarks: None.
Taiwan. Taiwan inventory (CSNN):	y (positive listing)	Remarks: None.

16. Other information, including date of preparation or last revision

HMIS Hazard ID

Health	*	2
Flammability		0
Physical Hazards		1
PERSONAL PROTECTION		

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

Issue Date: 04/20/2020

Revision Date: No data available.

Version #: 1.6

Further Information: No data available.

RTV122

Disclaimer:

Notice to reader

Unless otherwise specified in section 1, Momentive products are intended for use in the manufacture and/or formulation of products and are not intended for direct consumer use. These products are not intended for long-lasting (> 30 days) implantation, injection or direct ingestion into the human body, nor for use in the manufacture of multiple use contraceptives. Keep out of the reach of children.

Further Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

® and TM indicate trademarks owned by or licensed to Momentive.