

A.  
System  
Overview

B1.  
Cable  
Ties

B2.  
Cable  
Accessories

B3.  
Stainless  
Steel Ties

C1.  
Wiring  
Duct

C2.  
Surface  
Raceway

C3.  
Abrasion  
Protection

C4.  
Cable  
Management

D1.  
Terminals

D2.  
Power  
Connectors

D3.  
Grounding  
Connectors

E1.  
Labeling  
Systems

E2.  
Labels

E3.  
Pre-Printed  
& Write-On  
Markers

E4.  
Permanent  
Identification

E5.  
Lockout/  
Tagout  
& Safety  
Solutions

F.  
Index




## Locking Fork Terminals, Nylon Insulated – Non-Funnel Entry

### Type PN-LF

- Continuously molded design provides reliable, consistent performance through the applicator for a high quality termination every time
- Snap in place for secure connection
- Fork design provides for fast and easy installation, without the need to remove fastener
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications

- Internal barrel serrations assure good wire contact and maximum tensile strength
- UL Flammability UL 94V-2/HB, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486A/B



| Part Number  | Wire Range  | Color Code | Stock Thickness (In.) | Max. Ins. (In.) | Stud Size | Figure Dimensions (In.) |      |      | CA9 Series Crimp Die | CA-800/EZ Series Crimp Die | Pieces Per Reel |
|--------------|-------------|------------|-----------------------|-----------------|-----------|-------------------------|------|------|----------------------|----------------------------|-----------------|
|              |             |            |                       |                 |           | L                       | W    | C    |                      |                            |                 |
| PN18-6LF-3K  | 22 – 18 AWG | Red        | 0.03                  | 0.145           | #6        | 0.82                    | 0.27 | 0.19 | CD9-1A               | CD-800-1                   | 3000            |
| PN18-8LF-3K  |             |            |                       |                 | #8        | 0.89                    | 0.29 | 0.23 |                      |                            | 3000            |
| PN18-10LF-3K |             |            |                       |                 | #10       | 0.89                    | 0.33 | 0.23 |                      |                            | 3000            |
| PN14-6LF-3K  | 16 – 14 AWG | Blue       | 0.03                  | 0.162           | #6        | 0.85                    | 0.25 | 0.18 | CD9-2A               | CD-800-2                   | 3000            |
| PN14-8LF-3K  |             |            |                       |                 | #8        | 0.92                    | 0.29 | 0.23 |                      |                            | 3000            |
| PN14-10LF-3K |             |            |                       |                 | #10       | 0.92                    | 0.33 | 0.23 |                      |                            | 3000            |
| PN10-6LF-2K  | 12 – 10 AWG | Yellow     | 0.04                  | 0.225           | #6        | 1.02                    | 0.30 | 0.21 | CD9-3B               | CD-800-3                   | 2000            |
| PN10-8LF-2K  |             |            |                       |                 | #8        | 1.05                    | 0.30 | 0.21 |                      |                            | 2000            |
| PN10-10LF-2K |             |            |                       |                 | #10       | 1.05                    | 0.34 | 0.21 |                      |                            | 2000            |

For applicator information, see page D1.143.




## Locking Fork Terminals, Nylon Insulated – Funnel Entry

### Type PNF-LF

- Continuously molded design provides reliable, consistent performance through the applicator for a high quality termination every time
- Snap in place for secure connection
- Fork design provides for fast and easy installation, without the need to remove fastener
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications

- Internal barrel serrations assure good wire contact and maximum tensile strength
- UL Flammability UL 94V-2/HB, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486A/B



| Part Number    | Wire Range  | Color Code | Stock Thickness (In.) | Max. Ins. (In.) | Stud Size | Figure Dimensions (In.) |      |      | CA9 Series Crimp Die | CA-800/EZ Series Crimp Die | Pieces Per Reel |
|----------------|-------------|------------|-----------------------|-----------------|-----------|-------------------------|------|------|----------------------|----------------------------|-----------------|
|                |             |            |                       |                 |           | L                       | W    | C    |                      |                            |                 |
| PNF18-6LF-3K   | 22 – 18 AWG | Red        | 0.03                  | 0.145           | #6        | 0.85                    | 0.27 | 0.19 | CD9-1A               | CD-800-1                   | 3000            |
| PNF18-6LFW-3K  |             |            |                       |                 | #6        | 0.85                    | 0.29 | 0.19 |                      |                            | 3000            |
| PNF18-8LF-3K   |             |            |                       |                 | #8        | 0.89                    | 0.29 | 0.23 |                      |                            | 3000            |
| PNF18-10LF-3K  | 16 – 14 AWG | Blue       | 0.03                  | 0.162           | #10       | 0.89                    | 0.33 | 0.23 | CD9-2A               | CD-800-2                   | 3000            |
| PNF14-6LF-3K   |             |            |                       |                 | #6        | 0.85                    | 0.25 | 0.18 |                      |                            | 3000            |
| PNF14-8LF-3K   |             |            |                       |                 | #8        | 0.92                    | 0.29 | 0.23 |                      |                            | 3000            |
| PNF14-10LFN-3K | 12 – 10 AWG | Yellow     | 0.04                  | 0.225           | #10       | 0.92                    | 0.28 | 0.23 | CD9-3B               | CD-800-3                   | 3000            |
| PNF14-10LF-3K  |             |            |                       |                 | #10       | 0.92                    | 0.33 | 0.23 |                      |                            | 3000            |
| PNF10-6LF-2K   |             |            |                       |                 | #6        | 1.02                    | 0.30 | 0.21 |                      |                            | 2000            |
| PNF10-8LF-2K   | 12 – 10 AWG | Yellow     | 0.04                  | 0.225           | #8        | 1.05                    | 0.30 | 0.21 | CD9-3B               | CD-800-3                   | 2000            |
| PNF10-10LF-2K  |             |            |                       |                 | #10       | 1.05                    | 0.34 | 0.21 |                      |                            | 2000            |
| PNF10-14LF-2K  |             |            |                       |                 | 1/4"      | 1.19                    | 0.46 | 0.32 |                      |                            | 2000            |

For applicator information, see page D1.143.